



RocketLinx® ES7510-XT

Part Number: 32046-3



KEY FEATURES AND BENEFITS::

- Integrate IP cameras, access points and other PoE devices
- Eight 10/100BASE-TX PoE Plus ports and two Gigabit RJ45/SFP combo ports featuring Digital Diagnostic Monitoring (DDM)
- PoE ports support both IEEE 802.3af (15.4W) and the latest high power IEEE 802.3at standards (30W)
- Easy setup and administration via Netvision application, web page or Cisco-like command line interfaces
- Advanced redundant ring support with 5ms recovery time, for up to 4 x 100M rings plus two Gigabit uplink rings
- Advanced security features include Port Security, Access IP List, HTTPS and SSH login
- SNMP and IEEE 802.1AB LLDP for network management
- Tag-VLAN supporting multiple VLAN traffic isolation
- LACP port trunking for bandwidth aggregation to support video surveillance
- Redundant DC power inputs and multiple event relay output for advanced device alarm control
- Extended operating temperature -40° to 75°C
- NEMA TS2 certified
- RoHS2 compliant under CE
- IPv6 support

POE SWITCH

PRODUCT DESCRIPTION::

PoE Plus Supporting High Power Devices

The Comtrol RocketLinx ES7510-XT managed industrial PoE Plus switch is designed to meet the high power and advanced management needs of critical traffic applications such as real-time IP video surveillance and wireless communication utilizing outdoor rated IP cameras and high power IEEE 802.11 access points. Featuring a rugged design for harsh environments, intuitive web, CLI, SNMP management options, power scheduling and eight fully compliant IEEE 802.3at PoE injector ports, the ES7510-XT is easily installed in industrial settings and traffic cabinets supporting even the most power intensive devices such as IP cameras with heaters and pan/tilt/zoom controls.

Innovative Power Control

In addition to functioning as a PoE power source, the ES7510-XT includes advanced device controls, ensuring that power consumption does not exceed parameters defined by the user. This includes power budget control functions to limit power output on

devices not reporting correct consumption rates and device priority options to guarantee power to critical devices while avoiding power supply overloads.

Management and Security

The RocketLinx ES7510-XT is equipped with full Layer 2+ management capabilities to provide the most flexible network configuration and control. Features like Link Aggregation Control Protocol allow grouping of multiple ports to enhance bandwidth and provide load balancing while Port-Based VLAN, QoS, IGMP Snooping, and Rate Control features enable optimum control over the network environment. In addition to the full array of management capabilities, the ES7510-XT also supports the most advanced security features to protect the network and guarantee secure, reliable data transmission. Fault relay and e-mail notification of event alarms, DHCP supporting IP and MAC binding, IEEE 802.1X network access control, SSH, and many other controls are included to make secure administration and management a simple task.



connect. communicate. control.

ROCKETLINX SPECIFICATIONS ::

HARDWARE

Network Interface
 10/100BASE-TX PoE Plus
 10/100/100BASE-TX
 100BASE-FX, 1000BASE-SX/LX/LHX/XD/ZX Gigabit Fiber

Connector Type
 Eight - RJ45
 Two - RJ45/SFP Combo

Enclosure
 IP30 Grade Steel Metal Case with Aluminum panel housing for heat dissipation

Installation Method
 DIN rail
 Wall or panel mount

LED Indicators
 Power 1/2
 System Status
 Ring Status
 DI and DO Status
 Ethernet Port Link/Activity
 PoE Status
 Gigabit Port Link/Activity

Digital Input (DI)/Digital Output (DO)
 4-pin screw terminal block with one DI and one DO (Dry Relay Output)

Serial Console Port
 One RJ45 RS-232 (TXD, RXD, Signal GND), Baud Rate: 9600bps, Data Bits: 8, Parity: None, Stop Bits: 1, Flow Control: None

Thermal Monitoring
 Embedded board-level thermal detector for main-chip temperature monitoring

Dimensions 5.0" x 6.3" x 3.7"
 12.7 x 16 x 9.4 cm

Product Weight 1.85 lbs
 1.29 kg

ETHERNET SPECIFICATIONS

Number of Ports
 Ten: 8 - RJ45 and 2 - RJ45 SFP combo Gigabit uplink

RJ45
 8 RJ45: 10/100BASE-TX PoE Plus
 2 RJ45: 10/100/100BASE-TX
 Auto MDI/MDIX, Auto-Negotiation (Speed/Duplex Mode)

SFP DDM (Optional)
 100BASE-FX Fiber, 1000BASE-SX/LX/LHX/XD/ZX
 Auto MDI/MDIX, Auto-Negotiation (Speed/Duplex Mode)

Cable Types
 Cat 3, Cat 4, Cat 5, Cat 5e, Cat 6 (UTP or STP)

Link Distances
 RJ45: 100 meters
 SFP DDM: (Depends on Model: Single-Mode: 30KM, Multi-Mode: 2KM)

Port Alarm Relay Yes

Transfer Packet Size
 64 bytes to 1522 bytes (includes double VLAN tag)

Standards
 IEEE 802.3af PoE
 IEEE 802.3at LLDP PoE Plus
 IEEE 802.1AB: Link Layer Discovery Protocol (LLDP)
 IEEE 802.1D-2004: Rapid Spanning Tree Protocol (RSTP)
 IEEE 802.1p: Class of Service
 IEEE 802.1Q-2003: VLAN Tagging and GVRP
 IEEE 802.1s: Multiple Spanning Tree Protocol (MSTP)
 IEEE 802.1X: Port based network access control
 IEEE 802.3: 10BASE-T
 IEEE 802.3ab: 100BASE-TX
 IEEE 802.3ad: Port Trunking with Link Aggregation Control Protocol (LACP)
 IEEE 802.3u: 100BASE-TX Fast Ethernet and 100BASE-FX Fast Ethernet Fiber
 IEEE 802.3x: Flow Control and Back-Pressure
 IEEE 1588: Precision Time Protocol (PTP)

Internet Protocol IPv4 and IPv6

POE FEATURES

PoE Modes
 802.3af
 802.3at (2-event)
 802.3at (LLDP)
 Forced

Number of PoE Plus Injector Ports 8

PSE Type
 802.3at Type 2
 Alternative A

Maximum Power/PoE Port (Max.)
 15.4W (IEEE 802.3at)
 30W (IEEE 802.3at)

Total Power Budget (Max.) 80W at 74°C

Standard PoE Voltage Output
 Yes
 IEEE 802.3af compliant - 47-57VDC
 IEEE 802.3at compliant - 50-57VDC

PoE Control
 Enable or disable PoE, set/port PoE mode, power budget, power budget mode (auto/manual), and schedule-based PoE functions



Power Budget Warning Level Yes

PoE Powered Device Check
 Real-time status monitoring of PoE PDs with an option to reset the PoE PD

Real-time PoE Status Yes

PoE Output Pin-Out (RJ45)
 Pins 1, 2 - V+
 Pins 3, 6 - V-

PoE Scheduling
 PoE ports are configurable as On/Off by hourly/daily/weekly basis

MANAGEMENT FEATURES

Configuration and Monitoring
 Out-Band Management: Console Port with Command Line Interface (CLI) - Similar to Cisco CLI, In-Band Management: Web Interface (HTTP/HTTPS) or a Telnet/SSH console with CLI

Embedded Watchdog
 Embedded hardware watchdog timer automatically resets system if switch system failure occurs

System Upgrade/Backup
 Provides TFTP/Web interface for firmware upgrade and configuration backup/restore

SNMP
 V1, V2c, V3 with SNMP trap function, up to four trap stations

SNMP MIB
 MIB-II, Bridge MIB, VLAN MIB, IGMP MIB, Ethernet-like MIB, Control Private MIB, and RMON

Email Warning
 Automatic warning, up to four accounts by pre-defined events

System Log
 Supports both local mode and server mode

DHCP
 DHCP client, DHCP server with IP and MAC address binding, Port-based DHCP server configuration and DHCP relay agent (Option 82)

NETWORK PERFORMANCE

Back-Pressure
 IEEE 802.3x 1000Mbps Half-Duplex only

Class of Service (CoS)
 IEEE 802.1p 4 priority queues/port

Flow Control Pause Frame
 IEEE 802.3x 10/100/1000Mbps Full-Duplex

GMARP
 GARP Multicast Registration Protocol

IGMP Snooping
 V1/V2/V3 for multicast filtering and IGMP Query V1/V2; Supports unknown multicasting, Processes forwarding policies: drop, flooding, and forward to router port

IP Security
 Assign authorized IP addresses to specific port, 10 Max/port

Loop Protection
 Provides Layer 2 loop prevention through the STP, RSTP, and MSTP. Loop protection increases the efficiency of STP, RSTP, and MSTP by preventing ports from moving into a forwarding state that would result in a loop in the network

Modbus TCP/IP
 CLI support for Modbus TCP/IP communications with Function Code 4 (factory automation). Operates as slave/server device, while a typical master/client device is a host computer running appropriate through Ethernet. The Modbus TCP/IP master can read or write to the Modbus registers provided by the Modbus TCP/IP application software (SCADA/HMI system)

Packet Buffer Memory
 1Mbits

Port-Based Network Access Control
 IEEE 802.1X: Supports user authentication by the RADIUS account, password and key for the RADIUS servers (Primary and Secondary)

Port Configuration
 Port Link Speed, Link Mode, Port Status, Enable/Disable

Port Mirroring
 Online traffic monitoring on multiple selected ports

Port Security
 Assign authorized MAC addresses to specific port, 10 max/port

Port Trunk
 IEEE 802.3ad LACP with timer and static port trunk; trunk member up to 8 ports and maximum 5 trunk groups including gigabit Ethernet ports

Private VLAN
 Direct client ports in isolated/community VLAN to promiscuous port in primary VLAN

Rate Control
 Ingress filtering for broadcast, multicast, unknown DA or all packets. Egress filtering for all packet types.

Switch Technology
 32Gbps switch fabric, store/forward switch technology, 8K MAC address

System Throughput
 8.3 Mega packets/sec
 14,880pps - 10Mbps; 148,800pps - 100Mbps;
 1,488,100pps - 1000Mbps

Time Synchronization
 Supports IEEE 1588, NTP protocol with daylight saving function, and localized time sync function

Prioritization (DoS)
 802.1p CoS tag and IPv4 ToS/Diffserv information to prioritize industrial network traffic

VLAN
 IEEE 802.1Q tag VLAN with 256 (max) VLAN entries and 2K GVRP entries; 3 VLAN link modes; trunk, hybrid, and link access
 IEEE 802.1 QinQ supports double VLAN tag function for

implementing metro network topologies

NETWORK REDUNDANCY

Rapid Spanning Tree Protocol
 IEEE 802.1D-2004 Rapid Spanning Tree Protocol (RSTP)
 Compatible with legacy STP and IEEE 802.1w

Multiple Spanning Tree
 IEEE 802.1s MSTP, each MSTP instance can include one or more VLANs

Redundant Ring Technology
 Failure recovery within 5ms
 Rapid Dual Homing: Multiple uplink paths to upper switches
 Ring Trunking: Integrates port aggregate function in ring path to get higher throughput ring architecture
 Multiple Ring: Couple or multiples of up to 4 100M rings and up to 2 Gigabit rings in one switch

ELECTRICAL SPECIFICATIONS

Device Power Input Voltage (DC1/DC2) (Positive or Negative)
 802.3af 48VDC (48-57VDC)
 802.3at 53VDC (50-57VDC)

Device Power Consumption
 Without PD Load (Max.) 15W
 With PD Load (Max.) 100W

Power Connector Type
 One 4-pin terminal block for DC1/2

Power Input Redundancy
 Dual Redundant Inputs

PSU Type Passive

Reverse Polarity Protection Yes

Digital Output (Relay Output) 1

DC Input Voltage 24VDC

Current Consumption (24VDC) 0.5A maximum

Multi-Event Relay Feature
 Power, Port Link, Ring Status Change, Ping, Ping Reset, Dry Output, and DI

ENVIRONMENTAL SPECIFICATIONS

Air Temperature
 System On -40° to 75°C
 System Off -40° to 75°C

Operating Humidity (non-condensing) 0% to 90%

MTBF (Mean time between failures) 50.9 years

EXPORT INFORMATION

Packaged Shipping Weight 4.1 lbs
 1.86 kg

Package Dimensions 11.3" x 5.5" x 9.1"
 28.7 x 13.97 x 23.11 cm

UPC Code 7-56727-32046-3

ECCN 5A992

Schedule B Number 8517.62.0050

REGULATORY APPROVALS

Emissions
 European Standard EN55022
 AS/NZS CISPR 22
 FCC Part 15 Subpart B
 Class A limit

Immunity
 European Standard EN55024:
 IEC 1000-4-2/EN61000-4-2: ESD
 IEC 1000-4-3/EN61000-4-3: RF
 IEC 1000-4-4/EN61000-4-4: Fast Transient/ Burst
 IEC 1000-4-5/EN61000-4-5: Surge
 IEC 1000-4-6/EN61000-4-6: Conducted Disturbance
 IEC 1000-4-8/EN61000-4-8: Magnetic Field
 IEC 1000-4-11/EN61000-4-11: DIPS and Voltage Variations

Safety
 IEC 60950/EN60950 (LISTED)
 CSA C22.2 No. 60950/UL60950 Third edition

Vibration IEC 61373

Shock IEC 61373

Other
 RoHS2 compliant under CE
 NEMA TS2 compliant

Regulatory Approvals

RECOMMENDED PRODUCTS::

- 1200054** Power over Ethernet Splitter (24VDC, 24 Watts)
- 1200048** 48VDC External Power Supply Adapter
- 1200057** SFP, Multi-Mode, 2KM, 100BASE-FX (Extended Temperature)
- 1200058** SFP, Single-Mode, 30KM, 100BASE-FX (Extended Temperature)

Warranty Information
 Comtrol offers a 30-day satisfaction guarantee and 5-year limited warranty.

Sales Support
 +1.763.957.6000
 sales@comtrol.com

Technical Support
 +1.763.957.6000
 www.comtrol.com/support

Email, FTP, and Web Support
 info@comtrol.com
 ftp.comtrol.com
 www.comtrol.com