



O2T5 Uses CS or megapixel CS type lenses




Features:

- Dual-codec (H.264 & MJPEG)
- Progressive scan megapixel (2.0M CMOS)
- Multi-profile streaming (up to 5 streams of different resolutions, frame rates and codec selections)
- Digital PTZ, video crop
- Analog video output (CVBS)
- Built-in microphone
- Built-in standard PoE
- 2-way audio communication
- Built-in true day/night operation
- Robust design & convenient installation
- SD card slot (card not included)
- ONVIF support*
- 2 year warranty



lens not included



Camera Specifications

Image Sensor	Progressive scan 1/3.2" CMOS, 2.0M pixels
Full Resolution	1,600 x 1,200 pixels (UXGA)
Minimum Illumination (50IRE)	0.2 lux / F1.2
S/N Ratio	42db
White Balance	AWB (= 2500°C - 6500°C)
DSS	Supported
Recommended Lens	Varifocal 4.5 -10mm, F1.6 (not included)
Day/Night	Supported

Video Specifications

Compression Method	Simultaneous dual-codec (H.264 & MJPEG)
Resolution	15FPS @ 1600 x 1200 / 1280 x 1024 / 30FPS @ 1280 x 720 / 800 x 608 / 640 x 480 / 704 x 480 / 704 x 240 / 352 x 240 / 176 x 112
Multi-Profile Streaming	5 simultaneous video profiles
Intelligent Bit-Rate Control	CBR, VBR, HBR
PTZ	Digital PTZ & video crop
Image Setting	Text overlay, privacy mask, de-interlace filter
Motion Detection	3 regions

Audio Specifications

Mono Upstream	32Kbps G.726 ADPCM - LINE-in / MIC-in
Mono Downstream	128Kbps 16-bit Linear PCM - LINE-out (1Vpk)
Stereo	Stereo support

Network Specifications

Network Protocol	IPv4/v6, TCP, UDP, IGMP, ICMP, ICMPv6, ARP, RARP, PPPoE, RTCP, RTP, RTSP, SDP, HTTP, HTTPS, SMTP, FTP, DHCP, UPnP, SNMP, NTP, DNS, DynDNS, SOCKS
Speco DDNS	Supported (free of charge)
Security	User ID & password protection, IP address filtering, - HTTPS encryption, digest authentication, user access log, 802.1x support

User Access

8 concurrent users on D1 resolution
Depending on resolution, number of users may vary

External Terminal Specifications

LAN	10 / 100BaseT LAN
Analog Output	1 channel D1 CVBS output of the encoding video
Alarm Input / Output	1 sensor input & 1 relay output
Other	Two Stereo Jack / RS-232 Debug / 12VDC in

System Integration Specifications

Standard PoE (IEEE802.3af)	Supported
Intelligent Video	Motion detection
Alarm Triggers	Intelligent video & sensor input
Alarm Events	Video file upload (FTP), still image (email), relay output

Client Software

Speco NVR	64 ch (free of charge)
-----------	------------------------

Operating Environment

Operating Temperature/ Humidity	32° F – 113° F / 8% – 80% RH
Power Supply	PoE, 12VDC (power supply not included)
Power Consumption	500mA
Dimensions	2.6" (W) x 2.3" (H) x 4.7" (L)
Weight	1 lb.
Housing	Aluminum, silver
Approvals	FCC, CE, MIC, RoHS
Included in Package	IP camera, CD (user's guide, software), DC power adaptor, L wrench, ceiling mount, screws
iPhone® / Android™ App	Speco OnSIP

Optional Accessories



IPPOEINJ1295
12.95W PoE Injector



PSW5
12VDC
Power Supply

*visit www.specotech.com/onvif.html for latest ONVIF support

iPhone is a trademark of Apple Inc., registered in the U.S. and other countries. Android is registered to Google.

Speco Technologies is constantly developing and improving products.

We reserve the right to modify product design and specifications without notice and without incurring any obligation.



Rev. 2/26/13

For more information contact Speco Technologies

200 New Highway, Amityville, NY 11701 • Toll Free: 1-800-645-5516 • Fax: 631-957-9142 or 631-957-3880
www.specotech.com