

Total Access 900e

Market Leading Gen 3 IP Business Gateways

Product Features

- Market leading IP Business Gateways, with 66 percent higher performance than previous generations
- Seamless voice and data integration over VoIP-based network architectures
- Designed for Ethernet and Multi-T1 applications
- Optional eSBC functionality
- Up to 24 analog POTS interfaces
- Optional outbound lifeline via FXO
- Compatible with industry-leading softswitches and call agents
- Dynamic bandwidth allocation affords more efficient utilization
- Integral full-featured business-class IP router
- Stateful inspection firewall for network security
- Quality of Service (QoS) for delay and jitter sensitive traffic like VoIP
- Supports 802.1q Virtual LAN (VLAN) Trunking
- Voice Quality Monitoring (VQM)
- Command Line Interface (CLI) mimics industry *de facto* standard
- Network Address Translation (NAT) for IP address concealment
- Feature-rich ADTRAN Operating System (AOS)
- Rugged metal case
- Optional battery backup
- Industry-leading five-year warranty

The Total Access® 900e (Gen 3) Series of market leading IP Business Gateways for Ethernet and multi-T1 applications from ADTRAN® are designed for carrier Ethernet and SIP/MGCP Voice over IP (VoIP) networks. These products feature all the same robust routing and voice features of the previous generation IPBGs, along with a host of new features and functions that enable cost effective, reliable IP service delivery. These devices use the ADTRAN Operating System (AOS) to simplify management and administration. Multiple models offer flexibility for varied applications from PRI delivery and SIP trunking services to Hosted IP PBX offerings.

The Total Access 900e Series offers up to 24 FXS ports for analog voice delivery, and three Ethernet interfaces (one Gigabit and two Fast) for access to the Total Access 900e's router or WAN/LAN access. The Total Access 900e Series can be coupled with a NetVanta® Power over Ethernet (PoE) switch to provide connectivity to a variety of network devices and personal computers, as well as to power IP phones and Wireless Access Points (WAPs).

VoIP Gateway

The Total Access 900e Series utilizes SIP or MGCP for VoIP applications, providing interoperability with industry-leading soft switches, feature servers, and gateways. Acting as a gateway, the Total Access 900e converts IP signaling from the carrier into traditional TDM analog and digital voice services. This functionality allows the Total Access 900e Series to deliver voice services to both IP phones and traditional telephony equipment simultaneously. For customers implementing a hosted PBX or IP Centrex service, the Total Access 900e Series is ideal for providing customers additional analog ports necessary to support their remaining analog phones, fax machines, or modems. The Total Access 900e Series supports many popular calling features such as caller ID, call hold, forward, transfer, and call waiting. Voice Activity Detection (VAD) and silence suppression are supported to ensure reliable VoIP call quality.

Enterprise Session Border Control (eSBC)

The Total Access 900e also can provide eSBC functionality delivering a truly converged application platform at the customer premises. This feature is

becoming mandatory in today's service deployment to normalize, secure and troubleshoot the SIP to SIP communication between a carrier network and the customers SIP compliant equipment.

Remote Survivability

In addition, the Total Access 900e Series can act as a registrar and Back-to-Back User Agent (B2BUA) or as a SIP-transparent proxy to facilitate remote survivability and NAT traversal. In the event of a service interruption on the wide area network or if the carrier's call agent were to become unavailable, calls may continue locally at the customer premises between IP-based or analog phones. In addition, the embedded FXO port can be used as a survivable interface for outbound calls to the PSTN.

QoS, Security, Routing, and VQM

The Total Access 900e Series uses the AOS to provide a stateful inspection firewall; NAT; DHCP server/client; and feature-rich, standards-based, IP routing functionality supporting BGP, OSPF, and RIP routing protocols. Inherent QoS methods ensure appropriate classification and prioritization of VoIP traffic. These methods include Low Latency Weighted Fair Queuing, class based weighted fair queuing, support for Differentiated Services (DiffServ) protocol, Frame Relay Fragmentation (FRF.12), and Frame Relay traffic shaping. Voice Quality Monitoring (VQM) captures Mean Opinion Score (MOS), jitter, delay, and packet loss statistics necessary to troubleshoot VoIP calls over the WAN to help ensure superior call quality.

Management

The Total Access 900e Series can be remotely managed by ADTRAN's n-Command® MSP platform. ADTRAN n-Command MSP offers the ability to discover devices, make mass configuration changes or firmware upgrades, backup/restore configuration, and generate inventory reports for asset management. ADTRAN's n-Command MSP also offers VoIP VQM and reporting, SIP ladder diagram, as well as an industry leading, easy-to-use, Graphical User Interface (GUI). Total Access 900e products are housed in a rugged metal enclosure; available in wallmount, rackmount, and desktop mountings; and offer a battery backup system for up to eight hours of uninterrupted service upon a customer-site power outage. Total Access 900e products are backed by an industry-leading warranty.



Total Access 900e

Market Leading Gen 3 IP Business Gateways

Product Specifications

Physical Interfaces

T1

- Quad T1/FT1
- RJ-48C

Ethernet

- **Three Ethernet Interfaces (WAN/LAN Support):**
 - One Gigabit
 - Two Fast
- Full Duplex
- RJ-45
- Supports 802.1q VLAN Trunking

USB 2.0

- One Interface

Digital Voice

- PRI
- T1 CAS Support
- **Signaling Methods**
 - E&M Wink
 - E&M Immediate
- Feature Group D
- RJ-48C

Analog Voice

- 8, 16, and 24 FXS POTS via 50-pin Amphenol
- 68.5 Vrms with 20VDC Offset Maximum Ring Voltage
- Sinusoidal Ringer Waveform
- 48 V, Nominal On-hook Battery Voltage
- 30 mA, Nominal Loop Current
- **FXS 2-wire Impedances**
 - 600Ω
 - 900Ω
 - 600Ω +2.16μF
 - 900Ω +2.16μF
- **FXO 2-wire Impedances (Lifeline FXO)**
 - 600Ω
 - 900Ω
 - 600Ω +2.16μF
 - 900Ω +2.16μF
- **Signaling Methods**
 - Loop Start
- **FXO 2-wire impedances (Standard FXOs)**
 - 600Ω
 - 900Ω
 - 600Ω +2.16μF
 - 900Ω +2.16μF

- Integral FXO (900e Series)

■ Signaling Methods

- Loop Start
- Ground Start

■ FXO 2-wire Impedances

- 600Ω +2.16μF
- 900Ω +2.16μF
- Rs 220 ohms, Rp 820 ohms, Cp 115nF
- Rs 270 ohms, Rp 750 ohms, Cp 150nF
- Rs 270 ohms, Rp 750 ohms, Cp 150nF, Zin 600r
- Rs 320 ohms, Rp 1,050 ohms, Cp 230nF
- Rs 350 ohms, Rp 1,000 ohms, Cp 210nF, Zin 600r
- Rs 370 ohms, Rp 620 ohms, Cp 310nF
- Rs 800 ohms, Rp 100 ohms, Cp 50nF

■ Signaling Methods

- Loop Start
- Ground Start
- DPT

Craft

- DB-9

Memory

- **RAM:** 512 MB RAM
- **Flash:** 128 MB Flash

VoIP

- SIP
- MGCP (FXS Interfaces Only)

Packet-based Voice Resources

- **CODECs**
 - G.711-64k PCM
 - G.729a-8k CS-ACELP
- G.168 Echo Cancellation
- Up to 64ms Echo-tail length
- Supports up to 60 Channels DSP
- Supports 30 T.38 Sessions

Media Stream

- RTP/UDP/IP (RFC 3550)
- RTP Payload for DTMF Digits (RFC 2833)
- Supports Port-to-port Hairpin Call
- SDP (RFC 2327)

Total Access 900e

Market Leading Gen 3 IP Business Gateways

NAT Traversal and Remote Survivability

- B2BUA
- SIP Registrar for IP Phones
- SIP proxy with Survivability
- Transparent/Stateful/Outbound

Tone Services

- Local DTMF Detection
- Local Tone Generation
 - DIALtone
 - Busy
 - Call Waiting
 - Alternate Call Waiting
 - Receiver Off Hook
- Ringing
 - Distinctive Ring

Calling Feature Support

(Varies with feature server/gateway)

- Caller ID
 - Name and Number (MDMF, SDMF)
 - Call Waiting Caller ID
- Voice Mail
 - Stutter dialtone
 - Visual Message Waiting Indicator (VMWI)
- Call Hold
- Call Forward
 - Busy Line
 - No Answer
- Call Transfer
 - Blind, Attended
- Call Waiting
- Distinctive Ring
- Do Not Disturb
- Three-way Calling
- Call Return
- Speed Dial
- 3-way Conferencing (3WC)

Security

Firewall

- Stateful Inspection Firewall
- Denial of Service (DOS) Protection
- Access Control Lists
- Application Level Gateways
- Packet Filtering

NAT

- Basic NAT (1:1) and NAT (Many:1)

QoS

- Low Latency and WFQ
- Hierarchical QoS
- DiffServ packet marking and recognition
- Frame Relay Fragmentation
- Traffic Monitoring (NetFlow 9)

VQM

- Packet Capture (PCAP)
- MOS prediction
- Jitter, Delay and Packet Loss
- Past and Active Calls

VPN

- **IPSec Tunnel Mode:** 100 Tunnels
- **Encryption:** DES, 3DES, and AES
- **Authentication Mechanisms:** XAUTH, Digital certifications, Pre-Shared Keys, and Secure ID

Protocols

- BGP
- Multilink Frame Relay
- OSPF
- PPP
- RIP (v1 and v2)
- Multilink PPP
- GRE
- HDLC
- IGMP V2
- PAP and CHAP
- Frame Relay
- Multi-VRF

Routed Protocols

- IP

DHCP

- Client
- Relay
- Server

Management and Utilities

- Familiar CLI
- Web-based GUI
- n-Command Support
- SNMP v2 and v3
- SYSLOG Logging
- Telnet, Craft/Console Port, SSH, Ping, Trace route, NTP
- TCL Scripting



ADTRAN, Inc.
Attn: Enterprise Networks
901 Explorer Boulevard
Huntsville, AL 35806
P.O. Box 140000
Huntsville, AL 35814-4000

256 963-8000
256 963-8699 fax

General Information
800 9ADTRAN
info@adtran.com
www.adtran.com

Pre-Sales Technical Support
888 423-8726
application.engineer@adtran.com
www.adtran.com/presales

Post-Sales Technical Support
888 423-8726
support@adtran.com
www.adtran.com/support

Where to Buy
888 423-8726
channel.sales@adtran.com
www.adtran.com/where2buy

ProServices
888 874-2237
proservices@adtran.com
www.adtran.com/proservices

Global Inquiries
256 963-8000
256 963-6300 fax
international@adtran.com

ADTRAN believes the information in this publication to be accurate as of publication date, and is not responsible for error. Specifications subject to change without notice. ADTRAN, NetVanta, n-Command and Total Access are registered trademarks of ADTRAN, Inc. and its affiliates in various countries. All other trademarks mentioned in this document are the property of their respective owners.

ADTRAN warranty duration and entitlements vary by product and geography. For specific warranty information, visit www.adtran.com/warranty

ADTRAN products may be subject to U.S. export controls and other trade restrictions. Any export, re-export, or transfer of the products contrary to law is prohibited.

For more information regarding ADTRAN's export license, please visit www.adtran.com/exportlicense



ADTRAN is an ISO 9001, ISO 14001, and a TL 9000 certified supplier.

642439xxF1-8B September
Copyright © 2013 ADTRAN, Inc.
All rights reserved.

Total Access 900e

Market Leading Gen 3 IP Business Gateways

Product Specifications

Firmware Upgrade

- FTP
- X-Modem
- TFTP
- HTTP

Environment

- **Operating Temperature:** 32° to 122 °F (0° to 50 °C)
- **Storage Temperature:** -40° to 158 °F (-40° to 70 °C)
- **Relative Humidity:** Up to 95%, Non-condensing
- **Maximum Altitude:** 10,000 Feet

Physical and Power

Chassis

- Wallmount
- 1U Rackmount
- Desktop Metal Enclosure

Dimensions

- **Total Access 908e:**
1.75 in. x 17 in. x 8 in. (H x W x D)
- **Total Access 916e/924e:**
1.75 in. x 17 in. x 10 in. (H x W x D)

Weight

- **Total Access 908e:** 5.5 lbs.
- **Total Access 916e/924e:** 7 lbs.



Power

- **Total Access 908e:** 120 VAC, 60 Hz, 75W
- **Total Access 916e and 924e:** 120 VAC, 60 Hz, 110W
- **Battery Backup:** Optional eight-hour system
- **LEDs Total Access 900e**
 - Voice
 - Status
 - Gig 1
 - USB
 - T1 1 - 4
 - Ethernet 1 - 2

Agency Approvals

- FCC Part 15, Class A
- FCC Part 68
- Industry Canada CS03
- ETL and Canadian ETL (C-ETL)

Battery Backup Options

- Rackmount or Wallmount

Warranty

- Five Years (North America)

Ordering Information

Equipment	Part No.
Total Access 908e Gen 3	4243908F1
Total Access 908e Gen 3 with Lifeline FXO	4243908F2
Total Access 908e Gen 3 with Session Border Control with Lifeline FXO	4243908F2SBC
Total Access 916e Gen 3	4243916F1
Total Access 916e Gen 3 with Lifeline FXO	4243916F2
Total Access 924e Gen 3	4243924F1
Total Access 924e Gen 3 with Lifeline FXO	4243924F2
Total Access 924e Gen 3, 16 FXS, 9 FXO (1 Lifeline)	4243924F3
Total Access 900e Gen 3, SBC Feature Pack Upgrade	1950900G3
Battery Backup Systems	
Total Access 908e Gen 3, Eight-hour, Wallmount	1200641L1
Total Access 916e/924e Gen 3, Eight-hour, Wallmount/Rackmount	1175044L1
Total Access 916e/924e Gen 3, Eight-hour, Wallmount	1175044L2