


#### MIL-W-22759/44



# **Product Description**

ETFE Copolymer Stranded Conductor

## **Applications**

Used as interconnect wire in protected harness applications.

#### **Specifications**

CONDUCTOR: Silver-coated copper

- INSULATION: Cross-linked extruded, modified ETFE

TEMPERATURE: 200°CVOLTAGE: 600 Volts

Part No.	Conductor Size AWG	Stranding No. x AWG	Diameter of Stranded Conductor Min. (in.)	Diameter of Stranded Conductor Max. (in.)	Finished Wire Resis. @ 20°C (68°F) ohms/1,000 ft.)	Finished Wire Nom. O.D. (in.)	Finished Wire Approx. Wt. Ib./1,000 ft.
M22759/44-28-XX	28	7 x36	.014	.015	63.8	0.27002	.91
M22759/44-26-XX	26	19 x 38	.018	.020	38.4	0.32002	1.4
M22759/44-24-XX	24	19 x 36	.023	.025	24.3	0.37002	2.0
M22759/44-22-XX	22	19 x 34	.029	.032	15.1	0.43002	2.8
M22759/44-20-XX	20	19 x 32	.037	.040	9.19	0.50002	4.3
M22759/44-18-XX	18	19 x 30	.046	.050	5.79	0.60002	6.5
M22759/44-16-XX	16	19 x 29	.052	.057	4.52	0.68002	8.3
M22759/44-14-XX	14	19 x 27	.065	.072	2.88	0.85003	13.0
M22759/44-12-XX	12	19 x 28	.084	.089	1.90	0.103003	19.7

Electrical and Electronic Wire & Cable • Enterprise Cabling & Security Solutions • Fasteners

Anixter Inc. World Headquarters • 2301 Patriot Boulevard, Glenview, IL 60026-8020 • 1.800.ANIXTER • 224.521.8000 • anixter.com

# Product Data Sheet | Anixter Catalog Page



\* All part numbers require color code designation, please refer –XX to the color code chart down below.

## **Hook Up and Lead Wire Insulation Color Code Chart**

0	black
1	brown
2	red
3	orange
4	yellow
5	green
6	blue
7	violet/purple
8	gray
9	white
P	pink
T	tan
D	dark (i.e. D6=dark blue
L	light (i.e. L6=light blue)
	- '

1.1...1

For white with black stripe - 90
For green with yellow stripe - 54
For white with a black and red stripe - 902
For white and black twisted conductor - 9/0
For white, black and red twisted conductors - 9/0/2

Electrical and Electronic Wire & Cable • Enterprise Cabling & Security Solutions • Fasteners

Anixter Inc. World Headquarters • 2301 Patriot Boulevard, Glenview, IL 60026-8020 • 1.800.ANIXTER • 224.521.8000 • anixter.com