P-touch

TZ 14-14



ECTRONIC LABELING SYSTEM

brother

1 1 1 1 1 1


PC-Ready Great for group sharing!
Carry it around, use it anywhere, or connect it to your PC...

Mary Smith

Rechargeable Labeler







PC-Ready

- Connect to PC for special labeling projects
- Also, a full-function stand-alone labeler

High Visibility LCD

- Label preview see your work before printing
- Graphical, 15 character x 2 line display

Quick, Easy Label Creation

- Easy one-key access for templates and symbols
- Automatic tape cutter



Space Conce



Model PT-18R Electronic Labeling System

PT-18R Specifications

PRINTING FEATURES

- Prints durable laminated labels from 1/4" to 3/4" wide
- · Printing options include standard, vertical, and mirrored formats
- Prints text in 7 sizes and 4 character widths
- Prints industry standard bar code symbologies
- · Sharp, crisp printing of text and graphics

LABEL-DESIGN FEATURES (stand-alone mode)

- Advanced features including easy auto templates, auto character sizing based on tape width, sequential numbering and repeat (multi-copy) printing
- Design and print up to 5 lines depending on width of tape
- Special formatting options for text including alignment and framing
- Built-in general office and industrial templates and symbols

EASE-OF-USE FEATURES

- Ni-MH rechargeable power source... never buy batteries!
- Automatic cutter
- · Easy grip, horizontal style machine
- QWERTY keyboard with one key operation
- LCD display: 15 character x 2 line graphic display
- Print Extra-Strength and Flexible ID labels simply by switching cassettes
- Memory functions to store frequently used templates

INCLUDES P-TOUCH EDITOR SOFTWARE

- · Easy-to-use label design tools
- · Pre-designed templates you can use or easily customize
- Tools for importing text and graphics
- · Utilities to help you easily print data from databases
- Drivers for PC

CARTON CONTENTS

- PT-18R Labeling System
- Ni-MH rechargeable battery (built-in)
- AC Adapter (AD-60)
- Charger cradle base
- CD (Design Software & Drivers)
- User manual
- USB cable
- One 1/2" (12 mm) x 16.4' (5 m) black on white Standard Laminated tape (TZ231)

SPECIFICATIONS

 Powered by rechargeable Ni-MH battery, or through cradle with built-in AC adapter

T 40D OVOTEM DECUMPEMENT

- Unit Weight: 1.276 lbs.
- Unit Dimensions: 5.96"(w) x 2.08"(d) x 4.9"(h)
- · One year limited warranty

| PT-18R SYSTEM REQUIREMENTS | |
|----------------------------|--|
| Operating System | Pre-installed Windows 98, 98SE, Me, 2000 Professional, XP Professional, or XP Home Edition |
| CPU | Intel® Pentium 266MHz or higher required (700MHz or higher recommended) |
| Memory (RAM) | 64MB or more required |
| Hard-Disk [†] | 50MB of available space or more required |
| Interface | USB 1.1 or later |
| Others | CD-ROM drive (required to install the software) |
| Monitor | 800 x 600 dpi (SVGA/High Color or higher graphics card) |

Uses interchangeable TZ tape cassettes.









For a system with Microsoft® Windows®, 2000 Pro or XP, be sure to install it from an account with administrator privileges.

- Requires additional purchase
- $^{\scriptscriptstyle \dagger}$ $\,$ The hard-disk free space is required for installing all options.

© 2004 Brother International Corporation,100 Somerset Corporate Boulevard, Bridgewater, NJ 08807 All rights reserved. All trademarks and registered trademarks are the property of their respective companies. All specifications subject to change without notice. Printed in U.S.A.

For P-touch information, visit <u>www.brother.com</u> or call 1-877-4PTOUCH (1-877-478-6824)

Got questions? Please contact the Product Manager by e-mailing your questions to:

industrial@brother.com

