





Lion-R EtherNet/IP I/O Rugged Modules with 16 Digital Inputs



Type	0980 ESL 811-EIP 16DI-M12-R	
Product Description	LioN-R Digital input module, 16 digital input channels, EtherNet/IP devices, rotary address switches for setting addresses, M12 LAN connector, D-coded	
Order Number	934 691-001	
Diagnostic indication		
LED	Indication	Condition
1...8 A	White	Channel status
1...8 DIA A	Red	Periphery error
1... 8 B	White	Channel status
1... 8 DIA B	Red	Periphery error
P1 Lnk/Act	Green Yellow flashing Off	Connection to an Ethernet device I/O device exchanging data No connection to any other device
P2 Lnk/Act	Green Green flashing Off	Connection to an Ethernet device I/O device exchanging data No connection to any other devices
MS (Module status)	Green Green flashing Red/Green flashing Red flashing Off	Device is ready for operating Wrong configuration Self test is running Firmware update Device is switches off
NS (Network status)	Green flashing Green Red flashing Red Red/Green flashing Off	IP address is available Connection to master is available At least one connection has timed out IP address is already being used by another device Self test is running Device is switched off/Device has no IP address
US	Green Red	Voltage 18 V<= US<=30 V Voltage US<18 V or US>30 V
UL	Green Red	Voltage 18 V<= US<=30 V Voltage US<18 V or US>30 V

Technical modifications reserved.

Bit assignment								
Bit	7	6	5	4	3	2	1	0
M12 Input 16DI								
Byte 0	4B	4A	3B	3A	2B	2A	1B	1A
Byte 1	8B	8A	7B	7A	6B	6A	5B	5A


Pin assignment		
LAN connection M12, D-coded	Power supply 7/8"	Input/Output M12
 <p>1 = TD+ 2 = RD+ 3 = TD- 4 = RD Housing = shielding</p>	 <p>1 = +24 V Actuators 2 = +24 V Logic/Sensor 3 = GND (0 V) Logic/Sensor 4 = GND (0 V) Actuators Housing = PE</p>	 <p>1 = +24 V 2 = IN B 3 = GND (0 V) 4 = IN A 5 = earth Housing = PE</p>

Part number	Order number
0980 ESL 811-EIP 16DI-M12-R	934 691-001





LioN-R EtherNet/IP I/O Rugged Modules with 16 Digital Inputs

Product Description	
Type	0980 ESL 811-EIP 16DI-M12-R
	
Technical Data	
Protection Class	IP67
Operating Temperature Range	-10°C to +60°C
Weight	605 g
Housing Material	Metal (diecast zinc)
Bus System	
Transmission Rate	10/100 Mbps
Address Range	0 to 255
Default Address	0
Inputs	
Rated Input Voltage	24 V DC
Sensor Type	PNP (source)
Power Consumption of Sensor	Max. 200 mA
Reverse Polarity Protection	Yes
Short Circuit-proof	Yes
Number of Digital Channels	16
Status Indicator	LED white per channel
Diagnostic Indicator	LED red per port
Included in Delivery	
M12 Dust Covers	4 pieces
Attachable Labels	10 pieces

The use of these products in aggressive media should be verified in each case. Technical modifications reserved.
 Certifications have been applied for UL and CSA.