

# **GX93 Series Low-current, Synchronizable Mini-horns**



- Single unit is capable of 12 VDC or 24 VDC determined by input voltage
- ► 3100 Hz horn frequency
- Input terminals accept 18 AWG (1.2 mm) to 12 AWG (2.3 mm) wire
- ► Low current consumption
- Variety of mounting options for new construction and retrofit applications
- ► UL464 Listed for Fire Protective Service
- Textured finish high impact plastic faceplate, available in fire alarm red or off-white

The GX93 Series mini-horns are high quality remote signaling appliances that can be used on the same circuit as other Gentex devices using the AVS Series Synchronization Modules. They offer dependable remote annunciation and are listed for use with both filtered and unfiltered power. These signaling appliances are UL464 listed for use with fire protective systems.

## Certifications and Approvals

Note	Gentex Corporation holds the Listings and
	Approvals.

Region	Certificati	on
USA	UL	ULSZ: Audible Signal Appliances (UL464), ULSZ7: Audible Signal Appliances Certified for Canada (cULus)
	CSFM	7135-0569: 126
	CBFP NYC/MEA	City of Chicago Bureau of Fire Protection 285-91-E: Vol. XVI

#### **Installation/Configuration Notes**

#### **Mounting Considerations**

These mini-horns mount on single-gang back boxes.

#### **Synchronization**

Although the AVS44 modules can be used with these devices, the AVSM modules are recommended in loops where no HS24 or ST24 devices are used.

#### Wiring

The terminal blocks accept wires with diameters between 18 AWG (1.2 mm) and 12 AWG (2.3 mm).

#### **Parts Included**

Quant.	Component
1	Horn
1	Hardware pack
1	Literature pack

#### **Technical Specifications**

#### **Alarm Ratings**

Sound output at 10 ft (3 m):	81 dBA		
Audible Device Current (maximum):			
At 12 V	13 mA RMS, 17 mA FWR		
At 24 v:	18 mA RMS, 20 mA FWR		

#### 2 | GX93 Series Low-current, Synchronizable Mini-horns

#### **Environmental Considerations**

Temperature (operating): +32°F to +120°F (0°C to +49°C)

**Mechanical Properties** 

Dimensions (H x W x D): 5.5 in. x 4.5 in. x 0.5 in.

(14 cm x 11 cm x 1.3 cm)

**Power Requirements** 

Voltage (Input): 8 VDC to 33 VDC

#### **Ordering Information**

#### GX93-R Mini-Horn (red)

GX93-R

Red, 12 VDC or 24 VDC, 3100 Hz horn with field-selectable temporal (Code 3) or continuous tone pattern

GX93-W Mini-Horn (off-white)

GX93-W

Off-white, 12 VDC or 24 VDC, 3100 Hz horn with field-selectable temporal (Code 3) or continuous tone pattern

#### **Accessories**

## **AVS-44 Synchronization Control Module**

AVS-44

Synchronization Control Module primarily for use with the Gentex HS24 Series and ST24 Series notification appliances.

#### **AVS44-W Synchronization Control Module** (white)

AVS44-W

Synchronization Control Module primarily for use with the Gentex HS24 Series and ST24 Series notification appliances.

#### **AVSM-R Synchronization Control Module** (red)

AVSM-R

Synchronization module for use with all Gentex synchronizable notification appliances except the HS24 Series and the ST24 Series.

#### **AVSM-W Synchronization Control Module** (white)

AVSM-W

Synchronization module for use with all Gentex synchronizable notification appliances except the HS24 Series and the ST24 Series.

#### SGP-R Trim Plate (red)

SGP-R

The SGP trim plates are used with the GX91 and GX93 Mini-horns. They are constructed of durable plastic and are designed for mounting to a single-gang electrical box.

### SGP-W

#### SGP-W Trim Plate (white) The SGP trim plates are used with the GX91

and GX93 Mini-horns. They are constructed of durable plastic and are designed for mounting

to a single-gang electrical box.

130 Perinton Parkway

Bosch Security Systems, Inc. Fairport, New York, 14450, USA Phone: +1 800 289 0096 Fax: +1 585 223 9180 security.sales@us.bosch.com www.boschsecurity.us

Europe, Middle East, Africa: Bosch Security Systems B.V. P.O. Box 80002 F.O. BOX 80002 5600 JB Eindhoven, The Netherlands Phone: + 31 40 2577 284 Fax: +31 40 2577 330 emea.securitysystems@bosch.com www.boschsecurity.com

Asia-Pacific: Re Robert Bosch (SEA) Pte Ltd, Security Systems Represented by 11 Bishan Street 21 Singapore 573943 Phone: +65 6258 5511 Fax: +65 6571 2698 apr.securitysystems@bosch.com www.boschsecurity.com