


109-00018



Article Number: 109-00018

Q Tie, 8.3" Long, 50lb Tensile Strength, PA66, Natural, 100/pkg

 RoHS

Base Data

Local Order Number	109-00018
Type	Q50R
Color	Natural (NA)
Features and Benefits	<ul style="list-style-type: none"><li>• Open-head design with easily detectable slot opening allows for swift and easy insertion</li><li>• Pre-lock feature allows for a temporary hold</li><li>• The large ribbed tail permits an ergonomic installation</li><li>• Two rails on the strap ensure guidance through the cable tie head</li></ul>
Product Description	Q Ties have a distinctive open-style head, a pre-lock function, and a large ribbed tail. The easily detectable slot opening offered with the tail and tie head offers ease of placement especially when working with gloves is necessary or for blind applications with limited view of the installation. The pre-lock feature allows for temporary holding of cable and wire bundles, permitting additional cables and wires to be placed without destroying the cable tie. Q Ties can be tensioned by hand or with one of HellermannTyton's mechanical cable tie application tools.
Fixation Method (FF)	None
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Short Description	Q Tie, 8.3" Long, 50lb Tensile Strength, PA66, Natural, 100/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	50.0 lbs
Minimum Tensile Strength (N)	220 N
Length L (imperial)	8.3 "
Length L (metric)	210 mm
Width W (imperial)	0.19 "
Width W (metric)	4.7 mm
Bundle Diameter min (imperial)	0.12 "
Bundle Diameter min (metric)	5.0 mm
Bundle Diameter max (imperial)	2.0 "
Bundle Diameter max (metric)	50.0 mm
Thickness T (imperial)	0.06 "
Thickness T (Metric)	1.5 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	100

**Carton Quantity** 6000 Pieces

**Material and Specifications**

---

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL94 V2
<b>Halogenfree</b>	Yes
<b>Operating Temperature</b>	-40 °F to +185 °F (-40 °C to +85 °C)
<b>ROHS Conformity</b>	Yes