

123A00-1



Brand Features

Omni-Bus is a distributed control system for lights, shades, fans, shutters, pumps, and more. Utilizing the worldwide DIN rail standard for mounting, Omni-Bus controls CFL, LED, electronic low voltage, Halogen, and incandescent lighting. Output devices are rated for 110/220/240V 50-60Hz markets unless otherwise noted. All wall stations are 24VDC and below. Modular Omni-Bus components can be located where needed to save wiring and installation costs. Elegant, multi-button programmable wall stations eliminate the owners of in wall being wiring and multi-button programmable wall stations. eliminate the expense of in-wall high voltage wiring to multi-way switches.

Item Description

Omni-Bus Power Supply 2.5A DIN Rail Module

Features and Benefits

- This 24VDC 2.5A power supply module provides power to the Omni-Bus network through the required 124A00-1 Omni-Bus component
- · All modules are CE, FCC, UL (ETL), SASO, and C-Tick approved

UPC Code: 87225700723

Country of Origin: Please Contact Customer Service

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc. 201 North Service Road, Melville, NY 11747 Telephone: 1-800-323-8920 · FAX: 1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): 1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: 1-800-469-7890 · FAX: 1-800-824-3005 www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2012-2015 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

