

Anixter Level 2 for Industrial Network Environments

Power Supplies: 24V 40 A Three Phase



Anixter Item #	Product Description
L2-24V-40A-3P	DIN Rail Mount Power Supply, Three Phase, 24 VDC / 40 A

Input Circuit	
Rated input voltage U	3 x 400-500 V AC
Input voltage range	340-575 V AC
	480-820 V DC
Frequency range AC	47-63 Hz
Typical input current	1.72 A
Typical power consumption	1058 W
Inrush current limiting	30 A
Internal input fuse	T 5 A / 500 V AC
Power factor correction (PFC)	< 3.5 mA

Indication of Operational States:	
Output voltage	Green LED Red LED
	OUTPUT OK: V: output voltage OK OUTPUT LOW: V: output voltage too low
Output Circuit	
Rated output voltage	24 V DC
Tolerance of the output voltage	0...+1 %
Adjustment range of the output voltage	22.5-28.5 V DC
Rated output power	960 W
Rated output current I	40 A
Signaling contact for output voltage OK	solid-state (max. 60 V DC, 0.3 A)
Minimum fuse rating to achieve short-circuit protection	M 60 V DC, m 0.3 A fast-acting
Output circuit - No-load, overload and short-circuit behavior:	
Efficiency	typ. 92%
Duty time	100%
Dimensions (W x H x D)	275.8 x 124 x 118.8 mm [10.86 x 4.88 x 4.68 in]
Weight	3.275 kg (7.220 lb)
Material of housing	Metal
Mounting	DIN rail (IEC/EN 60715), snap-on mounting without any tool
Mounting position	horizontal
Degree of protection housing / terminals	IP20 / IP20
Electrical connection - input circuit / output circuit:	

Wire size fine-strand with wire end ferrule	fine-strand with wire end ferrule	Input circuit L1, L2, L3: 0.2-4 mm ² (24-11 AWG) Output circuit L+, L+, L-, L-: 0.5-10 mm ² (20-8 AWG) Signalling circuit: 0.2-4 mm ² (24-11 AWG)
	fine-strand without wire end ferrule	Input circuit L1, L2, L3: 0.2-6 mm ² (24-11 AWG) Output circuit L+, L+, L-, L-: 0.5-16 mm ² (20-6 AWG) Signalling circuit: 0.2-6 mm ² (24-10 AWG)
	rigid	Input circuit L1, L2, L3: 0.2-6 mm ² (24-11 AWG) Output circuit L+, L+, L-, L-: 0.5-16 mm ² (20-6 AWG) Signalling circuit: 0.2-6 mm ² (24-10 AWG)
Stripping length		8 mm (0.31 in)
Environmental Data		
Ambient temperature range	operation	-40...+70 °C
	rated load	-40...+70 °C
	storage	-40...+85 °C
Damp heat (cyclic)	(IEC/EN 60068-2-30)	95 % without condensation
Shock (half-sine)	(IEC/EN 60068-2-27)	Half sine wave, 15G, 11 ms, 3 axes, 6 Faces, 3 times for each face
Vibration (sinusoidal)	(IEC/EN 60068-2-6)	10-500 Hz, 2G, each along X, Y, Z axes 6 min / cycle
Standards		
Product standard		EN 61204-3
Low Voltage Directive		2006/95/EN

EMC directive	2004/108/EN	
RoHS directive	2002/95/EN	
Electrical safety	EN 60950-1, UL 60950-1, UL 508, EN 61558-1, EN 61558-2-17; EN 60204-1	
Electromagnetic Compatibility		
Interference immunity to:	IEC/EN 61000-6-2	
Electrostatic discharge	IEC/EN 61000-4-2	Level 4 (air discharge 15 kV / contact discharge 8 kV)
Radiated, radio-frequency, electromagnetic field IEC/EN	IEC/EN 61000-4-3	Level 3 (10 V/m)
Electrical fast transient/burst	IEC/EN 61000-4-4	Level 4 (4 kV / 5 kHz)
Surge	IEC/EN 61000-4-5	L-L Level 3 (2 kV) / L-PE Level 4 (4 kV)
Conducted disturbances, induced by radio-frequency fields	IEC/EN 61000-4-6	Level 3 (10 Vrms)
Power frequency magnetic fields	IEC/EN 61000-4-6	Level 4 (30 A/m)
Voltage dips, short interruptions and voltage variations	IEC/EN 61000-4-6	dips: >95 % 0.5 ms / >30 % 0.5 ms
		interruptions: >95 % 250 ms
Interference emission	IEC/EN 61000-6-3	
High-frequency radiated	IEC/CISPR 22, EN 55022	Class B
IEC/CISPR 22, EN 55022	IEC/CISPR 22, EN 55022	Class B
Limits for harmonic current emissions	Class A	

Electrical and Electronic Wire & Cable • Enterprise Cabling & Security Solutions • OEM Supply – Fasteners
 Anixter Inc. World Headquarters • 2301 Patriot Boulevard, Glenview, IL 60026-8020 • 1.800.ANIXTER • 224.521.8000 • anixter.com

Anixter is a leading global distributor of enterprise cabling and security solutions, electrical and electronic wire and cable, and OEM supply – fasteners and other small parts.
 We reduce risk, complexity and cost from our customers' purchasing decisions, business processes and supply chains.

Anixter does not manufacture these products. Any product warranties are provided by the applicable manufacturers. Data and suggestions made are not to be construed as recommendations to purchase or as authorizations to use any products in violation of any law or regulation. TO THE FULLEST EXTENT PERMITTED BY LAW, ANIXTER DISCLAIMS ALL WARRANTIES, EITHER EXPRESS OR IMPLIED. ANIXTER MAKES NO WARRANTY OR REPRESENTATION, EXPRESS OR IMPLIED, ABOUT THE ACCURACY OR COMPLETENESS OF ANY INFORMATION PROVIDED.