



DB224-B

Andrew® Omni Exposed Dipole Antenna, 155–165 MHz, 360° horizontal beamwidth, fixed electrical tilt

- Broad response
- Two-piece mast for ease of shipping

Electrical Specifications

Frequency Band, MHz	155–165
Gain, dBi	8.1
Beamwidth, Horizontal, degrees	360
Beamwidth, Vertical, degrees	16.0
Beam Tilt, degrees	0
VSWR Return Loss, dB	1.5 14.0
Input Power per Port, maximum, watts	500
Polarization	Vertical
Impedance	50 ohm

General Specifications

Antenna Brand	Andrew®
Antenna Type	Omni, exposed dipole
Band	Single band
Operating Frequency Band	155 – 165 MHz

Mechanical Specifications

Color	Silver
Lightning Protection	dc Ground
Radiator Material	Aluminum
RF Connector Interface	N Male
RF Connector Location	Bottom
RF Connector Quantity, total	1
Wind Area, maximum	0.3 m ² 3.2 ft ²
Wind Loading, maximum	560.5 N @ 100 mph 126.0 lbf @ 100 mph
Wind Speed, maximum	128.7 km/h 80.0 mph

Dimensions

Length	6477.0 mm 255.0 in
Net Weight	15.9 kg 35.0 lb

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant by Exemption
China RoHS SJ/T 11364-2006	Above Maximum Concentration Value (MCV)

DB224-B

POWERED BY



ISO 9001:2008

Designed, manufactured and/or distributed under this quality management system



Included Products

DB365-OS — Pipe Mounting Kit that consists of two clamps for mounting antennas to round members 1.25 - 3.5 in (35 - 89 mm) OD round members.