

H11MP-602**6-1/8 in EIA Male Flange without gas barrier for 4 in HJ11-50 air dielectric cable****OBSOLETE****This product was discontinued on: April 1, 2014**

General Specifications

Interface	6-1/8 in EIA Male Flange
Body Style	Straight
Brand	HELIAX®
Gas Barrier	No
Mounting Angle	Straight

Electrical Specifications

Connector Impedance	50 ohm
Operating Frequency Band	0 – 860 MHz
Cable Impedance	50 ohm
RF Operating Voltage, maximum (vrms)	9721.00 V
dc Test Voltage	28 kV
Insulation Resistance, minimum	5000 MOhm
Average Power	57.0 kW @ 900 MHz
Peak Power, maximum	1890.00 kW
Insertion Loss, typical	0.05 dB

Mechanical Specifications

Outer Contact Attachment Method	Tab-flare
Inner Contact Attachment Method	Thread-in stub
Outer Contact Plating	Unplated
Inner Contact Plating	Silver

Dimensions

Nominal Size	4 in
Diameter	206.25 mm 8.12 in
Length	215.90 mm 8.50 in
Weight	12.97 kg 28.59 lb

Environmental Specifications

Operating Temperature	-40 °C to +150 °C (-40 °F to +302 °F)
Storage Temperature	-70 °C to +100 °C (-94 °F to +212 °F)

Return Loss/VSWR

Frequency Band	VSWR	Return Loss (dB)
40–2300 MHz	1.04	35.00

H11MP-602

POWERED BY



Regulatory Compliance/Certifications

Agency

ISO 9001:2008

Classification

Designed, manufactured and/or distributed under this quality management system

* Footnotes

Insertion Loss, typical 0.05v⁻freq (GHz) (not applicable for elliptical waveguide)