

Toll Free: 1-888-357-0798 Direct Tel:1-863-357-0798 Facsimile: 1-863-357-0006

STAINLESS STEEL SPEAKERPHONE PANELS

511 & 510 STAINLESS STEEL SPEAKERPHONE PANELS

Flush Mount or Replacement Panel for Weatherproof (WPP) or Open Enclosure Housings (HOB)

Discover CEECO's Rugged SSP Speakerphone model with autodial and ring-down capability. These speakerphones are the best fit for both indoor and outdoor use. These high quality speakerphones can be flush mounted or be installed in our durable, yet attractive weatherproof (WPP) or open enclosure housings (HOB). The stainless steel phone has a weatherproof and puncture proof speaker, that offers clear and reliable communication suitable for all your emergency, courtesy, and entrance security needs. CEECO's dedicated sales team, knowledgeable technical support, and readily available telephones and parts gives you the product and service you can count on. Manufactured in the USA, CEECO telephones are Built to Last and are supported by over 84 years of experience.





Made in the USA

FEATURES

7 1/6"W x 11 1/4"H

Weight 5 lbs

Tamper Resistant Security Hardware

Puncture and Weather Proof Speaker

Low Powered Versions Available

Optional ADA Features Available

Optional Second Number Autodial -D2

Can be Installed in an Open Enclosure (HOB) or a Weatherproof Housing (WWP)

Line Powered

Requires 301-064 Security Tool only required for installation when in HOB or WPP)

1 Year Warranty and Lifetime Support

SPECIFICATIONS

Weight: Approximately 6 lbs.

Mounting: Flush Mounted

Weatherproof Housing (WPP)

Weather Resistant Open Enclosure (HOB)

Environment: Temperature: -30°C (-22°F) to 60°C (140°F)

Humidity: 0%-90% non-condensating

Input Power: Telephone Line Powered

Loop Current: 30mA min to 80mA max

Impedance:600 ohmsType Jack:RJ11CRinger Equivalency:0.4AUL & FCC Registration:Certified

ACCESSORIES: 301-064 Security Tool

(only required for installation when in

HOB or WPP)



CEECO has been providing telecom solutions since 1930. Our vandal resistant technology focuses on providing public communication solutions while reducing replacement and repair costs, lowering the customer's total cost of ownership. CEECO also offers custom design and branding to your specifications. Our commitment to providing expert service and support extends beyond the warranty of our product. We offer support for the life of the product! CEECO is devoted to giving you the quality and service you deserve.



Toll Free: 1-888-357-0798 Direct Tel:1-863-357-0798 Facsimile: 1-863-357-0006

STAINLESS STEEL SPEAKERPHONE PANELS

511-510 STAINLESS STEEL SPEAKERPHONE PANELS

Flush Mount or Replacement Panel for Weatherproof (WPP) or Open Enclosure Housings (HOB)

KEYPAD SPEAKERPHONE PANELS		AUTO DIAL SPEAKERPHONE PANELS			RING-DOWN SPEAKERPHONE PANELS			
SPP-511-F	SPP-511-FD O SECTION O SECTION	SSP-511-D	or SSP-511-D2	SSP-511-DD	SPF	P-511-X	SPP-511-X-ADA	
Dimensions: 7 1/6"W x 11 1/4"H		Dimensions: 7 1/6"W x 11 1/4"H			Dimensions: 7 1/6"W x 11 1/4"H			
Stainless Steel, Speakerphor	ne Panel	anel Stainless Steel, Speakerphone Panel		ne Panel	Stainless Steel, Speakerphone Panel			
Puncture and Weatherproof S	ncture and Weatherproof Speaker		Puncture and Weatherproof Speaker			Puncture and Weatherproof Speaker		
Press to Start/ Press to Stop Button • Phone will detect when the called party disconnects and will reset		Press to Start/ Press to Stop Button • Phone will detect when the called party disconnects and will reset			Press to Start/ Press to Stop Button • Phone will detect when the called party disconnects and will reset			
SSP-511-F Model Chrome Dial Keypad (F) Will allow or block incoming calls Call restriction capability Programmable conversation time-out Optional speed dialing Programmable PBX prefix dialing or access number SSP-511-FD Model Chrome Tone Dial Keypad (F) and Auto Dial Push Button (D) Will allow or block incoming calls Call restriction capability Programmable conversation time-out Optional speed dialing Programmable PBX prefix dialing or access number		SSP-511-D Model Auto Dial Push Button (D) • Will allow or block incoming calls • Programmable conversation time-out capability • Programmable PBX prefix dialing or access number			SPP-511-X Model Ring-down Operation (X) • Will allow or block incoming calls • Initiate a call when programmed through a PBX or phone system • Programmable conversation time-out			
		SSP-511-D2 Model Auto Dial Push Button (D2) • Will dial a second number if called party doesn't answer first number dialed SSP-511-DD Model Auto Dial Push Button (DD) • Two programmable auto dial buttons • Ability to allow or block incoming calls • Programmable conversation time-out capability			LOW POWER MODELS SPP-510-F, SPP-510-D, SPP-510-X • Full Function ADA features are NOT available			
								ADDITIONAL OPTIONS
-ADA	Open Enclosure F	lousing	Weatherproof Housing			Additional	Options & Features	

ADDITIONAL OPTIONS		IP - Voice over Internet Protocol Version available on all models (SIP)			
-ADA	Open Enclosure Housing	Weatherproof Housing	Additional Options & Features		
ENERG PHONE		HULUALIZU:	Auto Answer (AA) Remote Programming (RP) Voice Announcement (VA)		
 Red/ green LED call progress indicator light Braille Emergency Plate "EMERG. PHONE" Red Push Button 	Standard Black Housing -R Red Housing -S Stainless Steel Housing	Standard Black & TELEPHONE on Door • -B-EMER Black & EMERGENCY on Door • -R Red & EMERGENCY on Door • -R-TEL Red & TELEPHONE on Door • -Y Yellow & EMERGENCY on Door • -Y-TEL Yellow & Telephone on Door • -G Grey & TELEPHONE on Door • -G-EMER Grey & EMERGENCY on Door			