

HOB-331-X SPECIFICATIONS

AUTODIAL TELEPHONE PANEL WITH HANDSET FOR RING-DOWN OPERATION IN A OPEN ENCLOSURE STEEL HOUSING


Standard Analog Power, but also available in VoIP versions

Weather and vandal resistant stainless steel phone in an open enclosure wall mount black housing with telephone emblem on sides. Designed for ring-down operation. The telephone will accept incoming calls and relies on external equipment to control calling. Equipped with marine quality chrome mechanical hookswitch or optional (-M) magnetic hookswitch, ID window, 32" hearing aid compatible armored cord handset, and tamper resistant security screws. HOB models available in black, (-R) red, or (-S) stainless steel.



SPECIFICATIONS

Panel Size:	7 1/6"W x 11 1/4"H
Open Enclosure Housing:	7 1/4"W x 11 1/2"H x 5"D
Weight:	Approximately 10 lbs.
Mounting Instructions:	Open Enclosure Housing 4 holes spaced 8" x 5 7/8"
Environment:	Temperature: -30°C (-22°F) to 60°C (140°F) Humidity: 0%-90% non-condensating
Programming:	Via Mini Jumpers
Input Power:	Telephone Line Powered
Loop Current:	23mA min to 80mA max
Impedance:	600 ohms
Type Jack:	RJ11C
Ringer Equivalency:	0.4A
Hearing Aid Compatible:	Meets EIA standards
UL & FCC Registration:	Certified
ACCESSORIES:	301-064 Security Tool (required for installation)



ADDITIONAL OPTIONS

IP - Voice over Internet Protocol Version available on all models (SIP)

-M	-IVC	-ACH**	-LB	Open Enclosure Housing	-RIL	-RIS
Sealed Magnetic Hookswitch <ul style="list-style-type: none"> Completely Sealed No Moving Parts 	Push Button Volume Control Background Noise reducer	Other Length armored cord from 14" to 72"(inches). Example: -ACH14 14" Long	Handset with internal steel lanyard (braided metal rope) and lanyard mounting bracket that is secured onto panel for added strength.	Standard Black Housing -R Red Housing -S Stainless Steel Housing	Ring Indicator Light located on the phone panel for visual ring indication	Ring Indicator Light located on the phone panel for visual ring indication



Providing Telecommunication Solutions Since 1930

Communication Equipment
& Engineering Company

<http://www.ceeco.net>

Email: sales@ceeco.net

519 SW Park Street

Okeechobee, FL

Voice 863-357-0798

Fax 863-357-0006