MHD-341-X-IVC SPECIFICATIONS

MAGNETIC HOOKSWITCH DESK TELEPHONE WITH AUTODIAL FOR RING-DOWN OPERATION


Standard Analog Power, but also available in VoIP versions

Completely sealed dust and corrosion protected desktop stainless steel telephone with impenetrable magnetic hookswitch incased in housing. Operates as a ring-down telephone that provides dial tone; however, requires external equipment to control calling. Equipped with a 32" hearing aid compatible magnetic handset, internal volume control via volume control button with loudness symbol and background noise minimization, and steel mounting backplate.



SPECIFICATIONS

Panel Size:	6.37" W x 9.75" H x 4" D		
Weight:	Approximately 7 lbs.		
<u>Mounting Instructions:</u>	Separate the cover assembly from the backplate assembly by pulling the bottom forward and lifting up. The backplate assembly is designed rest on any flat surface.		
Environment:	Temperature: -30°C (-22°F) to 60°C (140°F) Humidity: 0%-90% non-condensating		
Input Power:	Telephone Line Powered		
Programing:	Via Mini Jumpers		
Loop Current:	23mA min to 80mA max		
Impedance:	600 ohms		
<u>Type Jack:</u>	RJ11C		
<u>Ringer Equivalency:</u>	0.4A		
Hearing Aid Compatible:	Meets EIA standards		
UL& FCC Registration:	Certified		
ACCESSORIES:	301-037 Security Tool (required for installation)		



ADDITIONAL OPTION	DDITIONAL OPTIONS IP - Voice over Internet Protocol Version available on all models (SIP)				
-IVC	-BR	-ACH18	-CCH5	-RIL	#301-037
VDLUME *3	ENERG PHONE Biological	ð	3	\bigcirc	
Push Button Volume Control • Background Noise reducer	Braille "EMER PHONE" plate on panel	18" Armored Cord Handset	5 foot Industrial Strength Coiled Cord	Ring Indicator Light located on the phone panel for visual ring indication	Security Tool (Required for installation)



Providing Telecommunication Solutions Since 1930

Communication Equipment	519 SW Park Street
& Engineering Company	Okeechobee, FL
http://www.ceeco.net	Voice 863-357-0798
Email: sales@ceeco.net	Fax 863-357-0006