# MHW-341-D-IVC SPECIFICATIONS

## MAGNETIC HOOKSWITCH WALL HANDSET TELEPHONE WITH AUTODIAL

# Standard Analog Power, but also available in VoIP versions

Completely sealed dust and corrosion protected surface mount stainless steel telephone with impenetrable magnetic hookswitch incased in housing. Operates as a hotline phone that autodials a telephone number from one to eleven digits when the handset is activated. Equipped with a 32" hearing aid compatible magnetic handset, internal volume control via volume control button with loudness symbol and background noise minimization, and steel mounting backplate.

#### **SPECIFICATIONS**

6.37" W x 9.75" H x 4" D **Panel Size:** Weight: Approximately 7 lbs.

**Mounting Instructions: Vertical Surface Mount:** Separate the cover

assembly from the backplate. The plate assembly is designed to be mounted on any flat vertical surface. • Four mounting holes: 3" W x 6" H

Temperature: -30°C (-22°F) to 60°C (140°F) **Environment:** 

Humidity: 0%-90% non-condensating

Telephone Line Powered **Input Power:** 

**Programing:** Via Mini Jumpers

23mA min to 80mA max **Loop Current:** 


600 ohms **Impedance:** RJ11C Type Jack: **Ringer Equivalency:** 0.4A


Hearing Aid Compatible: Meets EIA standards

**UL& FCC Registration:** Certified

301-037 Security Tool **ACCESSORIES:** 

(required for installation)





Voice over Internet Protocol Version available on all models (SIP)			
CCH5	-RIL	#301-037	
S			



IP - V



**ADDITIONAL OPTIONS** 

### Providing Telecommunication Solutions Since 1930

Communication Equipment	519 SW Park Street
& Engineering Company	Okeechobee, FL
http://www.ceeco.net	Voice 863-357-0798
Email: sales@ceeco.net	Fax 863-357-0006