SSP-560-D SPECIFICATIONS

LARGE FLUSH OR WALL MOUNTED HANDSFREE SPEAKERPHONE WITH AUTODIAL PUSH BUTTON FOR LOW POWER CONSUMPTION

Robust heavy gauge stainless steel flush mount or surface mount low power consumption handsfree speakerphone that automatically dials a preprogrammed number from 1-11 digits when the button is pushed and red LED light to indicate phone is activated. Press to start/press to stop button for initiation and termination of phone calls. Telephone can be programmed to cancel calls after 1, 3, or 5 minutes or no timed call-out. Phone is built with tamper resistant security screws and weatherproof, puncture resistant speaker and microphone. Optional (-SW) stainless steel surface mount box available



SPECIFICATIONS

| Panel Size: | 10.12"W x 13.12"H 2"D (Behind Panel) 2.65"D (With Wall Mounting Box) | | | | | | |
|-------------------------------|---|---|-------|-------------|---|---------------|---|
| Weight: | Approximately 6 lbs. | | | | | | |
| <u>Mounting Instructions:</u> | Rough-in flush mounting box (Standard) Dimensions: 8.50" W x 11.50"H x 2.75" D 3 mounting holes per side of panel spaced 5.25" apart vertically and two holes spaced 7.8" apart horizontally Surface Wall Mounting Box (- SW) 4 holes spaced 6W" x 9H" | Mounting Box $f - 6^{\circ} \int_{-1}^{-1}$ | 2.65" | | 0 | <u>10.12"</u> | |
| <u>Environment:</u> | Temperature: -30°C (-22°F) to 60°C (140°F) Humidity: 0%-90% non-condensating | 13.12" Wire Entry | | 13.12" I | ٥ | Ô | і L@ і 10.50' |
| Programming: | Via Mini Jumpers | | 1 | ÷ | | | 10.50 |
| Input Power: | Telephone Line Powered | 0 | | i | | | - Pi |
| Loop Current: | 27mA min to 80mA max | No. | | 1 | 6 | | <u> </u> |
| Impedance: | 600 ohms | 10.12" | | V | | | CEECO |
| <u>Type Jack:</u> | RJ11C | | | | | | |
| Ringer Equivalency: | 0.4A | | | | | | |
| UL & FCC Registration: | Certified | | | | | | |
| ACCESSORIES: | 301-037 Security Tool (required for installation When in a Box) | | | | | | |

| DDITIONAL OPTIONS IP - Voice over Internet Protocol Version available on all models (SIP) | | | | |
|--|---|---|---|--|
| -ADA | -SW | -RIL | Standard rough in mounting box | Additional Options & Features |
| ENERG. PHONE PROVE | | 0 | | Auto Answer (AA) Remote Programming (RP) Voice Announcement (VA) |
| Red/ green LED call progress indicator light Braille Emergency Plate "EMERG. PHONE" Red Push Button | Stainless steel wall/ surface mounting box | Ring Indicator Light located on the phone panel for visual ring indication. | Rough-in flush mounting box Dimensions: 8.50" W x 11.50"H x 2.75" D | |

| and the second second | _ | |
|-----------------------|---|----|
| | | |
| | | 00 |
| | | 15 |

Providing Telecommunication Solutions Since 1930

| Communication Equipment | 519 SW Park Street |
|-------------------------|--------------------|
| & Engineering Company | Okeechobee, FL |
| http://www.ceeco.net | Voice 863-357-0798 |
| Email: sales@ceeco.net | Fax 863-357-0006 |
| | |