SSP-570-D SPECIFICATIONS

STAINLESS STEEL HANDSFREE SPEAKERPHONE PANEL WITH AUTODIAL PUSH BUTTON FOR LOW POWER CONSUMPTION

Reliable stainless steel low power consumption handsfree panel speakerphone with pushbutton for ring-down operation and red LED light to indicate phone is activated. Press button to disconnect call. Telephone can be programmed to cancel calls after 1, 3, or 5 minutes or no call time-out. Phone relies on external equipment to control calling. Equipped with a black push button, tamper resistant security screws and weatherproof, puncture resistant speaker and microphone. Optional 371-011 mounting box, 371-012 frame available.





SPECIFICATIONS

Panel Size: 6.80"W x 9.87"H

2.75"D (Behind Panel)

3" D (w/ Optional Mounting Box)

Weight: Approximately 7 lbs.

Approximately 10 lbs. w/optional mounting

box and frame

Mounting: Flush Mounted

Four holes proved on front panel

Spaced: 6"W x 9"H

Optional Mounting Box available (371-011) **Box Dimensions:** 7"W x 10"H x 3" D Box Requires: mounting frame (371-012) and four mounting brackets (371-009) **Frame Dimensions:** 9.56"W x 11.54"H

Environment: Temperature: -30°C (-22°F) to 60°C (140°F)

Humidity: 0%-90% non-condensating

Programming: VIA Mini Jumpers

<u>Input Power:</u> Telephone Line Powered

Loop Current: 30mA min to 80mA max


 Impedance:
 600 ohms

 Type Jack:
 RJ11C

 Ringer Equivalency:
 0.4A

 UL & FCC Registration:
 Certified

ACCESSORIES: 301-064 Security Tool



ADDITIONAL OPTIONS		IP - Voice over Internet Protocol Version available on all models (SIP)		
-ADA	371-011 Mounting Box	371-012 Mounting Box Frame	371-009 Mounting Bracket	Additional Options & Features
ENERG PHONE				Auto Answer (AA) Remote Programming (RP) Voice Announcement (VA)
 Red/ green LED call progress indicator light Braille Emergency Plate "EMERG. PHONE" Red Push Button 	Mounting Box that requires the 371-012 frame Dimensions: 7"W x 10"H x 3" D	Frame for mounting box required with purchase of 370-011: Dimensions: 9.56" W x 11.54"H four spaced holes 7.32"W x 10.35" H	Mounting bracket for 571/570 series telephone. 4 brackets are required	



Providing Telecommunication Solutions Since 1930

0	
Communication Equipment	519 SW Park Street
& Engineering Company	Okeechobee, FL
http;//www.ceeco.net	Voice 863-357-0798
Email: sales@ceeco.net	Fax 863-357-0006