SSW-520-D SPECIFICATIONS

MINI WALL HANDFREE SPEAKERPHONE WITH AUTODIAL BUTTON FOR LOW POWER CONSUMPTION

Standard Analog Power, but also available in VoIP versions

Rugged small stainless steel wall mount handsfree low power consumption speakerphone that automatically dials a preprogrammed number from 1-11 digits when the button is pushed and red LED light to indicate phone is activated. Press button to disconnect call. Telephone can be programmed to cancel calls after 1, 3, or 5 minutes or no call time-out. Equipped with weatherproof, puncture resistant speaker and microphone, security screws, and steel mounting backplate. Emergency phone features available to include red push button and Braille EMER Phone plate.





SPECIFICATIONS

Panel Size: 5" W x 10.75" H x 3" D
Weight: Approximately 7 lbs.

Mounting Instructions: Vertical Surface Mount: Separate the cover

assembly from the backplate.

The plate assembly is designed to be mounted on any flat vertical surface.

• Four mounting holes: 3" W x 6" H

Environment: Temperature: -30°C (-22°F) to 60°C (140°F)

Humidity: 0%-90% non-condensating

Input Power: Telephone Line Powered


Programing: Via Mini Jumpers


Loop Current: 27mA min to 80mA max


Impedance:600 ohmsType Jack:RJ11CRinger Equivalency:0.4AUL& FCC Registration:Certified

ACCESSORIES: 301-037 Security Tool

(required for installation)







ADDITIONAL OPTIONS	IP - \	IP - Voice over Internet Protocol Version available on all models (SIP)		
-ADA	-RIS	-RIL	Additional Options & Features	
ENERG PHONE			Auto Answer (AA) Remote Programming (RP) Voice Announcement (VA)	
 Red/ green LED call progress indicator light Braille Emergency Plate "EMERG. PHONE" Red push button 	Ring Indicator Flashing Blue Light (Requires AC Power)	Ring Indicator Light located on the phone panel for visual ring indication		



Providing Telecommunication Solutions Since 1930

Communication Equipment	519 SW Park Street
& Engineering Company	Okeechobee, FL
http;//www.ceeco.net	Voice 863-357-0798
Email: sales@ceeco.net	Fax 863-357-0006