## WPP-531-D2 SPECIFICATIONS

## HANDSFREE SPEAKERPHONE WITH 2ND NUMBER PUSH-BUTTON AUTODIAL IN A WEATHERPROOF HOUSING

## Standard Analog Power, but also available in VoIP versions

Heavy duty stainless steel handsfree speakerphone in a cast aluminum black waterproof housing with TELEPHONE on door and pin latch for wall or pole mount. Designed to automatically dial a preprogrammed number from 1-11 digits when the button is pushed. If there is no answer when first number is dialed, phone will reset itself and dial a second preprogrammed number and red/green LED light provides visual indication of call progress. Capable of dialing a PBX or access number, block or allow incoming calls, and provides call duration time-out from 1-9 minutes or no time-out. Telephone can not be left off-hook, as it detects when called party hangs up and resets itself. Equipped with a weatherproof, puncture resistant speaker and microphone and tamper resistant security screws. ADA Emergency features Available. WPP models available in black, (-R) red, (-Y) Yellow, or (-G) Gray with TELEPHONE or EMERGENCY on door.



SPECIFICATIONS						
Panel Size:	7 1/6"W x 11 1/4"H					
Weatherproof Housing:	9 1/2"W x 12 5/8"H x 8"D (Including Door)					
Weight:	Approximately 17 lbs.					
<b>Mounting Instructions:</b>	Weatherproof Housing	7.06	- P	8"	9-1/2"	
	4 holes spaced 8" x 5 7/8"	6.57		<u>"</u>		-
	Also available pole mounting bracket	1			L.	
Environment:	Temperature: $-30^{\circ}$ C ( $-22^{\circ}$ F) to $60^{\circ}$ C ( $140^{\circ}$ F)			i E	5-7/8" →	*
Environment:	Humidity: 0%-90% non-condensating				IIT I	THE
		***	11.25 10.73		8"	8" 12-5/8"
Programming:	Via DTMF Keypad	0	0.73			. Ħ
Input Power:	Telephone Line Powered				li↓	↓
Loop Current:	30mA min to 80mA max	•			<u>41</u> •	1
Impedance:	600 ohms	50	÷, ↓		ر	
<u>Type Jack:</u>	RJ11C		<b></b> ↓   <del></del> 7/8	- SPRING	G(OPTIONAL)	
<b>Ringer Equivalency:</b>	0.4A					
UL & FCC Registration:	Certified					
ACCESSORIES:	301-064 Security Tool					
	(required for installation)					

ADDITIONAL OPTIONS IP - Voice over Internet Protocol				tocol Ve	ol Version available on all models (SIP)		
-ADA	Weatherproof Housing	-ST/-SB/-RST	-RIL	-SP	Pole Mount	Additional Options & Features	
ENERG, PHONE State States		<b>a</b>	0	-	Ë)	Auto Answer (AA) Remote Programming (RP) Voice Announcement (VA)	
<ul> <li>Red/ green LED call progress indicator light</li> <li>Braille Emergency Plate "EMERG. PHONE"</li> <li>Red push button</li> </ul>	Standard Black & TELEPHONE on Door -B-EMER Black & EMERGENCY on Door -R Red & EMERGENCY on Door -R-TEL Red & TELEPHONE on Door -Y Yellow & EMERGENCY on Door -Y-TEL Yellow & Telephone on Door -G Grey & TELEPHONE on Door -G-EMER Grey & EMERGENCY on Door	Blue Strobe Light option: • Steady on • Flashing • For location visibility • Requires AC power	Ring Indicator Light located on the phone panel for visual ring indication.	Spring loaded door option	Pole Mounting bracket fits poles 2.5" - 6".		



## **Providing Telecommunication Solutions Since 1930**

Communication Equipment	519 SW Park Street
& Engineering Company	Okeechobee, FL
http://www.ceeco.net	Voice 863-357-0798
Email: sales@ceeco.net	Fax 863-357-0006