



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: PDUMV30

**Single-Phase Metered PDU, 30A 120V, 0U Vertical Rackmount, NEMA 5-15/20R outlets, NEMA L5-30P input plug**



### Highlights

- Metered single phase 30A 120V, 0U 63.75in / 162cm vertical rackmount PDU
- Pair of digital meters report output current in amps for each load bank
- Attached 10ft / 3.0m cord with NEMA L5-30P input plug
- 24 NEMA 5-15/20R outlets in two separately breakered load banks
- Toolless button mount and bolt-down bracket installation hardware included

### Description

Tripp Lite single phase Metered PDU / Power Distribution Units offer real-time local reporting of load level in amps via built-in digital display. Enables visual monitoring of PDU load levels to prevent overloads as additional equipment is added. Offers reliable rackmount multi-outlet power distribution from any protected UPS, generator or mains input power source. High quality design includes rugged all-metal housing and secure rackmount installation with included mounting accessories.

#### Applications

- Ideal means of powering networking equipment in datacenters, computer rooms and network closets

#### Package Includes

- PDUMV30 63.75 inch basic PDU with owner's manual
- Set of 2 bolt-on plug retention brackets and installation hardware
- Set of mounting brackets and installation hardware

### Features

- 30A single phase 120V Metered Power Distribution Unit / PDU
- Set of two lighted meters report PDU output current in amps for each 12 outlet load bank
- Attached NEMA L5-30P 30A 120V input plug with 10ft / 3m line cord
- 0U vertical rackmount format installs using no rack spaces
- 24 NEMA 5-15/20R output receptacles
- Outlets are arranged in two 12 outlet load banks, each with separate 20A breaker and current metering
- Toolless installation supported in button-mount compatible equipment racks
- Bolt-down installation brackets support installation in other racks and additional surfaces
- Cord retention brackets keep vital equipment plugs connected

### Specifications

OVERVIEW	
Model Type	Metered
PDU Type	Metered
OUTPUT	

Frequency compatibility	50 / 60 Hz
Output nominal voltage	120V
Overload protection	Outlets are arranged in two separately breakered load banks. The top 20A breaker covers outlets on the upper half, the bottom 20A breaker covers outlets on the lower half of the PDU. Each breakered bank covers 12 5-15/20R outlets.
Outlet quantity / type	24 5-15/20R (each outlet accepts 5-15P or 5-20P equipment plugs)
<b>INPUT</b>	
PDU Input Voltage	100; 120; 127
Recommended Electrical Service	120V
Maximum Input Amps (A)	30
Maximum Input Amps (A) Details	Agency de-rated to 24A continuous
Input connection type	L5-30P (120V 30A)
Plug Type	NEMA L5-30P (30A 120V)
PDU Plug Type	NEMA L5-30P
Input cord length (ft.)	10
Input cord length (m)	3
Voltage compatibility (VAC)	120
Phase	Single-Phase
<b>LEDS ALARMS &amp; SWITCHES</b>	
Switches	n/a
Front panel LEDs	Includes 2 built-in 2-character LED meters to display power consumption of items plugged into each separately breakered 20A loading bank.
<b>PHYSICAL</b>	
Shipping weight (lbs)	13
Shipping weight (kg)	5.9
Unit Dimensions (HWD/in)	63.75 x 2.25 x 3.75
Unit Dimensions (HWD/cm)	162 x 5.7 x 9.5
Shipping Dimensions (HWD/in)	64.5 x 3.5 x 4.75
Shipping Dimensions (HWD/cm)	163.8 x 8.9 x 12.1
Unit weight (lbs)	8
Unit weight (kg)	3.6
Material of construction	Aluminum

<b>Style</b>	Vertical Rackmount, Wallmount, Raceway, Workbench
<b>Form factors supported</b>	0u vertical installation in equipment racks, plus under-counter and wallmount
<b>PDU Form Factor</b>	Vertical (0U)
<b>ENVIRONMENTAL</b>	
<b>Relative Humidity</b>	0-95% non-condensing
<b>CERTIFICATIONS</b>	
<b>Certifications</b>	Tested to UL60950-1 (USA, Canada), NOM (Mexico)
<b>WARRANTY</b>	
<b>Product Warranty Period (U.S., Canada &amp; Puerto Rico)</b>	Lifetime limited warranty

## Related Items

### Optional Products

Product Type	Related Model	Description	Qty.
Power Cables	<a href="#">P007-002</a>	2-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	1
Power Cables	<a href="#">P007-006</a>	6-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	1
Power Cables	<a href="#">P007-010</a>	10-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	1
Power Cables	<a href="#">P010-012</a>	12-ft. 18AWG Power cord (NEMA 5-15P to IEC-320-C13)	1
Power Cables	<a href="#">P012-006</a>	6-ft. Notebook Power cord (NEMA 1-15P to IEC-320-C7)	1
Power Cables	<a href="#">P022-001</a>	1-ft. 18AWG Power Extension cord (NEMA 5-15R to NEMA 5-15P)	1
Power Cables	<a href="#">P023-001</a>	1-ft. 14AWG Power Adapter cord (NEMA L5-15R to NEMA 5-15P)	1
Power Cables	<a href="#">P034-010</a>	10-ft. 14AWG Heavy Duty Power cord (IEC-320-C19 to NEMA 5-15P)	1
Power Cables	<a href="#">P044-061</a>	6-inch 12AWG Heavy Duty Power Adapter cord (NEMA-L5-20R to NEMA-5-20P)	1
Power Cables	<a href="#">P049-010</a>	10-ft. 12AWG Heavy Duty Power cord (IEC-320-C19 to NEMA 5-20P)	1
Rack Accessories	<a href="#">SRCABLEDUCT1U</a>	1U Horizontal Cable Manager (Finger duct with cover.)	1
Rack Accessories	<a href="#">SRCABLERING1U</a>	1U Horizontal Cable Manager (Flexible ring type.)	1
Rack Accessories	<a href="#">SRCABLERING2U</a>	2U Horizontal Cable Manager (Flexible ring type.)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=3747](http://www.tripplite.com/en/products/model.cfm?txtModelID=3747).

Copyright © 2012 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.