

A&E Specifications FS-DM-FLUSH

## FS-DM-FLUSH

## Bid-Spec

### 1.0 Description

The FS-DM-FLUSH is a fixed indoor flush ceiling mount that has been manufactured to protect the Pro Series 360° cameras. Its unique, plenum-rated design provides easy install and access for 360° cameras that need drop ceiling and overhang installations.

### 2.0 Bid Specification

- This accessory shall be compatible with the Pro Series 360° cameras.
- This accessory shall be mounted directly into a drop ceiling or overhang.
- This accessory shall feature an aluminum and steel body that is fire resistant that is plenum rated.
- This accessory shall be used for indoor applications.
- This accessory shall be supplied with one 1/2"Hex Head Stainless Steel with 1/2 x 20 thread, one 3/8" Hex Head Stainless Steel with 1/2 x 20 thread, one 1/4" Stainless Steel Flat Washer and one Stainless Steel 1/4' Split Lock Washer.



A&E Specifications FS-DM-FLUSH

## FS-DM-FLUSH

# Quick-Spec

### 3.0 Minimum Performance Specification

The FS-DM-FLUSH accessory will meet the following operating requirements:

Mechanical

Dimensions 7.9 x 8.6 in (201 x 220mm)
Weight 3.65 lbs (1656 g) w/o camera
Construction Body- 20 & 22 gauge steel

Trim- stamped steel

Flush Lens Plate- 1/8 in aluminum

**Environmental** 

Certificates Plenum rated, RoHS certified Operating Temperature 0°C to 49°C ( 32°F to 120°F)

#### **Model Number**

FS-DM-FLUSH

### Warranty

Minimum 3 Year Parts and Labor