



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

External Battery Pack for select Tripp Lite 3-Phase UPS Systems (BP480V40C)

MODEL NUMBER: **BP480V40C**



Highlights

- Extends runtime of compatible Tripp Lite UPS Systems using special "+/-" 240VDC configuration
- Hardwire installation

Package Includes

- BP480V40C external battery pack
- Warranty information
- Owner's Manual

Description

Tripp Lite's BP480V40C External Battery Pack offers extended battery runtime when used in conjunction with compatible Tripp Lite UPS systems. Includes internal disconnect for battery isolation.

Compatible UPS Systems: SU40K, SU60K, SU80K, SU20KX, SU40KX, SU60KX, SU80KX and other Tripp Lite UPS systems specifying the use of this battery pack.

Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Multiple battery packs can be daisy-chained to the UPS for even longer extended run operation

Specifications

BATTERY	
Expandable Battery Runtime	Multiple battery packs can be daisy-chained to the UPS for extended runtime
DC System Voltage (VDC)	+/- 240VDC
UPS Connection	Hardwire (contractor supplies wiring - see Owner's Manual for gauge recommendations)
Typical Battery Lifespan	3-5 years typical (North America)
PHYSICAL	
Shipping Dimensions (hwd / in.)	76.25 x 28.75 x 45.75
Shipping Dimensions (hwd / cm)	193.7 x 73 x 116.2
Shipping Weight (lbs.)	1960
Shipping Weight (kg)	889.8



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Unit Dimensions (hwd / in.)	66.9 x 20.5 x 33.7
Unit Dimensions (hwd / cm)	169.9 x 52.1 x 85.6
Unit Weight (lbs.)	1603
Unit Weight (kg)	727.8
Material of Construction	Steel
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.