

## DVI to VGA Y Splitter Adapter Cable (DVI-I-M to 2x HD15-F), 1-ft.

MODEL NUMBER: P120-001-2



### Description

Tripp Lite's P120-001-2 DVI to 2 x VGA splitter allows you to attach two VGA enabled devices, such as monitors and projectors, to your computer's DVI-I port. DVI-I enabled computers are capable of outputting both Analog and Digital signals, so the splitter is perfect for connecting VGA LCD monitors, projectors simultaneously. (For splitting to two DVI-enabled monitors, use Tripp Lite P564-001). Fully molded construction and double-shielding ensures long life and high performance. Supports video resolutions up to 2048 x 1536.

### Features

- Connect two VGA monitors to a single DVI-I port
- 1 ft. DVI-A Analog Male to 2 x VGA (HD15) Female Cable
- Fully molded construction and double-shielding ensures long life
- Superior video quality; supports video resolutions up to 2048 x 1536
- RoHS Compliant

## Specifications

OVERVIEW	
Chromebook Compatible	No
Display Style	Adapter
Model Type	VGA
Cable Types	DVI
INPUT	
Cable Length (ft.)	1

### Highlights

- Splits a DVI-A Analog signal to connect two VGA-enabled devices to a single DVI-I port
- Ideal solution when you need to display a video signal to 2 monitors for presentations.
- Fully molded construction and double-shielding guarantees long life
- Superior video quality; supports video resolutions up to 2048 x 1536

### System Requirements

- DVI-I enabled computer (supports both Analog and Digital)

### Package Includes

- 1 ft. DVI-A Analog Male to 2 x VGA (HD15) Female Cable



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

Cable Length (m)	0.30
<b>PHYSICAL</b>	
Color	Black
<b>CONNECTIONS</b>	
Connector A	DVI-A (MALE)
Connector B	HD15 (FEMALE) (X2)
Connector C	HD15 (Female)
Number of Connectors	3
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.