

Null Modem Serial DB9 Serial Cable (DB9 to DB25 F/M), 6-ft.

MODEL NUMBER: P456-006







Highlights

- Superior molded cables with foil-shielding for maximum EMI/RFI protection
- Gold-plated connectors provide superior conductivity
- Null modem cables connect two serial devices that require a null modem configuration

System Requirements

 Two serial devices (one with a DB25 Male connector and the Other with a DB9 Female connector) requiring a null modem (cross-wired) configuration.

Package Includes

 6-ft. Null Modem Gold Cable DB9F to DB25M

Description

Null modem cables and adapters connect two serial devices that require a null modem (cross-wired) configuration. This 6ft cable has a DB9 female connector on one end and a DB25 male connector on the other.

Superior molded cables with foil-shielding offer maximum EMI/RFI protection. Gold-plated connectors and contacts provide superior conductivity.

Features

- DB9 female to DB25 male
- Superior molded cables with foil-shielding for maximum EMI/RFI protection
- · Gold-plated connectors provide superior conductivity

Specifications

OVERVIEW		
Style	Null Modem Cables	
Cable Types	NULL MODEM	
INPUT		
Cable Length (ft.)	6	
Cable Length (m)	1.83	
PHYSICAL		
Color	Black	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

CONNECTIONS		
Connector A	DB9 (FEMALE)	
Connector B	DB25 (MALE)	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.