

# 6-Outlet Industrial Surge Protector, 6-ft. Cord, 900 Joules, 15 in. length

MODEL NUMBER: PM6NS











#### **Highlights**

- . 6 outlets/6 ft. cord
- 900 joules

## **Applications**

 Offers multiple outlet power distribution and surge suppression in workbench, wallmount or floor mount applications. Ideal protection for home appliances, entertainment centers, industrial equipment and other electronic loads.

## Package Includes

- PM6NS Power Strip
- Warranty information
- Instruction manual

#### **Description**

The Waber-by-Tripp Lite PM6NS Power Strip offers a convenient method of power distribution and surge suppression in workbench, wallmount or floor mount applications. Includes 6 NEMA 5-15R output receptacles, 6 foot AC line cord and keyhole mounting tabs for installation in a wide variety of applications. Protects connected equipment from transient surges and line noise with built in surge suppression rated at 900 joules. Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features metal housing, lighted power switch with integrated 15 amp resettable circuit breaker and attractive beige housing with black output receptacles and power cord.

PLUG/OUTLETS - Input: NEMA 5-15P/Output: 6 NEMA 5-15R

ELECTRICAL - 120VAC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT - Corded power distribution strip with surge suppression

SUPPRESSION - 900 joules AC suppression

#### **Features**

- Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications
- Includes 6 NEMA 5-15R output receptacles
- Lighted combination power switch with integrated circuit breaker
- Keyhole mounting tabs for installation in a wide variety of applications
- UL1449 3rd Edition (USA/400V rating), UL1363 (USA), cUL (Canada)
- 15 amp power handling capacity
- 6 foot AC line cord
- 900 joule rating

# **Specifications**





OVERVIEW		
Style	Strip	
OUTPUT		
Frequency Compatibility	50 / 60 Hz	
Output Receptacles	(6) 5-15R	
Output (Watts)	1800	
Circuit Breaker (amps)	15	
USB Charging	No	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Connection Type	NEMA 5-15P input plug	
Input Cord Length (ft.)	6	
Input Cord Length (m)	1.83	
Input Cord Gauge Type	14 gauge, SJT	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	45000	
USER INTERFACE, ALERTS & CON	TROLS	
Switches	Combination AC circuit breaker and lighted two position power switch controls power to all outlets	
Diagnostic LEDs	Protection present (green)	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	900	
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
UL1449 Let Through Rating	400V - UL Verified	
EMI / RFI Filtering	Up to 20dB	
Immunity	Conforms to IEE 587 / ANSI C62.41	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	No	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	





PHYSICAL		
Shipping Dimensions (hwd / in.)	2.25 x 15 x 6	
Shipping Dimensions (hwd / cm)	5.72 x 38.1 x 15.24	
Shipping Weight (lbs.)	1.85	
Shipping Weight (kg)	0.84	
Unit Dimensions (hwd / in.)	1.5 x 12.5 x 2.5	
Unit Dimensions (hwd / cm)	3.81 x 31.75 x 6.35	
Unit Weight (lbs.)	1.2	
Unit Weight (kg)	0.54	
Material of Construction	Metal	
Integrated Keyhole Mounting Tabs	Keyhole mounting tabs enable wall mounting	
Receptacle Color	Black	
Color (AC Line Cord)	Black	
Outlets Measurement (Center to Center)	38.89mm	
Keyhole Slot Mounting Measurement (Center to Center)	165mm	
SPECIAL FEATURES		
Right-Angle Plug	No	
CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition	
UL1363 (Power Tap)	UL1363	
cUL / CSA (Canada)	cUL	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.