

# SmartRack Thermal Duct Kit for SmartRack Enclosures

MODEL NUMBER: **SRTHERMDUCT**



## Description

The SRTHERMDUCT Thermal Duct Kit can change a standard SmartRack 42-48U enclosure into a sealed passive cooling structure that allows heat built up inside a rack to be directed up and into the facility CRAC / HVAC return air system.

## Features

- Improves cooling efficiency of standard Tripp Lite rack enclosures
- Adjustable roof-mount thermal duct connects to HVAC return air system
- Included gaskets and panels help seal enclosure for proper airflow management through thermal duct
- Compatible with standard 42-48U SmartRack Enclosures

## Highlights

- Improves cooling efficiency in Tripp Lite standard rack enclosures
- Adjustable roof-mounted thermal duct moves air upward and out of the rack enclosure
- Compatible with standard 42-48U SmartRack Enclosures

## System Requirements

Standard 42-48U Tripp Lite Rack Enclosure

## Package Includes

- Height-adjustable roof-mount thermal duct
- Roof-mount cable access panel
- Enclosure bottom
- Door gasket seals
- (12) Magnetic vinyl sheet rear door seals
- (4) M8 screws
- (4) M4 screws
- (16) M4 nuts
- Owner's manual

# Specifications

OVERVIEW	
Model Type	Passive Cooling
Accessories Type	Duct Kit
PHYSICAL	
Shipping Dimensions (hwd / in.)	11.8 x 25.6 35.4
Shipping Dimensions (hwd / cm)	29.97 x 65.02 x 89.92
Shipping Weight (lbs.)	70
Shipping Weight (kg)	31.5
Housing Color	Black



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

Roof	Thermal duct adjusts between 20.5-34.5 inches when assembled.
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	5-year limited warranty

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.