



## SNA Terminal Blocks T&B Catalog Number:

UPC Number: Status: Description: 029041006 66201997088 Active

Gray, feed through terminal block with 6 mm spacing, 25 Amp rated UL current with spring clamp connection that accepts 24-10 AWG UL wire range

Features

	Top entry wire connection
	Touch-safe IP20 protection
Application	
Application	
	For use with applications ranging from standard distribution and control panels, to specialized ap- plications in key industries such as traction, ener- gy, maritime, explosive atmospheres, material han- dling, etc.
General	
Style	Feed Through
Color	Gray
Mounting	DIN 3
Series	D 4/6.4L
Connection Technology	Spring Clamp
UL Wire Range (AWG)	24-10
Rated IEC Wire Range (Solid) (mm2)	4
Rated CSA Wire Size (AWG)	10
Dimension Information	
L x W x H (mm)	94.5 x 6 x 27.2
L x W x H (mm) Spacing (mm)	94.5 x 6 x 27.2 6
,	
Spacing (mm)	6
Spacing (mm) L x W x H (in)	6 3.72 x .238 x 1.07
Spacing (mm) L x W x H (in) Spacing (inches)	6 3.72 x .238 x 1.07
Spacing (mm) L x W x H (in) Spacing (inches) <b>Specifications</b>	6 3.72 x .238 x 1.07 0.236
Spacing (mm) L x W x H (in) Spacing (inches) <b>Specifications</b> UL Current (Amps)	6 3.72 x .238 x 1.07 0.236 25
Spacing (mm) L x W x H (in) Spacing (inches) <b>Specifications</b> UL Current (Amps) UL Voltage (VAC)	6 3.72 x .238 x 1.07 0.236 25 600
Spacing (mm) L x W x H (in) Spacing (inches) <b>Specifications</b> UL Current (Amps) UL Voltage (VAC) Rated UL Wire Size (AWG)	6 3.72 x .238 x 1.07 0.236 25 600 10
Spacing (mm) L x W x H (in) Spacing (inches) <b>Specifications</b> UL Current (Amps) UL Voltage (VAC) Rated UL Wire Size (AWG) IEC Voltage (VAC)	6 3.72 x .238 x 1.07 0.236 25 600 10 800
Spacing (mm) L x W x H (in) Spacing (inches) <b>Specifications</b> UL Current (Amps) UL Voltage (VAC) Rated UL Wire Size (AWG) IEC Voltage (VAC) IEC Current (Amps)	6 3.72 x .238 x 1.07 0.236 25 600 10 800 32
Spacing (mm) L x W x H (in) Spacing (inches) <b>Specifications</b> UL Current (Amps) UL Voltage (VAC) Rated UL Wire Size (AWG) IEC Voltage (VAC) IEC Current (Amps) CSA Voltage (VAC)	6 3.72 x .238 x 1.07 0.236 25 600 10 800 32 600
Spacing (mm) L x W x H (in) Spacing (inches) <b>Specifications</b> UL Current (Amps) UL Voltage (VAC) Rated UL Wire Size (AWG) IEC Voltage (VAC) IEC Current (Amps) CSA Voltage (VAC) CSA Current (Amps)	6 3.72 x .238 x 1.07 0.236 25 600 10 800 32 600
Spacing (mm) L x W x H (in) Spacing (inches) <b>Specifications</b> UL Current (Amps) UL Voltage (VAC) Rated UL Wire Size (AWG) IEC Voltage (VAC) IEC Current (Amps) CSA Voltage (VAC) CSA Current (Amps) <b>Packaging</b>	6 3.72 x .238 x 1.07 0.236 25 600 10 800 32 600 25
Spacing (mm) L x W x H (in) Spacing (inches) <b>Specifications</b> UL Current (Amps) UL Voltage (VAC) Rated UL Wire Size (AWG) IEC Voltage (VAC) IEC Current (Amps) CSA Voltage (VAC) CSA Current (Amps) <b>Packaging</b> T&B Order Multiple	6 3.72 x .238 x 1.07 0.236 25 600 10 800 32 600 25 50
Spacing (mm) L x W x H (in) Spacing (inches) <b>Specifications</b> UL Current (Amps) UL Voltage (VAC) Rated UL Wire Size (AWG) IEC Voltage (VAC) IEC Current (Amps) CSA Voltage (VAC) CSA Current (Amps) <b>Packaging</b> T&B Order Multiple T&B Inner Pack	6 3.72 x .238 x 1.07 0.236 25 600 10 800 32 600 25 50 50

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125



www.tnb.com

Memphis, TN 38125

Fax: (901) 252-1321 Email:techsupport@tnb.com