Thomas@Betts





Project: 799A METROPLITAN HOTEL

Dynamic Braking / DC Drive T&B Catalog Number:

EHDB280C2P-1L

UPC Number: 66201943952 Status: Active

Description:

2 pole, 2 NO, plus 1 NO and 1 NC auxiliary contacts, 280 amp, DC drive, dynamic breaking contactor, with a 120V AC coil

dynamic breaking contactor, with Features	a 120V ÁC coil
	Double-break contacts with magnetic arc chutes
	Elevator service rated
Standards	
	cULus
Application	
	For use with solid state DC adjustable speed drive systems
General	
Octob	FUDD
Series	EHDB
Poles	2 NO AC
Coil Type	1 NO and 1 NC
Auxiliary Contacts Dimension Information	I NO and I NC
Dimension information	
H x W x D (inches)	7.79 x 5.35 x 6.65
Specifications	
Coil Voltage	120V AC
DC Continuous Current (A)	280
DC Power Pole Make/Break Voltage (V)	600
DC Power Pole Make/Break Current (C)	425
DC Dynamic Braking Pole Make Voltage	600
(V)	FCF
DC Dynamic Braking Pole Make Current (A)	303
DC Dynamic Braking Pole Break Voltage (V)	300
DC Dynamic Braking Pole Break Current (A)	363
Packaging	
Packago in Units	1
Package in Units T&B Sold in UOM	Each
	9.9 lbs. Each
T&B Weight Per UOM	3.3 IUS. Laul

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com