



Safety Switches T&B Catalog Number:

2TLA050007R0012

UPC Number:

80432583184

Status:

Active

Description:

Solenoid locking interlock safety switch featuring guard holding up to 1800N

Features

The MKey 9 series guard locking switches have a slim plastic body design and have been developed with a holding force of 1800N to keep medium guard doors closed until hazards have been removed

The high specification plastic body has a high resistance to chemical and washdown solutions and the stainless steel head provides a durable robust protection of the cam interlock

IP67 enclosure protection is maintained by a double seal lid gasket design and metal fixings

They have a slim profile and are designed to fit on 50mm frame (2 in) frame sections or to applications where space is restricted

The head will rotate to provide up to 8 actuator entry positions

An LED is available to indicate lock status

Application

Ensures that a machine stops when a door or a hatch is opened

General

Style Locking Switches

Series MKey 9

Dimension Information

L x W x H (mm) 160 x 46 x 45.50

L x W x H (in) 6.30 x 1.81 x 1.79

Packaging

Package in Units 1

T&B Sold in UOM Each

T&B Weight Per UOM 1.42 lbs. Each

Certifications

Approvals C_UL_US, CE, TUV

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com