

Standard T&B Catalog Number:

UPC Number: Status: Description: TY27M-2 78621084500 Active

Cable Tie 120lb 13" Red Nylon with Stainless Steel Locking Device Bulk Pk, Military Specified (MIL-SPEC MS3367-3-2) **Features**

| | Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulk- heads. Non-magnetic stainless steel locking device |
|--|--|
| | insures both maximum strength and the right tight- ness every time. |
| | Because there are no notches, Ty-Rap ties provide an infinite number of locking positions while fasten- ing the tie at the precise bundle diameter needed. |
| | The No-Slip Tail provides easy grip during tension- ing. Ty-Rap ties feature a unique friction surface de- signed to reduce slippage during installation. |
| | Smooth, notchless body reduces stress concentra- tion points under tension, making the tie stronger and lower profile than notched body ties. Ribbed and Stippled body grips the bundle and prevents slippage. Rounded edges protect insulation, pre- venting sharp edges from damaging cables. |
| General | |
| Material | Nylon 6.6 |
| Color | Red |
| Dimension Information | |
| | |
| Nominal Length (inches) | 13 |
| Length (inches) | 13.4 |
| Width (inches) | .270 |
| Max. Wire Bundle Diameter (inches) Specifications | 3.5 |
| Specifications | |
| Temperature Rating | -40°F to 185°F |
| Flammability Rating | UL 94 V-2 |
| Tooling | |
| Application Tools | WT197, ERG120 |
| Packaging | |
| | |
| T&B Order Multiple | 500 |
| T&B Inner Pack | 500 |
| Package in Units | 1000 |
| Package Type | Bulk |
| T&B Sold in UOM | Each |
| T&B Weight Per UOM | 1.06 lbs. per 100 |
| Application Support | |
| Material Selection Guide | Available on Website |
| Available Colors | Available on Website |
| Certifications | |



RoHS Compliance

Yes

For further technical assistance, please contact us...

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com