





## DIRECT-TO-CARD MONOCHROME PRINTER

- Affordable economical and reliable ID issuance
- Convenient operation plug-and-play; minimal maintenance required
- Efficient simple all-in-one card personalization with optional magnetic stripe encoding

## **TECHNOLOGY HIGHLIGHTS**

- Simple one-color, single-side, edge-toedge printing
- Eco-friendly refillable ribbon cartridge reduces cost and waste
- Print to standard CR-80 and CR-79 cards, from 9 mil to 40 mil thick
- Optional resin-erase and rewrite capability for visitor badges and temporary workers
- Optional magnetic stripe encoding

## **APPLICATIONS**

- Bank and financial services payment cards
- Casino employee and member ID
- Employee and temporary badges for small- to medium-sized businesses
- Retail loyalty program member ID and payment cards

The FARGO® DTC1000M Monochrome printer delivers the ultimate simplicity in card personalization. The affordable printer is easy to use, virtually maintenance-free and economical to operate.

The DTC1000M is the cost-effective, low- to moderate-volume card issuance solution for organizations such as casinos, financial services firms, small businesses and retailers. An eco-friendly erase-and-rewrite option also makes the printer ideal for visitor badges and temporary worker ID applications.

The DTC1000M prints a single color, edge-to-edge image on one side of a standard CR-80 or CR-79 identification card. The resin thermal transfer process assures clear reproduction of photo images, bar codes and alphanumeric data.

Connect quickly via USB or optional Ethernet port and begin creating ID badges within seconds. With the built-in Swift  $ID^{TM}$  application, you can start printing without having to install any

additional software. Receive instant system status cues through color-coded buttons during your printing operation.

Ribbon options include standard or premium black, or your choice of green, blue, red, white, silver or gold.

Print ribbon and card-cleaning roller installation is a snap with the cartridge-based design. A standard refillable cartridge for black resin ribbons decreases waste and reduces cost in the most common resin printing applications.

For magnetic stripe cards, an optional module enables inline, onestep encoding and card printing.

The FARGO DTC1000M Monochrome printer is built to the quality and reliability standards of every Genuine HID™ product. It is fully interoperable with other HID Global products and solutions, as well as most third party systems, enabling organizations to leverage their existing technology investments.



## **SPECIFICATIONS**

Model Name	DTC1000 Monochrome
Print Method	Resin thermal transfer
Resolution	300 dpi (11.8 dots/mm)
Colors	Monochrome: black, green, blue, red, white, silver or gold
	Provided as Refill Ribbon for Cartridge in Printer: • Resin black (standard and premium): 1,000 prints
Print Ribbon Options	Provided in Disposable Ribbon Cartridge:  Resin black and overlay panel, KO*: 500 prints Resin green, blue, red, white, silver or gold: 1000 prints Rewrite technology - No ribbon is required Standard resin black refillable ribbon cartridge (included)
Print Speed**	7 seconds per card (K*); 12 seconds per card (KO*)
Accepted Standard Card Sizes	CR-80, 3.375 in. L $\times$ 2.125 in W (85.6 mm L $\times$ 54 mm W); CR-79 adhesive back, 3.313 in L $\times$ 2.063 in W (84.1 mm L $\times$ 52.4 mm W)
Print Area	CR-80 edge-to-edge, 3.36 in L x 2.11 in W (85.3 mm L x 53.7 mm W); CR-79, 3.3 in L x 2.04 in W (83.8 mm L x 51.8 mm W)
Accepted Card Thickness	0.009 in to 0.040 in (0.229 mm to 1.016 mm)
Accepted Card Types	PVC or polyester cards with polished PVC finish; monochrome resin required for 100% polyester cards; optical memory cards with PVC finish
	optical memory cards with FVC milish
Input Hopper Card Capacity	100 cards at 0.030 in (0.762 mm)
Input Hopper Card Capacity	100 cards at 0.030 in (0.762 mm)
Input Hopper Card Capacity Output Hopper Card Capacity	100 cards at 0.030 in (0.762 mm)  Up to 30 cards at 0.030 in (0.762 mm)
Input Hopper Card Capacity Output Hopper Card Capacity Card Cleaning	100 cards at 0.030 in (0.762 mm)  Up to 30 cards at 0.030 in (0.762 mm)  Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon chan
Input Hopper Card Capacity Output Hopper Card Capacity Card Cleaning Memory	100 cards at 0.030 in (0.762 mm)  Up to 30 cards at 0.030 in (0.762 mm)  Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon chan  32 MB RAM  Windows* XP and Vista* (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit).
Input Hopper Card Capacity Output Hopper Card Capacity Card Cleaning Memory Software Drivers	100 cards at 0.030 in (0.762 mm)  Up to 30 cards at 0.030 in (0.762 mm)  Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon chan 32 MB RAM  Windows* XP and Vista* (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit).  MAC: OS X 10.5 & 10.6. Linux***
Input Hopper Card Capacity Output Hopper Card Capacity Card Cleaning Memory Software Drivers Interface	100 cards at 0.030 in (0.762 mm)  Up to 30 cards at 0.030 in (0.762 mm)  Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon chan 32 MB RAM  Windows* XP and Vista* (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit).  MAC: OS X 10.5 & 10.6. Linux***  USB 2.0, optional Ethernet with internal print server
Input Hopper Card Capacity Output Hopper Card Capacity Card Cleaning Memory Software Drivers Interface Operating Temperature	100 cards at 0.030 in (0.762 mm)  Up to 30 cards at 0.030 in (0.762 mm)  Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon chan 32 MB RAM  Windows* XP and Vista* (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit).  MAC: OS X 10.5 & 10.6. Linux***  USB 2.0, optional Ethernet with internal print server  65° to 80° F / 18° to 27° C
Input Hopper Card Capacity Output Hopper Card Capacity Card Cleaning Memory Software Drivers Interface Operating Temperature Humidity	100 cards at 0.030 in (0.762 mm)  Up to 30 cards at 0.030 in (0.762 mm)  Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon chan 32 MB RAM  Windows* XP and Vista* (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit).  MAC: OS X 10.5 & 10.6. Linux***  USB 2.0, optional Ethernet with internal print server  65° to 80° F / 18° to 27° C  20% to 80% non-condensing
Input Hopper Card Capacity Output Hopper Card Capacity Card Cleaning Memory Software Drivers Interface Operating Temperature Humidity Dimensions	100 cards at 0.030 in (0.762 mm)  Up to 30 cards at 0.030 in (0.762 mm)  Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon chan 32 MB RAM  Windows* XP and Vista* (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit).  MAC: OS X 10.5 & 10.6. Linux***  USB 2.0, optional Ethernet with internal print server  65° to 80° F / 18° to 27° C  20% to 80% non-condensing  8.8 in H x 13.7 in W x 7.9 in D (224 mm H x 348 mm W x 201 mm D)
Input Hopper Card Capacity Output Hopper Card Capacity Card Cleaning Memory Software Drivers Interface Operating Temperature Humidity Dimensions Weight	100 cards at 0.030 in (0.762 mm)  Up to 30 cards at 0.030 in (0.762 mm)  Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon chan 32 MB RAM  Windows* XP and Vista* (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit).  MAC: OS X 10.5 & 10.6. Linux***  USB 2.0, optional Ethernet with internal print server  65° to 80° F / 18° to 27° C  20% to 80% non-condensing  8.8 in H x 13.7 in W x 7.9 in D (224 mm H x 348 mm W x 201 mm D)  7.5 lbs (3.4 Kg)  Safety: UL 60950-1, CSA C22.2 (60950-1), and CE;
Input Hopper Card Capacity Output Hopper Card Capacity Card Cleaning Memory Software Drivers Interface Operating Temperature Humidity Dimensions Weight Agency Listings	100 cards at 0.030 in (0.762 mm)  Up to 30 cards at 0.030 in (0.762 mm)  Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon chan 32 MB RAM  Windows* XP and Vista* (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit).  MAC: OS X 10.5 & 10.6. Linux***  USB 2.0, optional Ethernet with internal print server  65° to 80° F / 18° to 27° C  20% to 80% non-condensing  8.8 in H x 13.7 in W x 7.9 in D (224 mm H x 348 mm W x 201 mm D)  7.5 lbs (3.4 Kg)  Safety: UL 60950-1, CSA C22.2 (60950-1), and CE; EMC: FCC Class A, CE (EN 55022 Class A, EN 55024), CCC, BSMI, KC
Input Hopper Card Capacity Output Hopper Card Capacity Card Cleaning Memory Software Drivers Interface Operating Temperature Humidity Dimensions Weight Agency Listings ENERGY STAR* / Green	100 cards at 0.030 in (0.762 mm)  Up to 30 cards at 0.030 in (0.762 mm)  Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon chan 32 MB RAM  Windows* XP and Vista* (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit).  MAC: OS X 10.5 & 10.6. Linux***  USB 2.0, optional Ethernet with internal print server  65° to 80° F / 18° to 27° C  20% to 80% non-condensing  8.8 in H x 13.7 in W x 7.9 in D (224 mm H x 348 mm W x 201 mm D)  7.5 lbs (3.4 Kg)  Safety: UL 60950-1, CSA C22.2 (60950-1), and CE; EMC: FCC Class A, CE (EN 55022 Class A, EN 55024), CCC, BSMI, KC  ENERGY STAR qualified printer and refillable supply cartridges
Input Hopper Card Capacity Output Hopper Card Capacity Card Cleaning Memory Software Drivers Interface Operating Temperature Humidity Dimensions Weight Agency Listings ENERGY STAR* / Green Supply Voltage	100 cards at 0.030 in (0.762 mm)  Up to 30 cards at 0.030 in (0.762 mm)  Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon chan 32 MB RAM  Windows* XP and Vista* (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit).  MAC: OS X 10.5 & 10.6. Linux***  USB 2.0, optional Ethernet with internal print server  65° to 80° F / 18° to 27° C  20% to 80% non-condensing  8.8 in H x 13.7 in W x 7.9 in D (224 mm H x 348 mm W x 201 mm D)  7.5 lbs (3.4 Kg)  Safety: UL 60950-1, CSA C22.2 (60950-1), and CE; EMC: FCC Class A, CE (EN 55022 Class A, EN 55024), CCC, BSMI, KC  ENERGY STAR qualified printer and refillable supply cartridges  100-240Vac, 50-60Hz, 1.6 Amps max.
Input Hopper Card Capacity Output Hopper Card Capacity Card Cleaning Memory Software Drivers Interface Operating Temperature Humidity Dimensions Weight Agency Listings ENERGY STAR* / Green Supply Voltage Supply Frequency	100 cards at 0.030 in (0.762 mm)  Up to 30 cards at 0.030 in (0.762 mm)  Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon chan 32 MB RAM  Windows* XP and Vista* (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit).  MAC: OS X 10.5 & 10.6. Linux***  USB 2.0, optional Ethernet with internal print server  65° to 80° F / 18° to 27° C  20% to 80% non-condensing  8.8 in H x 13.7 in W x 7.9 in D (224 mm H x 348 mm W x 201 mm D)  7.5 lbs (3.4 Kg)  Safety: UL 60950-1, CSA C22.2 (60950-1), and CE; EMC: FCC Class A, CE (EN 55022 Class A, EN 55024), CCC, BSMI, KC  ENERGY STAR qualified printer and refillable supply cartridges  100-240Vac, 50-60Hz, 1.6 Amps max.  50 Hz / 60 Hz
Input Hopper Card Capacity Output Hopper Card Capacity Card Cleaning Memory Software Drivers Interface Operating Temperature Humidity Dimensions Weight Agency Listings ENERGY STAR* / Green Supply Voltage Supply Frequency Warranty	100 cards at 0.030 in (0.762 mm)  Up to 30 cards at 0.030 in (0.762 mm)  Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon chan 32 MB RAM  Windows* XP and Vista* (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit).  MAC: OS X 10.5 & 10.6. Linux***  USB 2.0, optional Ethernet with internal print server  65° to 80° F / 18° to 27° C  20% to 80% non-condensing  8.8 in H x 13.7 in W x 7.9 in D (224 mm H x 348 mm W x 201 mm D)  7.5 lbs (3.4 Kg)  Safety: UL 60950-1, CSA C22.2 (60950-1), and CE; EMC: FCC Class A, CE (EN 55022 Class A, EN 55024), CCC, BSMI, KC  ENERGY STAR qualified printer and refillable supply cartridges  100-240Vac, 50-60Hz, 1.6 Amps max.  50 Hz / 60 Hz  Printer - 2 years; Printhead - 2 years, unlimited pass with UltraCard*
Input Hopper Card Capacity Output Hopper Card Capacity Card Cleaning Memory Software Drivers Interface Operating Temperature Humidity Dimensions Weight Agency Listings ENERGY STAR* / Green Supply Voltage Supply Frequency Warranty Encoding Options	100 cards at 0.030 in (0.762 mm)  Up to 30 cards at 0.030 in (0.762 mm)  Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon chan 32 MB RAM  Windows* XP and Vista* (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit).  MAC: OS X 10.5 & 10.6. Linux***  USB 2.0, optional Ethernet with internal print server  65° to 80° F / 18° to 27° C  20% to 80% non-condensing  8.8 in H x 13.7 in W x 7.9 in D (224 mm H x 348 mm W x 201 mm D)  7.5 lbs (3.4 Kg)  Safety: UL 60950-1, CSA C22.2 (60950-1), and CE; EMC: FCC Class A, CE (EN 55022 Class A, EN 55024), CCC, BSMI, KC  ENERGY STAR qualified printer and refillable supply cartridges  100-240Vac, 50-60Hz, 1.6 Amps max.  50 Hz / 60 Hz  Printer - 2 years; Printhead - 2 years, unlimited pass with UltraCard*  ISO Magnetic Stripe Encoding, dual high- and low-coercivity, Tracks 1, 2 and 3





North America: +1 949 732 2000 Toll Free: 1 800 237 7769

Europe, Middle East, Africa: +44 1440 714 850

Asia Pacific: +852 3160 9800 Latin America: +52 55 5081 1650 An ASSA ABLOY Group brand

© 2012 HID Global Corporation/ASSA ABLOY AB. All rights reserved. HID, HID Global, the HID Blue Brick logo, the Chain Design and FARGO are trademarks or registered trademarks of HID Global or its licensor(s)/supplier(s) in the US and other countries and may not be used without permission. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. 2012-08-08-fargo-dtc1000M-printer-ds-en

<sup>\*</sup> Indicates the ribbon type and the number of ribbon panels printed where K=Resin Black and O=Overlay.

\*\* Print speed indicates an approximate print speed and is measured from the time a card drops into the output hopper to the time the next card drops into the output hopper. Print speeds do not include encoding time or the time needed for the PC to process.

<sup>\*\*\*</sup>Linux versions: Ubuntu 8.04/9.04, Red Hat 5, Fedora 7/8/9/10/11, Open Suse 10.3, Debian 5.03/5.04, Mandiva one 2009