

# Indala Mid-Range Card Readers

## Indala FlexSecur® Technology for the Industry's Most Secure Proximity Readers - Exclusive Indala FlexSecur

Password-Protected Security between card and reader screens out unauthorized cards prior to sending access control data to the host system.

## Superior Format Control for the Most Application Choices - Indala products offer card

formats of up to 172 bits, and readers configurable for Wiegand, Magstripe, and Serial output formats.

## Indala Mid-Range Series Readers are Part of an Expansive Product Portfolio That Meets Every Proximity Reader Requirement – The HID

Indala Proximity portfolio includes classic, mullion/slim, wallswitch, mid-range, long-range, and heavy-duty keypad readers for every application.



## ACCESS choice.

The Indala 125 kHz Mid-Range Reader product line is HID's latest offering of highly-secure proximity readers. The HID Indala Mid-Range reader, with FlexSecur® technology, is designed for applications requiring a longer read range of up to 12 inches. These high-quality Indala Proximity Readers deliver outstanding and consistent performance with intelligent programming technology, a uniform core module, and a range of stylish bezel designs including Arch and Wave in a variety of colors.

## Exclusive FlexSecur® Security Technology

All HID Indala 125 kHz Proximity Readers feature FlexSecur technology, which provides an added level of access system security through a verification process at the reader. A unique HID Indala product feature, FlexSecur screens out unauthorized cards prior to sending access control data to the host system.

This additional verification step enhances the security of your access system in two ways:

1. The entire card data field is encrypted prior to programming the card. Therefore, the data on the card cannot be decoded to determine the actual information on the card. Only the reader is able to decrypt the data and transmit it to the access control system.
2. Cards and readers can be programmed uniquely for each site, protecting the end user against unauthorized entry attempts by using cards from another facility. Again, a feature unique to the HID Indala product line.

## Key Features:

- The Mid-Range reader can be mounted on both U.S. style single and double gang back boxes.
- Suitable for indoor and outdoor use.
- The larger size reader gives a longer read range than the HID Indala Mullion or Wallswitch readers, while offering the same modern design in a variety of bezel choices.

# Features

## Many Reader Bezel Style Choices for Design Flexibility

Stylish readers are available in many attractive, "snap-on" bezel styles and colors.

## Indoor / Outdoor Flexibility

All readers are fully potted and have weatherproof electronics assemblies, making them suitable for internal and external applications.

## Audio Tone Programming Flexibility

Standard, independently controllable audio tone is not tied to LED function.

## Compatible with Any Control Panel

Wiegand or Magnetic Stripe (Clock & Data) output easily interfaces with most existing access-control panels.

## Unbeatable Warranty and Technical Support

Customers can select HID Indala 125 kHz Proximity Readers with confidence because HID offers a lifetime product warranty and global Technical Support.

## Card Programming

The ProxSmith® Programmer System and Application Programming Interface puts flexibility and convenience in the hands of OEM and security professionals. With the ability to quickly program a card or reader on site, users no longer need to rely on the factory for custom formatted cards or readers. Plus, the ProxSmith Programmer System delivers the high level of security you expect from the HID Indala product line.

## Mid-Range Readers


<b>Mounting</b>	Metal or plastic single or double gang outlet box		
<b>Dimensions</b>	Arch - 5.1"H x 6.1"W x 1.1"T (13.0 x 15.5 x 2.8 cm); Wave - 5.5"H x 6.4"W x 1.4"T (14.0 x 16.3 x 3.5 cm)		
<b>Power Supply</b>	4-14 VDC		
<b>Current Requirements</b>	117 mA		
<b>Operating Temperature</b>	-31° F to 149° F (-35° C to 65° C)		
<b>Operating Humidity</b>	0-95% RH, non-condensing		
<b>Transmit Frequency</b>	125 kHz		
<b>Environmental Certifications</b>	IP55		
	UL294/cUL, FCC (US), Canada, CE Mark (Europe), Australia C-Tick, New Zealand EMC		
<b>Base Part Number</b>	<b>Product Description</b> Wave, Black Wave, Blue Wave, Black (Serial) Wave, Blue (Serial) Arch, Black Arch, Grey Arch, White Arch, Beige Arch, Black (Serial) Arch, Grey (Serial) Arch, White (Serial) Arch, Beige (Serial)	<b>Package Part # *</b> FP-1231A FP-1234A FP-1231S FP-1234S FP-3231A FP-3235A FP-3236A FP-3237A FP-3231S FP-3235S FP-3236S FP-3237S	<b>Bezel Only Part #</b> FPZ-1231A FPZ-1234A FPZ-1231A FPZ-1234A FPZ-3231A FPZ-3235A FPZ-3236A FPZ-3237A FPZ-3231A FPZ-3235A FPZ-3236A FPZ-3237A
<b>Options</b>	Color – Wave: Black, Blue. Arch: Black, Grey, White, Beige Selectable Output Type: Wiegand, ABA Track II, Serial TTL (requires use of BIL 232/422 Module) Standard Termination – wire pigtail Programmable: Yes		
<b>Warranty</b>	Lifetime		
<b>Read Ranges**</b>	FlexISO® Card FlexISO XT Card FlexCard® FlexTag™ FlexKey® FlexISO MIFARE® FlexISO DESFire™ FlexISO iCLASS®	Up to 12" (30 cm) Up to 12" (30 cm) Up to 12" (30 cm) Up to 7" (17 cm) Up to 7" (17 cm) Up to 12" (30 cm) Up to 12" (30 cm) Up to 12" (30 cm)	

\* Includes bezel and core module

\*\*Note: Dependent upon installation conditions.

Specifications are subject to change without notice.

© 2009 HID Global Corporation. All rights reserved. HID, the HID logo, Indala, ProxSmith, FlexSecur and iCLASS are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 05/2009



MKT-MIDRANGE-DS-EN



## ACCESS experience.

[hidglobal.com](http://hidglobal.com)

### HID Global Offices:

**Corporate North America**  
 15370 Barranca Pkwy  
 Irvine, CA 92618  
 U.S.A.  
 Phone: (800) 237-7769  
 Phone: (949) 732-2000  
 Fax: (949) 732-2360

**Asia Pacific**  
 19/F 625 King's Road  
 North Point  
 Island East  
 Hong Kong  
 Phone: +852 3160-9800  
 Fax: +852 3160-4809

**Latin America**  
 Circunvalacion Ote. #201 B  
 Despacho 2  
 Col. Jardines del Moral  
 Leon 37160, Gto.  
 Mexico  
 Phone: +52 477 779 1492  
 Fax: +52 477 779 1493

**Europe, Middle East & Africa**  
 Haverhill Business Park  
 Phoenix Road  
 Haverhill  
 Suffolk  
 CB9 7AE  
 England  
 Phone: +44 (0) 1440 714 850  
 Fax: +44 (0) 1440 714 840