



Epoxy Adhesive Kit

Includes: 6 tubes 1g, 6 syringes/needles

Description	Catalog No.
Easy mix (1g) tubes fit into syringes; superior bond strength; cures in 10 minutes at 90°C; eight month shelf life; 30 minute working time	OFCEP



Anaerobic Adhesive Kit

Includes: Primer and adhesive, 10 syringes and 10 needles

Description	Catalog No.
Anaerobic adhesive kit cures in 6-10 seconds	OFCAP
Replacement bottle of primer only	OFPRIME



Crimp Tool

Dual hex cavity: .0178"/.0151"; flat crimp 0.052"; hex crimp 0.136"; hardened die

Description	Catalog No.
For 2QUICK® crimp and Hubbell OptiChannel SC/ST-style epoxy/anaerobic connectors; crimp dies (included) pre-set at factory	OFCMT04



Hand Scribe Tool

Includes: 1 tool and scribe guide

Description	Catalog No.
Sapphire blade	OFSCRIBE



Scribe Guide

Includes: package of 6

Description	Catalog No.
Suitable for SC, ST-style, or LC connectors	OFSG



Polishing Puck

Includes: 1 stainless steel puck, polished surface; SC/ST-style or LC compatible


Description	Catalog No.
SC/ST-style	OFPUCK
LC	OFPUCKLC



Polishing Film

Includes: 25 sheets of 5, 1, and 0.3 micron, 1 polishing pad

Description	Catalog No.
Replacement kit	OFLFP



Loose Tube OSP Cable Break-Out Kits

Includes: tube kit, break-out block and crimp bushing

Description	Catalog No.
6-fiber break-out kit	OFBOKT6
12-fiber break-out kit	OFBOKT12



OFBOKT6



OFBOKT12

Fiber Cable Management Radius Clips

Includes: pack of 4 self-adhering clips with bend radius control element

Description	Catalog No.
Cable clips	FBRMGTCLPK4



LC Duplex Connector Extraction Tool

Ideal for servicing high density interconnections

Includes: 1 tool, individually packaged

Description	Catalog No.
Connector extraction tool	OFLCDTOOL1



Epoxy Cure Adapters

Includes: package of 6 adapters for heat cure oven

Description	Catalog No.
SC/ST-style	OFCA
LC	OFCALC



OFCA



OFCALC

OPTISOK®

Bundle Size Range	Catalog No.
0.125-0.562"	CCPS1
0.250-0.750"	CCPS2
0.750-1.750"	CCPS3



Support Grips

Cable Diameter Range, In. (cm)	Approx. Breaking Strength, Lb (N)	Closed Mesh	Rod Closing Split Mesh
.18"- .25" (.46- .63)	300 (1,334)	022291000	022291016
.23"- .32" (.58- .81)	300 (1,334)	022291001	022291017
.30"- .39" (.76- .99)	300 (1,334)	022291002	022291018
.37"- .48" (.94- 1.22)	300 (1,334)	022291003	022291019
.46"- .58" (1.17- 1.47)	400 (1,779)	022291004	022291020
.56"- .71" (1.42- 1.80)	600 (2,669)	022291005	022291021
.69"- .88" (1.74- 2.24)	800 (3,558)	022291006	022291022

IMPORTANT: Consult factory support for safety and working load factors for wire mesh grips.

