

230/400V / 30A / THREE-PHASE WYE POU

4. CURRENT METER - RED, 4-DIGIT LED DISPLAY PROVIDES TRUE RMS CURRENT THAT CONTINOUSLY SCROLLS THROUGH THE THREE DIFFERENT MEASURED CIRCUITS. METER DISPLAYS CIRCUIT NAME FOLLOWED BY THE MEASURED CURRENT (E.G. CR-1 REPRESENTS PHASE 1). BREAKER/PHASE (X,Y,Z) LEVEL MONITORING CAN ALSO BE ACCESSED REMOTELY VIA ETHERNET CONNECTION.

В

7. VISIT OUR ON-LINE CATALOG AT WWW.PANDUIT.COM FOR A CURRENT LIST OF PRODUCTS APPLICABLE FOR USE

09V098UC/02.PRT		
09V098UC_DC/02A.PRT		
NDUIT CORP TINLEY PARK, ILLINOIS		
CAL, MIXED (24) C-13 & (6) C-19, NETWORKED POWER OUTLET UNIT CUSTOMER DRAWING		
NISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: [METRIC - MILLIMETER] 0.013 X. +/- 0.8 0.015 X.X +/- 0.4 0.005 X.XX +/- 0.13	[METRIC - MILLIMETER] ANGLE	
MAT'L:	SCALE NONE	
	DRAWING NO.	DWG
	09V098UC	