THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



DETAIL A
(SCALE 4X)

PANDUIT P/N	WEIGHT
QZ1C1P3BN24Y1	17 lb (7.7 kg)

NOTES:
1. IDENTIFICATION: VERTICAL, (12) C-13 & (6) C-19 & (6) 5-20R NETWORKED 120/208V / 30A / THREE-PHASE WYE POU

PART NO.	COLOR
QZ1C1P3BN24Y1	BLACK

2. ACCESSORY COMPONENTS:
   (4) #10-32 x 1/2" MOUNTING SCREWS
   (4) #12-24 x 1/2" MOUNTING SCREWS
   (2) #10-32 LOCKING COLLAR SCREWS
   (2) L-BRACKETS
3. DIMENSIONS IN PARENTHESES ARE METRIC (mm).
4. CURRENT METER - RED, 4-DIGIT LED DISPLAY PROVIDES TRUE RMS CURRENT THAT CONTINOUSLY SCROLLS THROUGH THE THREE DIFFERENT MEASURED CIRCUITS. METER DISPLAYS CIRCUIT NAME FOLLOWED BY THE MEASURED CURRENT (E.G. CR-1 REPRESENTS PHASE 1). BREAKER/CIRCUIT (XY,YZ,ZX) LEVEL MONITORING CAN ALSO BE ACCESSED REMOTELY VIA ETHERNET CONNECTION.
5. UL® & c-UL® LISTED 60950.
6. RoHS COMPLIANT.
7. VISIT OUR ON-LINE CATALOG AT WWW.PANDUIT.COM FOR A CURRENT LIST OF PRODUCTS APPLICABLE FOR USE WITH THIS PART.
8. MAXIMUM AVAILABLE POWER = 8.6 KW



PLUG
30 AMP, 120/208V x 3~ WYE
TWIST LOCK
NEMA L21-30P



TWELVE (12)
RECEPTACLES
15 AMP, 250V
STRAIGHT BLADE
IEC 60320/C13



SIX (6)
RECEPTACLES
20 AMP, 250V
STRAIGHT BLADE
IEC 60320/C19

SIX (6)
RECEPTACLES
20 AMP, 125V
STRAIGHT BLADE
NEMA 5-20R

REV	DATE	BY	CHK	DESCRIPTION	ECN - R	CUST	SUP	OTH
00A	11-23-10	MAV	KRKE	RELEASED TO PRODUCTION	09V098NX			

MODEL FILENAME: 09V098NX/00.PRT
CAD FILENAME/LAYERS: 09V098NX_DC/00A.PRT

PANDUIT CORP TINLEY PARK, ILLINOIS

VERTICAL, (12) C-13 & (6) C-19 & (6) 5-20R NETWORKED POWER OUTLET UNIT (QZ1C1P3BN24Y1) CUSTOMER DRAWING

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:
INCHES: X.X +/- 0.03; X.XX +/- 0.015; X.XXX +/- 0.005
[METRIC - MILLIMETER]: X. +/- 0.8; X.X +/- 0.4; X.XX +/- 0.13
ANGLE +/- 1°
UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION

DRAWN BY: MAV
DATE: 11-23-10
CHK'D: KRKE
MAT'L:
SCALE: NONE
DRAWING NO.: 09V098NX
DWG: B SIZE