



## Modular 66 Cross Connect Blocks, 66M

Description	Block Size	Capacity	Catalog No.
66M block, Category 5 with cover	4 x 50	50-pair	<b>HPW66M150C5</b>
66M block	4 x 25	25-pair	<b>HPW66M125</b>
66M block	4 x 50	50-pair	<b>HPW66M150</b>
66M cover	-	-	<b>HPW66MCVR</b>

### Features/Benefits

- Designed to fill the requirements for data distribution using familiar quick-clips for termination
- Ability to transmit data rates up to 100 MHz

### Specifications

- With 4 slots on each row, there is flexibility for various configurations



HPW66M150C5

## Modular 66 Cross Connect Blocks, 66B

Description	Block Size	Capacity	Catalog No.
66B block, split (3x) (includes cover)	6 x 6	6-pair	<b>HPW66B36</b>
66B block cover for HPW66B 425 + 350	-	-	<b>HPW66BCVR</b>
66M block	6 x 12	6-pair	<b>HPW66B16</b>
66B block 25-pair, split (4x)	6 x 50	25-pair	<b>HPW66B425</b>
66B block 50-pair, split (4x)	6 x 50	50-pair	<b>HPW66B350</b>

### Features/Benefits

- Designed for fast and easy termination incoming telephone cables
- The smaller connecting blocks satisfy the need for a block smaller than the 25-pair size

### Specifications

- Stackable for increased plant flexibility



HPW66B16



HPW66B36



HPW66B425

## 12- and 16-Port Blocks

Description	Wiring	Jack Openings	Capacity	Catalog No.
Modular 66 block	T568B	12-8 pos. jacks	50-pair	<b>BR258066A</b>
Modular 66 block	USOC-RJ25	16-6 pos. jacks	50-pair	<b>BR256066A</b>

### Features/Benefits

- Supports installations not large enough to warrant a patch panel
- Designed with printed circuit boards for consistent electrical performance

### Specifications

- Category 3 (12-port) performance listed by UL (89D bracket included)



BR258066A

## Modular 66 Cross Connect Block Accessories

Description	Catalog No.
Cable routing spool without screw	<b>HPW66SPLA</b>
Cable routing spool with screw	<b>HPW66SPLB</b>
89B bracket (use to mount 66M series blocks)	<b>HPW89B</b>
89D bracket (use to mount 66M series blocks)	<b>HPW89D</b>
Backboard (blue, for 89D and 89B brackets) Includes 2-89B brackets as shown	<b>HPW66BB</b>
66B bracket (use to mount 66B series blocks)	<b>HPW66BBRKT</b>
Bridging clip (0.5" x 0.25") (pack of 100)	<b>HPW66BC100</b>

### Features/Benefits

- Cable routing spools provide control and dressing of distribution cables and jumper wires—available with or without screws
- Mounting holes are provided for use in a variety of mounting options

### Specifications

- Material: mounting brackets molded of durable self-extinguishing thermoplastic



HPW66BB



HPW89D



HPW66SPLB



HPW66BBRKT



HPW66BC100