



AMC-62 Foam 93 ohm | 8890033/45

**AMC-62 Foam 93 Ohm Coaxial Cable, black PVC jacket**

## Construction Materials

Center Conductor Material	Copper-clad steel wire
Dielectric Material	Foam PE
Shield (Braid) Coverage	95 %
Shield (Braid) Material	Bare copper
Shield (Tape) Material	No tape
Jacket Material	PVC

## Dimensions

Cable Length	1372 m   4500 ft
Cable Weight	33.00 lb/kft
Diameter Over Center Conductor	0.6426 mm   0.0253 in
Diameter Over Center Conductor Tolerance	±0.0003 in
Diameter Over Dielectric	3.6576 mm   0.1440 in
Diameter Over Dielectric Tolerance	±0.004 in
Diameter Over Jacket	6.147 mm   0.242 in
Diameter Over Jacket Tolerance	±0.007 in
Diameter Over Outer Shield (Braid)	4.343 mm   0.171 in

## Electrical Specifications

Capacitance	43.3 pF/m   13.2 pF/ft
Characteristic Impedance	93 ohm
Characteristic Impedance Tolerance	±5 ohm
Conductor dc Resistance, maximum	44.00 ohms/kft
Dielectric Strength	3 s @ 2500 Vdc
Jacket Spark Test Voltage	5000 V
Shield dc Resistance	4.00 ohms/kft
Velocity	86 %

## Environmental Specifications

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
-----------------------	--------------------------------------

## General Specifications

Application	Automotive
Cable Type	AMC-62
Jacket Color	Black
Brand	Auto Mobile Cable®

## Electrical Performance

Frequency	Attenuation (dB/100 m)	Attenuation (dB/100 ft)
50 MHz	5.90	1.80
100 MHz	8.86	2.70

AMC-62 Foam 93 ohm | 8890033/45

*\* Electrical specifications/performance listed represents values at standard condition of 20 °C (68 °F)*

## Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system