

AT-FS750/24POE

24 port Fast Ethernet PoE WebSmart Switch



AT-FS750/24POE-xx

24 port 10/100TX PoE WebSmart switch with 2 SFP combo ports

ECO-Friendly

The AT-FS750/24POE eco-friendly WebSmart switch conforms with Allied Telesis' commitment to environmentally friendly processes and products. It is designed to minimize power consumption through the use of a high efficiency power supply and a low power chipset.

With a low 12.9W* or 115.5W** typical power consumption, and a reduction in power during after-work hours (overnight mode) – as well as other power saving features included as standard, the Allied Telesis AT-FS750/24POE truly lives up to its name as an 'eco-friendly' switch. Not only does this help the planet by reducing the carbon footprint of each switch, it also lowers the Total Cost of Ownership (TCO) to the user, as the product costs less to run, and has improved reliability.

With all of these power saving features, the new eco-friendly AT-FS750/48 saves the user over 25% in power consumption over non eco-friendly models.

Performance

Allied Telesis' WebSmart switch integrates the simplicity of unmanaged switches with the performance and reliability of managed switches to provide a cost-effective solution for users to integrate management at the edge of their network. This WebSmart switch provides a network manager some key features using the simple web-based management function such as; port-based VLANs, IEEE 802.1p QoS, port trunking/link aggregation, port mirroring, priority queues and IEEE 802.1x security support. With support of up to 8K MAC addresses and a 512K packet buffer the AT-FS750/24POE WebSmart switch is an ideal option for integrating management into your network solution.

Key Features

VLAN

- Up to 256 IEEE 802.1Q VLANs
- Up to 4K VID
- Port-based
- Up to 64 groups

Quality of Service Classification

- IEEE 802.1p tagging
- Port-based priority
- Four priority queues per port

IP Multicast Support (IPv4)

- IGMP snooping(v1/v2)
- Static multicast group
- Spanning-Tree, IEEE 802.1d/w

IEEE 802.3ad Link Aggregation

- Manual

IEEE 802.1x Port-based and MAC-based Network Access Control

- Local authentication server (MD5 only)
- Remote authentication through RADIUS
- Dynamic VLAN assignment

- RADIUS client for IEEE 802.1x

- DHCP client

- Statistics charts in WEB

Others

- IEEE 802.3x flow control or HOL (†) blocking prevention († when flow control is off)
- Port mirroring
- Destination MAC filtering
- Ingress/egress rate limiting
- Broadcast storming control
- 100FX SFP support

*17 ports connected with 3m cables

**17 ports connected and full PoE utilization

Management Features

Window-based Supporting

- Switch discovery management up to 254 switches
- Monitor list
- Trap view
- Device setting
- Firmware upgrade by FTP and Web
- Configuration backup/restore by FTP
- Factory reset
- Password access control and restricted IP access list
- SNMPv1/v2c

MIBs

- RFC 1213 MIB-II
- RFC 1643 Ethernet MIB
- RFC 1493 Bridge MIB
- Private Enterprise MIB (Allied Telesis provide the spec)

RMON Groups (1,2,3,9)

- Stats
- History
- Alarms
- Events

PoE Intelligent Management

- IEEE 802.3af standard
- 12 10/100TX ports support PoE function (ports 1 to 12)
- Support up to 6 10/100TX ports in 15.4W simultaneously
- PoE module function tests
- Per-port LED/status monitoring
- Automatic detection and power budgeting



AT-FS750/24POE | 24 port Fast Ethernet PoE WebSmart Switch

Power over Ethernet

Capable of providing up to 12 ports of Class 2 IEEE 802.3af PoE power (6 ports Class 3), the AT-FS750/24POE is ideally suited for those applications using security cameras, wireless access points, IP phones, and other PoE powered devices. The PoE option eliminates the need for power rewiring and minimizes the clutter of power supplies and adapters in awkward places.

Value

Never thought you could afford managed switches in your network? Always wanted to provide management functionality at the edge? Now's your chance. Allied Telesis' WebSmart switch truly helps network managers get the most value for their dollar. With industry standard protocols, fiber media support via the SFP's, and simple Plug & Play usability right out of the box, how can you go wrong implementing this cost-effective solution into your network?

Quality and Reliability

Allied Telesis is a worldwide leader in unmanaged Ethernet switches. Shipping more than 250,000 unmanaged switches each year, Allied Telesis offers proven reliability and industry recognized quality.

Performance

14,880pps for 10Mbps Ethernet
148,800pps for 100Mbps Ethernet
1,488,000pps for 1000Mbps Ethernet

MAC addresses	8K
Packet buffer	512KB
DRAM	32M
Flash	4M
Switching capacity	12.8Gbps
Throughput	9.52Mpps

Power Characteristics

AC voltage/frequency requirements	100 - 240V AC, 50/60Hz
AC input power consumption	150W maximum
Available Power over Ethernet	100W @ 48VDC
IEEE 802.3af Class 3 (15.4 W)	Max 6 ports
IEEE 802.3af Class 2 (7.3 W)	Max 12 ports
IEEE 802.3af mode	Alternative A (MDI)

Interface Connections

10/100	RJ-45
SFP	1000SX or 1000LX

Environmental Specifications

Operating temp.	0°C to 40°C (32°F to 104°F)
Non-operating temp.	-25°C to 70°C (-13°F to 158°F)
Operating humidity	5% to 90% non-condensing
Storage humidity	5% to 95% non-condensing
Vibration	IEC 68-2-36
Shock	IEC 68-2-29
Drop	IEC 68-2-32

Technical Specifications

Physical Characteristics

Dimensions	44.4cm x 32.2cm x 4.35cm 17.5" x 12.7" x 1.7"
Weight	4.13 kg (9.11 lbs)

Wall-mount or Desktop

All units come with wall / 19" rack-mount brackets

Standards and Compliance

IEEE 802.3	CSMA/CD
IEEE 802.3i	10T
IEEE 802.3u	100TX
IEEE 802.3z	1000SX/LX
IEEE 802.3z/ab	1000T
IEEE 802.3x	Flow control
IEEE 802.1p	Prioritization (four queues)
IEEE 802.1x	Authentication
IEEE 802.1d	Bridging
IEEE 802.3ad	Link aggregation
IEEE 802.1Q	Tagged VLAN
IEEE 802.1d/w	Spanning-Tree
	Rapid Spanning-Tree
IEEE 802.3af	PoE (mode A)

Electrical/Mechanical Approvals

UL 1950
FCC/EN55022 Class A
VCCI Class A
C-Tick
EN60950 (TUV)
EN55024
CE
CSA / CUL

MTBF

256,000 hours
Bellcore TR332

Ordering Information

AT-FS750/24POE-xx

24 port 10/100TX PoE WebSmart switch
with 2 SFP combo ports

Where xx =	10 for US power cord
	20 for no power cord
	30 for UK power cord
	40 for Australian power cord
	50 for European power cord

Product Contents

Switch unit
Rack-mount/wall-mount brackets and screws
Power cord
User manual/install guide on CD
Rubber feet

USA Headquarters | 19800 North Creek Parkway | Suite 100 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895
European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11
Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

www.alliedtelesis.com

© 2011 Allied Telesis Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000361 Rev.B