## Network Storage



### TeraStation™ III



Buffalo<sup>™</sup> TeraStation<sup>™</sup> III is a larger capacity NAS device with robust RAID 5 capability. The redundancy of four separate hard drives in RAID 5 or RAID 1 modes mean that even if a hard drive fails, your data is safe.

With Hot Swap functionality, if a drive does fail, the TeraStation<sup>™</sup> III automatically powers down the faulty drive, enabling you to safely remove and replace without losing any data, or down time. The replication function allows the connection of a second TeraStation<sup>™</sup> via LAN port and replicates the data to improve reliability, fault tolerance or accessibility.

Available as desktop or 1U rackmount the TeraStation<sup>™</sup> III is the perfect solution for the home office or small to medium business that needs large, easy-to-deploy, easy-to-manage, redundant network attached storage.

- Available as desktop or 1U Rackmount
- High-Speed Up to 69MB/s high-speed data transfer rate
- Back-up Replication Function allows you to have a mirrored unit as a spare
- Easy set-up Clear LCD status display and intuitive Web interface means the units are simple to install and easy to manage
- Resilient Replace faulty hard drives with the Hot Swap functionality without interruption of work
- Connectivity Dual Ethernet for port trunking



TeraStation<sup>™</sup> III - Desktop



### TeraStation™ III -1U Rackmount



Note: 1TB = 1,000,000,000,000Bytes. Actual data throughput and range will vary depending upon network conditions and environment factors, including volume of network traffic, building materials and construction, and network overhead.

### **Key Specifications**

- Available as desktop or 1U Rackmount
- Five operational modes: JBOD, RAID 0, 1, 5, 10
- Hot Spare & Mirroring a failover mechanism provides reliability for uninterrupted operation
- Supports Apple Time Machine Back-up multiple Mac computers
- EXT3 Reader Back-up data held on attached USB hard drives via the USB ports can be read on Windows based PCs
- Optional Disk Encryption
- Quota Management prevent misuse of disk space by allocating the right amount of space by user
- Active Directory Support simplify the management of each TeraStation<sup>™</sup>
- Built-in DLNA Media Server
- Built-in BitTorrent Client

- WebAccess remotely access the TeraStation™ III from anywhere via PC, Mac, iPhone<sup>®</sup>, iPad<sup>®</sup>, Android Phone and Tablet
- Supports NFS can be mapped from UNIX so that a wide range of users can access the drives
- Built-in Print Server
- LCD Status Display and intuitive web interface
- PC Interlocking Power Management System for effortless
  power saving
- Schedule Power Management System for flexible power management, save up to 66%, reduce CO<sub>2</sub> omissions. Automatically turns on and shuts down with PC.
- Includes NovaBACKUP<sup>®</sup> Business Essentials with 10 licenses - protects data on servers locally or online. Regardless of theft, user error or hardware failure NovaBACKUP<sup>®</sup> protects and restores your data.



## Network Storage

# SPECIFICATIONS

LAN Interface	
Standard Compliance	IEEE802.3ab/IEEE802.3u/IEEE802.3 Standard
Data Transfer Rates	10/100/1000Mbps Autosensing
Connector Type	RJ-45
Number of Ports	2 (Auto MDIX)
Internal Hard Drives	
Number of Drives	4
Drive Interface	SATA
Hard Drive Sizes	1TB, 2TB, 3TB
Total Capacity	4.0TB, 8.0TB, 12.0TB
Supported RAID Levels	0, 1, 5, 10, JBOD
USB Interface	
Standard Compliance	USB 2.0
Connector Type	USB Туре А
Number of Ports	2
Data Transfer Rates	Max: 480Mbps (High-Speed Mode), Max: 12Mbps (Full Speed Mode)
Protocol Support	
Networking	TCP/IP
File Sharing	SMB/CIFS, AFP, FTP/FTPS, SFTP, HTTP/HTTPS, NFS
AD Authentication	Kerberos/LDAP
Management	HTTP, HTTPS
Other	
Dimensions (WxHxD)	Desktop 170 x 215 x 230mm, Rackmount 430 x 420 x 443mm
Weight	Desktop approx 8.0Kg (dependant on capacity) Rackmount approx 12.0Kg (dependant on capacity)
Operating Environment	5-35°C, 20-80% (non condensing)
OS Support	Windows 8 (32/64 bit), Win <sup>®</sup> 2000, XP, Vista, MCE2004/05, Win Server 2000/2003/2008, Mac OS X 10.3.9 or higher
Power Supply	Internal AC 100-240V, 50/60Hz
Desktop 1	U Rackmount
	5-RX4.0TL/R5 4.0TB
	5-RX8.0TL/R5 8.0TB
TS-X12.0TL/R5 12.0TB T	S-RX12.0TL/R5 12.0TB

Note: 1TB = 1,000,000,000,000Bytes. Actual data throughput will vary depending upon environment factors.

#### **About Buffalo**

Buffalo Technology is a leading global provider of award-winning storage, networking, memory, and multimedia solutions for the home and small business environments as well as for system builders and integrators. With more than three decades of networking and computer peripheral experience, Buffalo has proven its commitment to delivering innovative solutions that have put the company at the forefront of infrastructure technology.

© Buffalo Inc. 2011. BUFFALO logo, AirStation, Nfiniti, AOSS, TeraStation, LinkStation, DriveStation, DriveStation 2Share, MiniStation, Dualie and LinkTheater are either trademarks or registered trademarks of Melco Holdings Inc. or Buffalo Inc. Microsoft Windows and Microsoft logo are either registered trademarks or trademarks of Microsoft corporation in United States and/or other countries. The names and logos of other companies mentioned herein belong to their respective owners. The information within this datasheet is subject to change without notice. All rights reserved. E & OE.