

Sentry Smart CDU

Key Features

- > **High Density:** Single-power input feed; 24 outlets per enclosure (Quantity 12xC13 and 12xC19 outlets)
- > **Power Distribution:**
208 V 3-phase 50 A or 60 A power input feed options.
- > **Input Current Monitor:**
Precisely measure the aggregate current draw (in amps) of the circuit. On-site verification of the input current with LED digital display. Remote verification via web browser or serial screen.
- > **IP Access & Security:** Web interface, SSL, SSH, Telnet, SNMP, FTP, SNTp, Syslog, LDAP, LDAPS, TACACS, RADIUS, and RS-232 access
- > **SNMP Traps and Email alerts:**
Provide automated alerts for power and environmental conditions
- > **Environmental Monitoring:**
Each Smart CDU supports two external temperature & humidity probes and reports conditions thru the user interface without the need for additional IP addresses
- > **Add an Expansion Module:**
Connect the Smart Expansion CDU (CLG) to a Master unit (CSG) for power monitoring of separate power circuits from a single IP address

CSG-24VD/Y 50/60A Smart POPS[™] CDU with 12xC13 and 12xC19 Outlets

High-Density Power Distribution

The Smart Cabinet Power Distribution Units (CDU) provide reliable power distribution combined with local and remote power monitoring and environmental monitoring via IP. Use the network interface to view power, temperature and humidity levels via Web browser, or receive SNMP-based alarms and email alerts when conditions exceed defined thresholds.

Sentry POPS (Per Outlet Power Sensing) combines all of the features and functions of a Smart CDU with the ability to provide power monitoring per an individual outlet/device. Power information per individual outlet/device includes current, voltage, power (kW), apparent power, crest factor, and power factor. Using out grouping technology, power information is available per device, groups of devices (application), individual CDU or cabinet.

Additional Benefits:



POPS[™] (Per Outlet Power Sensing)

Monitor Current Load (A), Voltage (V), Power (W), Apparent Power (VA), Crest Factor and Power Factor per outlet at an accuracy of $\pm 2\%$.



Branch Circuit Protection

The Sentry CDU Family meets the UL 60950-1 requirement for Branch Circuit Protections
> UL-489 rated circuit breakers



PIPS - Per Input Power Sensing

Accurately measures Active Power, Apparent Power, Energy k-Wh, Power Capacity, and Power Capacity Used using the network interface. See the aggregate current draw, in Amps, locally using the onboard LED.



Temperature and Humidity

The Smart CDU supports two external 10ft (3m) probes. Each of these probes measure both temperature and humidity. Receive SNMP-based alerts or email notifications when conditions exceed defined thresholds.



Mixed Outlets

This Smart CDU combines 12 IEC 60320 C13 and 12 IEC C19 outlets within a single CDU to monitor power at the outlet-level.



Model	Available Input Voltages	Amperage	Available Input Cord	Outlets	Dimensions (L x W x D)
CSG-24VDX415A9 CLG-24VDX415A9*	240V 3-phase Delta 50/60Hz	60A	IEC Blue 9hr 3P+G Plug, 10'(3m), Bottom/Frt Cord	(12) IEC 60320/C13 (12) IEC 60320/C19	74.8 x 1.75 x 3.50 in. (1899 x 44 x 89 mm)
CSG-24VDV415A9 CLG-24VDV415A9*	240V 3-phase Delta 50/60Hz	50A	CS8365C Plug, 10'(3m), Bottom/Frt Cord	(12) IEC 60320/C13 (12) IEC 60320/C19	74.8 x 1.75 x 3.50 in. (1899 x 44 x 89 mm)
CSG-24VYY411A9 CLG-24VYY411A9*	208V 3-phase Wye 50/60 Hz	60A	IEC Blue 9hr 3P+N+G Plug, 10'(3m), Bottom/Frt Cord	(12) IEC 60320/C13 (12) IEC 60320/C19	74.8 x 1.75 x 3.50 in. (1899 x 44 x 89 mm)

* CLG part numbers refer to the Expansion CDU

Additional Features and Specifications

Agency Approvals

- > US & Canada (cTUVus Mark) to UL 60950-1:2003 and CAN/CSA 22.2 No. 60950-1-03
- > FCC Class A, Part 15
- > EMC to EN 55022 Class A, EN 55024, CISPR 22 Class A

Communications and Security

- > 10/100 BaseT Ethernet
- > HTTP/HTTPS
- > SSLv3/TLSv1
- > SNMPv2
- > SSHv2
- > Telnet
- > LDAPS/LDAPv3
- > TACACS+
- > RADIUS
- > RS-232 (Serial)

Branch Circuit Protection

- > Compliant to UL 60950-1

Accessories

- > Optional Temperature & Humidity Probe
 - EMTH-1-1 Temperature & Humidity Probe, 10 ft (3m)
- > SPM (Sentry Power Manager) Appliance:
 - Monitor and Manage multiple Sentry CDU's
 - Monitor and Manage all alarm conditions
 - Reporting and Trending
 - Group or Cluster outlets for reboot and power information
- > Environmental Monitor
 - EMCU-1-1B allows up to (2) additional temperature & humidity probes, (1) water sensor, (4) dry contact closures, (1) analog-to-digital contact sensor. Includes (1) temperature/humidity probe with unit.

1U SPM Appliance



Expansion Module
Model Numbers
> CLG-24VDX415A9
> CLG-24VDV415A9
> CLG-24VYY411A9



Server Technology

HEADQUARTERS - NORTH AMERICA
Server Technology, Inc.
1040 Sandhill Drive
Reno, NV 89521
United States
1.775.284.2000 Tel
1.775.284.2065 Fax
sales@servertech.com
www.servertech.com
www.servertechblog.com

EMEA
Server Technology Intl
Sienna Court
The Broadway
Maidenhead
Berkshire
SL6 1NJ
United Kingdom
+44 (0) 1628 509053 Tel
+44 (0) 1628 509100 Fax
salesintl@servertech.com

APAC
Server Technology Intl
37th Floor, Singapore Land Tower
50 Raffles Place
Singapore 048623
+65 (0) 6829 7008 Tel
+65 (0) 6234 4574 Fax
salesintl@servertech.com