

Sentry Switched CDU

Key Features

- > **Network Power Management:** Power cycle individual power outlets, or groups of power outlets, to remotely reboot servers and network devices, anywhere in the world. Or, power-off unused power receptacles
- > **High Power Distribution:** 200-240V 20A or 30A; 230V 16A or 32A dual input feed options
- > **High Density:** 32 outlets (24xC13 + 8xC19) per unit
- > **IP Access & Security:** Web interface, SSL, SSH, Telnet, SNMP, FTP, SNT, Syslog, LDAP, LDAPS, TACACS, RADIUS and RS-232 access
- > **Add an Expansion Module:** Connect the Switched Expansion CDU (CX) to a Master unit (CW) for power management of separate power circuits from a single IP address
- > **Environmental Monitoring:** Each Switched CDU supports two temperature & humidity probes and reports conditions thru the Web interface
- > **SNMP Traps:** Provide automated alerts for power and environmental conditions
- > **Input Current Monitor:** Precisely measure the aggregate current draw (in amps) on each power circuit. On-site verification of the input current with the LED digital display. Remote verification via browser or serial screen.
- > **Power-up Sequencing:** Prevent an in-rush power overload

CW-32VD2/E with C13 and C19 outlets

High-Density Power Distribution

The Switched CDU's combine remote configuration and management with power distribution and power and environmental monitoring. Reboot a single or dual-power server with one command. Receive SNMP alerts when power or environmental conditions exceed thresholds. Assign users specific access rights to designated outlets or groups.

Only the Switched CDU products provide the flexibility needed for all data centers and remote sites, including power requirements for high-amp, high voltage; UL 60950-1 branch circuit protection; SSL & SSH security; and SNMP-based input current monitoring.

Additional Benefits:



Branch Circuit Protection

The Sentry CDU Family meets the UL 60950-1 requirement for Branch Circuit Protection

- > UL-489 rated circuit breakers



PIPS - Per Input Power Sensing

Accurately measures Active Power, Apparent Power, Energy k-Wh, Power Capacity, and Power Capacity Used using the network interface. See the aggregate current draw, in Amps, locally using the onboard LED.



Temperature and Humidity

The Switched CDU supports two external probes. Each of these probes measure both temperature and humidity. Receive SNMP-based alert notifications when conditions exceed defined thresholds.



Linking (Expansion Modules)

The Switched CDU family has the capability to daisy chain units together. The Expansion Module provides the ability to link two power circuits under one IP address.



Model	Available Input Voltages	Amperage	Available Input Cord	Outlets	Dimensions (L x W x D)
CW-32VD2AA15A1 CX-32VD2AA15A1*	208-240V 50/60Hz	20A	Dual IEC C20 Inlets, Bottom/Frt Entry	(24) IEC 60320/C13 (8) IEC 60320/C19	42.0 x 3.5 x 3.5 in. (1067 x 89 x 89 mm)
CW-32VD2CA15A1 CX-32VD2CA15A1*	208-240V 50/60Hz	30A	Dual NEMA L6-30P Plugs, 10'(3m), Bottom/Frt Cord	(24) IEC 60320/C13 (8) IEC 60320/C19	42.0 x 3.5 x 3.5 in. (1067 x 89 x 89 mm)
CW-32VDEAA15A1 CX-32VDEAA15A1*	230V 50/60Hz	16A	Dual IEC C20 Inlets, Bottom/Frt Entry	(24) IEC 60320/C13 (8) IEC 60320/C19	42.0 x 3.5 x 3.5 in. (1067 x 89 x 89 mm)
CW-32VDEKA15A1 CX-32VDEKA15A1*	230V 50/60Hz	32A	Dual IEC Blue 2P+G Plugs, 10'(3m), Bottom/Frt Cord	(24) IEC 60320/C13 (8) IEC 60320/C19	42.0 x 3.5 x 3.5 in. (1067 x 89 x 89 mm)

* Expansion unit

Additional Features and Specifications

Agency Approvals

- > US & Canada (cTUVus Mark) to UL 60950-1:2nd Ed. and CAN/CSA 22.2 No. 60950-1-03
- > European Union (TUVGS Mark) to EN 60950-1:2001
- > FCC Class A, Part 15
- > CE Mark
- > EMC to EN 55022 Class A, EN 55024, CISPR 22 Class A

Communications and Security

- > 10/100 BaseT Ethernet
- > HTTP/HTTPS
- > SSLv3/TLSv1
- > SNMPv2
- > SSHv2
- > Telnet
- > LDAPv3
- > LDAPS
- > TACACS+
- > RADIUS
- > RS-232 (Serial)

Branch Circuit Protection

- > Compliant to UL 60950-1

Power Cord Options

- > PTCORD-1 IEC 60320/C19 - NEMA L6-20P , 10'(3m)
- > PTCORD-2 IEC 60320/C19 - Schuko 10'(3m)
- > PTCORD-3 IEC 60320/C19 - IEC 60309 (BS4343, CEE17) 16/20A Blue (UK Commando) 10'(3m)
- > PTCORD-4 IEC 60320/C19 - BS1363 13A (UK) 10'(3m)

Accessories

- > Optional Temperature & Humidity Probe
 - EMTH-1-1 Temperature & Humidity Probe, 10ft (3m)
- > Environmental Monitor
 - EMCU-1-1B allows up to (2) additional temperature & humidity probes, (1) water sensor, (4) dry contact closures, (1) analog-to-digital contact sensor. Includes (1) temperature/humidity probe with unit.
- > SPM (Sentry Power Manager) Appliance:
 - Monitor and Manage multiple Sentry CDU's
 - Monitor and Manage all alarm conditions
 - Reporting and Trending
 - Group or Cluster outlets for reboot and power information

1U SPM Appliance



Expansion Module

- > CX-32VD2AA15A1
- > CX-32VD2CA15A1
- > CX-32VDEAA15A1
- > CX-32VDEKA15A1



Server Technology

HEADQUARTERS -
NORTH AMERICA
Server Technology, Inc.
1040 Sandhill Drive
Reno, NV 89521
United States
1.775.284.2000 Tel
1.775.284.2065 Fax
sales@servertech.com
www.servertech.com
www.servertechblog.com

Western Europe, Middle East and
Africa
Server Technology
Fountain Court
2 Victoria Square
Victoria Street
St. Albans
AL1 3TF
United Kingdom
+44 (0) 1727 884676 Tel
+44 (0) 1727 220815 Fax
salesint@servertech.com

Central Europe, Eastern Europe and
Russia
Niederlassung Deutschland
Server Technology LLC
42119 Wuppertal
Germany
Tel: + 49 202 693917 x 0
Fax: + 49 202 693917-10
salesint@servertech.com

APAC
Server Technology
Room 2301, 23/F, Future Plaza
111-113 How Ming Street,
Kwun Tong, Hong Kong
Direct line: +852 3916 2048
Fax Line: +852 3916 2002
salesint@servertech.com