

## GS Hybrid DVR with Full D1 Recording

**D24GS** 24 Channel DVR with Digital Deterrent™


**D32GS** 32 Channel DVR with Digital Deterrent™

**Storage 500GB – 8TB**

D24GS500	D24GS6TB	D32GS2TB
D24GS1TB	D24GS8TB	D32GS4TB
D24GS2TB	D32GS500	D32GS6TB
D24GS4TB	D32GS1TB	D32GS8TB



16.9" W x 19.3" D



### Features

**EZ Setup:** for quick system setup

**EZ Network:** for quick set-up on a network

**EZ Search:** quickly search events from thumbnails

**EZ Record:** quickly setup recording resolutions and recording type

**EZ Copy:** auto copy what you are playing onto a USB flash drive

- H.264 video compression
- Full D1 real time recording
- Optimized for full HD surveillance
- Expanded video display options - HDMI support
- Storage expansion via eSATA and iSCSI
- D24GS: 8 analog channels + 16 IP channels
- D32GS: 16 analog channels + 16 IP channels
- ONVIF support\*
- Rack mountable (hardware included)
- 3 year warranty

#### Monitoring

- Up to 5 monitors connectable simultaneously
- 16 ch display for every monitor including spot monitor
- Full HD (1920 x 1080p) resolution support
- Various screen formats for Full HD and standard monitors
- On-Live Playback (Triplex)
- Data archiving support
- User Access: up to 10 concurrent users

#### Record / Search

- Various recording modes: Continuous, Motion, Alarm, Pre/Post-Event, Panic
- Easy record scheduling
- Various searching modes: Date/Time, Calendar, Time Bar, Event, Motion, Alarm, Text-In
- Disk mirroring, data archiving support
- Various actions (PTZ preset, record cameras, alarm, save image) configurable

#### External Device

- External hard drives attachable via eSATA port
- iSCSI support
- Remote keyboard support
- Various PTZ protocol support (60+)
- Free Speco DDNS service for use with dynamic IP addresses

- MAC® software provides live view and playback\*
- Simultaneous live view or playback while continuing to record, network transfer
- SNS communication alert via Twitter™

#### External Device (cont.)

- Remote monitoring, recording, playback, change system settings and camera control via network and/or Internet
- Real time live display
- IR remote control included - individually control up to 16 DVRs
- Multiple analytics such as museum search and advanced motion detection frame rate & picture quality or globally via EZ record
- Easy software upgrade via Network or USB flash drive
- Configurable per channel normal and event recording
- Full system monitoring
- Email notification of alarm events
- Per channel built-in PTZ camera protocol including Pelco D
- Automatic camera detection (Plug & Play)
- Digital zoom in live mode and playback
- Covert camera operation provides enhanced security and administrator control
- Hard drive status monitoring
- USB mouse supported (not included)
- Multiple language on-screen menus
- Playback while watching live on same monitor
- Up to 30 minutes pre-alarm recording
- Up to 30 minutes post-alarm recording
- Concurrent User Connections: Admin (2) / Watch (10) / Search (2)
- USB mouse supported (not included)
- Password to secure installation with configurable user authentication levels
- MAC® & PC compatible software included
- SecureGuard™ Plus compatible

#### Free Apps with support for view on most smart devices

iPhone is a trademark of Apple Inc., registered in the U.S. and other countries.  
Android is a trademark of Google Inc. Blackberry is registered to Blackberry.  
Speco Technologies is constantly developing and improving products.  
We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 1/22/15



#### Optional Accessory



**IRRPTKIT**  
IR Repeater Kit

Model Name	D24GS	D32GS
Video Inputs	8 BNC	16 BNC
Video Outputs	Primary: 1 HDMI, 1 VGA (HD), 1 BNC (SD)	Primary: 1 HDMI, 1 VGA (HD), 1 BNC (SD)
	Secondary: 1 VGA (SD), 1 BNC (SD)	Secondary: 1 VGA (SD), 1 BNC (SD)
	Spot: 1 BNC (8CH)	Spot: 1 BNC (16CH)
Looping Outputs	8 BNC	16 BNC
Display Resolution	HD: 1920 x 1080 . SD: 720 x 480	
RECORD & PLAYBACK		
Compression	H.264	
Recording Rate	240 fps @ CIF / 240 fps @ 2CIF / 240 fps @ D1	480 fps @ CIF / 480 fps @ 2CIF / 480 fps @ D1
Playback Rate	240 fps @ CIF	480 fps @ CIF
Recording Mode	Time-Lapse, Event, Pre-Event (up to 30 min), Panic	
Search Mode	Date/Time, Record Table, Calendar, Event, Motion, Museum	
SYSTEM		
Operating System	Embedded Linux	
Storage	Max. 4 HDD + eSATA	
Data Export	USB (HDD, Flash Drive), SATA DVD_RW	
Data Backup	Archiving, Mirroring	
NETWORK		
Connection	2 x Gigabit Ethernet	
Protocols	Manual, ADSL, DHCP, DVRNS	
Remote Software	Speco Central, Speco Remote (Internal, External)	
Max. Transmission Rate	120 fps @ CIF	
INTERFACE		
Audio In / Out	RCA 8 / 1 + 1 HDMI	RCA 16 / 1 + 1 HDMI
Alarm In / Out	16 / 4	
Serial Interface	RS232, RS485	
External Interface	2 x USB 2.0, eSATA	
User Interface	Front Buttons, Mouse, IR Remote Control, Remote Keyboard (Jog/Shuttle)	
OTHER		
Dimensions (W x H x D)	16.9" (W) x 3.46" (H) x 19.3" (D)	
Operating Temperature	41° F – 104° F	
Operating Humidity	0% – 90%	
Power	AC100 - 240 V- 50/60 Hz, 2.0 - 1.0A	
Approvals	FCC, UL, CE, CB, KCC, KC, PSE	
HYBRID		
Max. Channels	16CH x 2MP	
Supporting Products	ONVIF, OnSIP	
Megapixel Camera Support	Up to 2MP (max 16ch x 2MP under 70ips@2MP capacity)	
Display Rate	CIF: 480ips (NTSC or progressive)	
	2CIF: 240ips (NTSC or progressive)	
	4CIF: 120ips (NTSC or progressive)	
	1MP: 48ips (progressive) (1HD = 2.5 x 4CIF)	
	2MP: 24ips (progressive) (1HD = 5 x 4CIF)	
Playback Rate	CIF: 480ips (NTSC or progressive)	
	2CIF: 240ips (NTSC or progressive)	
	4CIF: 120ips (NTSC or progressive)	
	1MP: 48ips (progressive) (1HD = 2.5 x 4CIF)	
	2MP: 24ips (progressive) (1HD = 5 x 4CIF)	
Recording Rate	CIF: 140ips (NTSC or progressive)	
	2CIF: 130ips (NTSC or progressive)	
	4CIF: 110ips (NTSC or progressive)	
	1.3MP/720p: 110ips (progressive)	
	1080p: 70ips (progressive)	

Please note that specifications and unit exterior design are subject to change without notification.