

TUFGEAR SPRAY

Page: 1

Compilation date: 08/09/2014

Revision No: 5

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: TUFGEAR SPRAY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Open gear lubricant.

1.3. Details of the supplier of the safety data sheet

Company name: ROCOL

	ROCOL House		
	Swillington		
	Leeds		
	West Yorkshire		
	LS26 8BS		
	ENGLAND		
Tel:	+44 (0) 113 232 2700		
Fax:	+44 (0) 113 232 2740		
Email:	customer-service@rocol.com		

1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

Section 2: Hazards identification

2.1. Classification of the sub	2.1. Classification of the substance or mixture					
Classification under CLP: Flam. Aerosol 1: H222; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 3: H412; -						
	H229					
Most important adverse effects:	Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin					
	irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting					
	effects.					

2.2. Label elements

Label elements:	
Hazard statements:	H222: Extremely flammable aerosol.
	H229: Pressurised container: May burst if heated
	H315: Causes skin irritation.
	H336: May cause drowsiness or dizziness.
	H412: Harmful to aquatic life with long lasting effects.
Hazard pictograms:	GHS02: Flame
	GHS07: Exclamation mark

TUFGEAR SPRAY

Signal words: Danger

Precautionary statements:P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P251: Do not pierce or burn, even after use.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition
sources. No smoking.
P211: Do not spray on an open flame or other ignition source.
P285: In case of inadequate ventilation wear respiratory protection.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P264: Wash thoroughly after handling.
P273: Avoid release to the environment.
P332+313: If skin irritation occurs: Get medical advice/attention.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE) - REACH registered number(s): EXEMPT

	EINECS	CAS	PBT / WEL	CLP Classification	Percent			
	270-704-2	68476-85-7	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	50-70%			
F	HYDROCARBONS C7-C9, ISOALKANES - REACH registered number(s): 01-2119471305-42-0000							

921-728-3	-	-	Flam. Liq. 2: H225; Skin Irrit. 2: H315;	10-30%
			Aquatic Chronic 2: H411; STOT SE 3:	
			H336; Asp. Tox. 1: H304	

ACETONE

200-662-2	67-64-1	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319;	2-10%
			STOT SE 3: H336; -: EUH066	

HYDROTREATED LIGHT DISTILLATE (PETROLEUM)

26	65-149-8	64742-47-8	-	Flam. Liq. 3: H226; Skin Irrit. 2: H315;	<2%
				STOT SE 3: H335; Asp. Tox. 1: H304;	
				Aquatic Chronic 2: H411; STOT SE 3:	
				H336	

Section 4: First aid measures

Page: 2

TUFGEAR SPRAY

		Page:	3
4.1. Description of first aid m	leasures		
Skin contact:	Wash immediately with plenty of soap and water.		
Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.		
Ingestion: Wash out mouth with water. Do not induce vomiting. Consult a doctor.			
Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a		
	doctor.		
4.2. Most important sympton	ns and effects, both acute and delayed		
Skin contact:	There may be irritation and redness at the site of contact.		
	There may be irritation and redness. The eyes may water profusely.		
	There may be soreness and redness of the mouth and throat. May cause dizziness.		
_	There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness	5	
	or mental confusion may occur.		
Delayed / immediate effects:			
	ate medical attention and special treatment needed		
	Show this safety data sheet to the doctor in attendance.		
ection 5: Fire-fighting meas	·		
			_
5.1. Extinguishing media			_
Extinguishing media:	Do not use water. Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Use		
	water spray to cool containers.		
5.2. Special hazards arising	rom the substance or mixture		
Exposure hazards:	Extremely flammable. Forms explosive air-vapour mixture. In combustion emits toxic		
	fumes of carbon dioxide / carbon monoxide.		
5.3. Advice for fire-fighters			
Advice for fire-fighters:	Wear self-contained breathing apparatus. Wear protective clothing to prevent contact		
	with skin and eyes.		
ection 6: Accidental release	•		
ection 6. Accidental release			_
6.1. Personal precautions, pr	otective equipment and emergency procedures		
Personal precautions:	Refer to section 8 of SDS for personal protection details. Eliminate all sources of		
	ignition.		
6.2. Environmental precaution	ns		
Environmental precautions:	Do not discharge into drains or rivers.		
6.3. Methods and material fo	r containment and cleaning up		
Clean-up procedures:	Do not use equipment in clean-up procedure which may produce sparks. Absorb into	dry	
••	earth or sand. Transfer to a closable, labelled salvage container for disposal by an	-	

appropriate method.

TUFGEAR SPRAY

6.4. Reference to other sections

Reference to other sections: Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Smoking is forbidden.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition. Keep away from direct sunlight. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No special requirement.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

HYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE)

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL			
UK	1000ppm 1750mg/m3	1250ppm 2180mg/m3	-	-			
HYDROCAR	HYDROCARBONS C7-C9, ISOALKANES						
UK	1400 mg/m3 RCP TWA	-	-	-			
ACETONE							
UK	1210 mg/m3	3620 mg/m3	-	-			

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls				
Engineering measures:	Ensure there is sufficient ventilation of the area. Ensure lighting and electrical			
	equipment are not a source of ignition.			
Respiratory protection:	Respiratory protection not normally required in well ventilated area. In case of insufficient			
	ventilation use: Gas/vapour filter, type A: organic vapours (EN141).			
Hand protection:	Protective gloves. Nitrile gloves.			
Eye protection:	Safety glasses with side-shields.			
Skin protection:	Protective clothing.			
Environmental:	No data available			

TUFGEAR SPRAY

Page: 5

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties				
State:	Aerosol			
Colour:	Black			
Odour:	Characteristic odour			
Evaporation rate:	Fast			
Oxidising:	Non-oxidising (by EC criteria)			
Solubility in water:	Not miscible			
Viscosity:	Non-viscous			
Boiling point/range°C:	< 0 Melting point/range°C:	< -130		
Flammability limits %: lower:	1.8 upper:	9.4		
Flash point°C:	< -100 Autoflammability°C:	> 200		
Vapour pressure:	> 210 Relative density:	< 1		

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Sources of ignition.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong reducing agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

TUFGEAR SPRAY

Hazardous ingredients:

ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3	gm/kg
ORL	RAT	LD50	5800	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. May cause dizziness.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

Delayed / immediate effects: No data available.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

HYDROCARBONS C7-C9, ISOALKANES

Daphnia magna	48H EC50	2.4	mg/l
Pseudokirchneriella	72H ErC50	6.3	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H ErC50	18.4	mg/l

ACETONE

BLUEGILL (Lepomis macrochirus) LC5	250 8300	mg/l
------------------------------------	----------	------

12.2. Persistence and degradability

Persistence and degradability: Only slightly biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Highly volatile. Heavier than air.

TUFGEAR SPRAY

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Harmful to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations:	Transfer to a suitable container and arrange for collection by specialised disposal
	company.
Recovery operations:	No data available
Waste code number:	16 05 05
Disposal of packaging:	Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.
NB:	The user's attention is drawn to the possible existence of regional or national
	regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

Transport class: 2.1

14.4. Packing group

Packing group: n/a

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No data available

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk: No data available.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

TUFGEAR SPRAY

	TUFGEAR SPRAY		
		Page:	8
15.2. Chemical Safety Assess	sment		
Chemical safety assessment:	A chemical safety assessment has not been carried out for the substance or the mixture	;	
	by the supplier.		
Section 16: Other informatio			
	•		
Other information			
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No		
	453/2010.		
	Safety data sheet prepared in accordance with Commission Directive 2008/47/EC of 8		
	April 2008 amending, for the purposes of adapting to technical progress, Council		
	Directive 75/324/EEC relating to aerosol dispensers		
	Compiled in accordance with REACH.		
Phrases used in s.2 and s.3:	EUH066: Repeated exposure may cause skin dryness or cracking.		
	H220: Extremely flammable gas.		
	H222: Extremely flammable aerosol.		
	H225: Highly flammable liquid and vapour.		
	H226: Flammable liquid and vapour.		
	H229: Pressurised container: May burst if heated		
	H280: Contains gas under pressure; may explode if heated.		
	H304: May be fatal if swallowed and enters airways.		
	H315: Causes skin irritation.		
	H319: Causes serious eye irritation.		
	H335: May cause respiratory irritation.		
	H336: May cause drowsiness or dizziness.		
	H411: Toxic to aquatic life with long lasting effects.		
	H412: Harmful to aquatic life with long lasting effects.		
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive		
	and shall be used only as a guide. This company shall not be held liable for any		
	damage resulting from handling or from contact with the above product.		