


## Switched-Mode Power Supply, 1-Phase

EPSITRON® ECO Power



- Primary switch mode power supply unit
- Prepared for class I equipment
- Natural convection cooling when horizontally mounted
- Enclosed for use in switchgear cabinets
- Parallel operation, series connection possible
- Electrically isolated output voltage (SELV) acc. to EN 60950-1/UL 60950

Description	Item No.	Pack. Unit
Switched-Mode Power Supply, 24 VDC / 10 A	787-732	1

Technical Data	
<b>Input:</b>	
Nominal input voltage $V_i$ nom	110 ... 240 VAC
Input voltage range	85 ... 264 VAC; 130 ... 373 VDC
Frequency	47 Hz ... 63 Hz
Input current $I_i$	1.5 A typ. at 230 VAC; 3.0 A at 115 VAC
Discharge current	< 3.5mA
Inrush current	< 30 A
Mains failure hold-up time	> 20 ms at 230 VAC
<b>Output:</b>	
Nominal output voltage $V_o$ nom	24 VDC (SELV)
Output voltage range	22 ... 28 VDC adjustable
Output current $I_o$	10 A at 24 V DC
Factory preset	24 VDC
Adjustment accuracy	1%
Residual ripple	< 100 mV (peak-to-peak) to 20 MHz
Overload behavior	Constant power (in overload range: 1.15 ... 1.4 x $I_o$ ); shutdown and automatic restart in the event of a short circuit
Operational indication	LED green (24 V DC o.k.), LED red (overload)
<b>Efficiency / power losses:</b>	
Efficiency	82 % typ.
Power loss $P_V$	37.5 W (at 230 VAC and 10 ADC)
Max. power loss $P_V$	53 W (at 110 VAC and 11 ADC)
<b>Fuse protection:</b>	
Internal fuse	F 5 A / 250 V
External fuse	Circuit breakers 10 A, 16 A, characteristic: B or C An external DC fuse is required for the DC input voltage

Technical Data	
<b>Environmental requirements:</b>	
Ambient operating temperature	-10 °C ... +70 °C
Storage temperature	-25 °C ... +85 °C
Rel. humidity	95 % (no condensation)
Derating	-2.33 % / K (> 55 °C at 230 VAC)
Degree of pollution	2 (acc. to EN 50178)
Climatic category	3K3 (acc. to EN 60721)
<b>Safety and protection:</b>	
Test voltage pri.-sec./ pri.-gr. / sec.-gr.	3 kV AC / 1.5 kV AC / 0.5 kV AC
Protection class	Prepared for class I equipment
Degree of protection	IP20 acc. to EN 60529
Overvoltage protection	via varistor at primary circuit
Short circuit protection	yes
No-load proof	yes
Feedback voltage	28 VDC
Parallel operation	yes
Series connection	yes
MTBF	480000 h (acc. IEC 61709)
<b>Connection and type of mounting:</b>	
Wire connection	CAGE CLAMP® (WAGO 745 Series)
Cross sections	0.08 mm <sup>2</sup> ... 4 mm <sup>2</sup> / AWG 28 ... 12 (THHN, THWN)
Strip lengths	8 ... 9 mm / 0.33 in
Type of mounting	DIN-rail mount (EN 60715)
<b>Dimensions and weight:</b>	
Dimensions (mm) W x H x L	110 x 92 x 136
Weight	Height from upper-edge of DIN 35 rail 1200 g
<b>Standards and approvals:</b>	
Standards/Specifications	EN 60950, EN 61000-6-2, EN 61000-6-3, UL 60950, UL 508, ANSI/ISA 12.12.01 (Class I Div.2), ATEX, IEC Ex