



# **BP24V36-2US - 2U External 24V Rackmount Battery Pack for select Tripp Lite UPS Systems**

MODEL NUMBER: BP24V36-2US











### Description

BP24V36-2US rackmount external battery pack offers extended battery runtime when used in conjunction with expandable 24V Tripp Lite rackmount UPS systems. Includes heavy gauge cabling with high current DC connector for safe, simple installation. Included daisychain connector enables the connection of additional compatible 24V external battery packs to the host UPS. Included mounting accessories support 2U rackmount installation in 4 post racks. Options for 2-point front-rail mounting, 2 post center-mounting and wallmount installation available.

#### **Highlights**

- Extends the runtime of expandable 24V DC Tripp Lite UPS Systems
- Included daisychain connector supports the addition of multiple compatible external battery packs
- Supports 2U rackmount installation; 4 post installation accessories included
- Options for 2 post rackmount and wallmount installation available

#### **Applications**

 Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems

## **Package Includes**

- BP24V36-2US external battery pack with attached DC cabling
- 4 post compatible rack mounting hardware
- Owner's manual

Compatible with these UPS Systems - SMART750RMXL2U, SU750RTXL2U, SU750RTXLCD2U, SU1000RTXL2UA, S

#### **Features**

- Offers extended-run UPS operation when used in conjunction with compatible 24V DC Tripp Lite UPS systems
- Includes heavy gauge cabling with high current DC connectors for simple installation
- Daisychain connector enables the connection of additional compatible 24V external battery packs to the host UPS
- Included mounting brackets support rackmount installation in 4 post racks using only 2 rack spaces (2U)
- UPDHDEARKIT option supports 2 point front-rail rackmount installation without rear supports
- 2POSTRMKITWM option supports balanced 2 point center-mounting in 2 post equipment racks
- 2POSTRMKITWM option also enables wallmount installation

# **Specifications**

BATTERY	
DC System Voltage (VDC)	24
UPS Connection	Attached cable with red/black 75 amp DC connector





Typical Battery Lifespan	4-6 years typical (North America)	
PHYSICAL		
Installation Form Factors Supported with Included Accessories	4 post 19 inch rackmount	
Installation Form Factors Supported with Optional Accessories	2 post rackmount (2POSTRMKITWM); Wallmount (2POSTRMKITWM); 2-4 post front rail rackmount (UPSHDEARKIT)	
Shipping Dimensions (hwd / in.)	8.5 x 21.5 x 23.2	
Shipping Dimensions (hwd / cm)	21.6 x 54.6 x 58.9	
Shipping Weight (lbs.)	71.1	
Shipping Weight (kg)	32.3	
Unit Dimensions (hwd / in.)	3.4 x 17.3 x 13.8	
Unit Dimensions (hwd / cm)	8.6 x 7.9 x 35	
Unit Weight (lbs.)	59.4	
Unit Weight (kg)	27	
Material of Construction	Steel	
Form Factors Supported	2U Rack/Tower	
WARRANTY		
Product Warranty Period (U.S. & Canada)	2-year limited warranty	
Product Warranty Period (International)	1-year limited warranty	
Product Warranty Period (Mexico)	1-year limited warranty	
Product Warranty Period (Puerto Rico)	1-year limited warranty	
Optional Coverage	3 year, 5 year, next day and on-site warranty coverage available	

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.