

Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com



This product is compliant with Displayport v1.2. It is backward compatible with most Displayport 1.1a equipment running current graphics drivers, with the feature set being limited to that of your equipment (e.g. you may be limited to displaying in Clone / Mirror mode only). Compatibility with older graphics cards is not guaranteed.

2-Port DisplayPort v1,2 Splitter, Multi-Display, 3840 x 2160 4Kx2K UHD 1920x1080 up to 60Hz

MODEL NUMBER: B156-002







Description

Tripp Lite B156-002 allows you to split or expand a DisplayPort signal on two DisplayPort monitors using standard DisplayPort cables (Tripp Lite P580-Series). Ideal for connecting multiple monitors to a single video source for distributing important information at schools, airports and other venues. Display the same image on both monitors, extend the desktop across them, or display in video wall mode, where both monitors are combined to show a single image. Locate the splitter up to 25 ft. from the connected monitors. Supports Ultra High Definition (UHD) 4Kx2K video resolutions up to 3840 x 2160 @ 60Hz. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Features

- Splits or expands a DisplayPort signal to two DisplayPort monitors simultaneously
- Display the same image on both monitors, extend the desktop across them, or display in video wall mode, where both monitors are combined to show a single image
- Locate up to 25 ft. from the connected monitors.
- Supports Ultra High Definition (UHD) 4Kx2K video resolutions up to 3840 x 2160 @ 60Hz
- Supports 48-bit Deep Color (16-bits per channel)
- Supports HDCP, EDID and DDC
- DisplayPort version 1.2
- . Mounting hardware and bracket included for wall-, rack- or pole-mounting
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

Highlights

- Splits or expands a DisplayPort signal to two DisplayPort monitors simultaneously
- Ideal for distributing important information at schools, airports, waiting rooms and other venues
- Video resolutions up to 1920 x
 1080 @ 60Hz, or 3840 x 1080 @
 60Hz in extended mode
- Supports 48-bit Deep Color (16-bits per channel), and HDCP, EDID, and DDC
- DisplayPort version 1.2 compliant

System Requirements

- Computer with Displayport video output; Monitors with Displayport Input
- This product is compliant with
 Displayport v1.2. It is backward
 compatible with most Displayport
 1.1a equipment running current
 graphics drivers, with the feature
 set being limited to that of your
 equipment (e.g. you may be
 limited to displaying in Clone /
 Mirror mode only). Compatibility
 with older graphics cards is not
 quaranteed.

Package Includes

- B156-002 Multi-Display Splitter
 Expander
- Mounting Hardware
- Bracket (for wall-, rack- or pole-mounting)
- External Power Supply (Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 2A)





OVERVIEW	
Display Style	Splitter
Model Type	DisplayPort
Cable Type	CAT6
PHYSICAL	
Unit Dimensions (hwd / in.)	1.00 x 3.60 x 2.52
Unit Weight (lbs.)	1
Color	Black
CONNECTIONS	
Connector A	DISPLAYPORT (FEMALE)
Connector B	DISPLAYPORT (FEMALE) (X2)
Ports	3
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.