

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

2-Port Desktop KVM Switch w/ 2 KVM Cable Kits (PS2)

MODEL NUMBER: B022-002-KT-R



Description

Tripp Lite's B022-002-KT-R 2-port KVM Switch is the optimal solution for controlling 2 computers from one keyboard, mouse and monitor. Installation is a snap - just connect the PCs using the included PS/2 cable kits. P776-Series USB KVM cable kits are available separately for connection of USB computers. Easily switch between computers via front-panel push buttons or keyboard hotkey commands.

Features

- Control 2 computers from a single keyboard, mouse, and monitor
- . Comes with 2 PS/2 KVM cable kits
- P776-Series USB KVM cable kits are available separately for connection of USB computers
- Supports VGA, SVGA, or Multisync monitors
- Easy to install no software required
- Easily select a computer via front-panel push buttons or keyboard hotkeys
- Auto Scan function to monitor computer operation
- · Supports Microsoft IntelliMouse and the scrolling wheel on most mice
- Superior video quality up to 2048x1536; DDC2B
- · External power not required
- Compatible with all major operating systems except Mac and Sun

Specifications

General Info RoHS Y OVERVIEW

Highlights

- Control 2 computers with 1 keyboard, monitor and mouse
- Comes with 2 PS/2 KVM cable kits
- P776-Series USB KVM cable kits are available separately for connection of USB computers
- Simple plug-and-play design
- Ultra-slim design takes up minimal space
- Compatible with all major operating systems except Mac and Sun

System Requirements

- VGA, SVGA or Multisync Monitor with an HD15 port
- PS/2 mouse
- PS/2 keyboard
- PS/2 or USB computer
- Compatible with all major operating systems except Mac and Sun

Package Includes

- B022-002-KT-R 2-port KVM
 Switch
- (x2) PS/2 KVM Cable Kits
- PS/2 console cable kit
- Owner's Manual





Users 1 Console No Port Control Push Buttons, Hotkeys Max CPU 2 PC/Server Connections PS/2 Cat5 KVM Switch No IP Remote Access No Style Desktop PHYSICAL Unit Dimensions (hwd / in.) 1 x 5 x 3.25 Unit Dimensions (hwd / cm) 2.54 x 12.7 x 8.26 Unit Weight (lbs.) 0.73 Unit Weight (kg) 0.33 Color Silver LCD Monitor (in.) Not Applicable CONNECTIONS Ports 2 Included KVM Cable (Equipment HD15 (Male))		
Port Control Push Buttons, Hotkeys Max CPU 2 PC/Server Connections PS/2 Cat5 KVM Switch No IP Remote Access No Style Desktop PHYSICAL Unit Dimensions (hwd / in.) 1 x 5 x 3.25 Unit Dimensions (hwd / cm) 2.54 x 12.7 x 8.26 Unit Weight (lbs.) 0.73 Unit Weight (kg) 0.33 Color Silver LCD Monitor (in.) Not Applicable LCD Monitor (cm) Not Applicable CONNECTIONS Ports 2		
Max CPU 2 PC/Server Connections PS/2 Cat5 KVM Switch No IP Remote Access No Style Desktop PHYSICAL Unit Dimensions (hwd / in.) 1 x 5 x 3.25 Unit Dimensions (hwd / cm) 2.54 x 12.7 x 8.26 Unit Weight (lbs.) 0.73 Unit Weight (kg) 0.33 Color Silver LCD Monitor (in.) Not Applicable LCD Monitor (cm) Not Applicable CONNECTIONS Ports Ports 2		
PC/Server Connections Cat5 KVM Switch IP Remote Access No Style Desktop PHYSICAL Unit Dimensions (hwd / in.) Unit Dimensions (hwd / cm) Unit Weight (lbs.) Unit Weight (kg) Color LCD Monitor (in.) LCD Monitor (cm) PS/2 No No No No 1 x 5 x 3.25 Unit Weight (lbs.) 0.73 Unit Weight (kg) 0.33 Color LCD Monitor (in.) Not Applicable CONNECTIONS Ports 2		
Cat5 KVM Switch IP Remote Access No Style Desktop PHYSICAL Unit Dimensions (hwd / in.) Unit Dimensions (hwd / cm) Unit Weight (lbs.) Unit Weight (kg) Color LCD Monitor (in.) LCD Monitor (cm) Not Applicable CONNECTIONS Ports 2		
IP Remote Access		
Style Desktop PHYSICAL Unit Dimensions (hwd / in.) 1 x 5 x 3.25 Unit Dimensions (hwd / cm) 2.54 x 12.7 x 8.26 Unit Weight (lbs.) 0.73 Unit Weight (kg) 0.33 Color Silver LCD Monitor (in.) Not Applicable LCD Monitor (cm) Not Applicable CONNECTIONS Ports 2		
PHYSICAL Unit Dimensions (hwd / in.) 1 x 5 x 3.25 Unit Dimensions (hwd / cm) 2.54 x 12.7 x 8.26 Unit Weight (lbs.) 0.73 Unit Weight (kg) Color LCD Monitor (in.) LCD Monitor (cm) Not Applicable CONNECTIONS Ports 2		
Unit Dimensions (hwd / in.) 1 x 5 x 3.25 Unit Dimensions (hwd / cm) 2.54 x 12.7 x 8.26 Unit Weight (lbs.) 0.73 Unit Weight (kg) 0.33 Color Silver LCD Monitor (in.) Not Applicable LCD Monitor (cm) Not Applicable CONNECTIONS 2		
Unit Dimensions (hwd / cm) 2.54 x 12.7 x 8.26 Unit Weight (lbs.) 0.73 Unit Weight (kg) 0.33 Color Silver LCD Monitor (in.) Not Applicable LCD Monitor (cm) Not Applicable CONNECTIONS 2		
Unit Weight (lbs.) Unit Weight (kg) Color Silver LCD Monitor (in.) Not Applicable LCD Monitor (cm) Not Applicable CONNECTIONS Ports 2		
Unit Weight (kg) Color Silver LCD Monitor (in.) Not Applicable LCD Monitor (cm) Not Applicable CONNECTIONS Ports 2		
Color Silver LCD Monitor (in.) Not Applicable LCD Monitor (cm) Not Applicable CONNECTIONS Ports 2		
LCD Monitor (in.) LCD Monitor (cm) Not Applicable CONNECTIONS Ports 2		
LCD Monitor (cm) Not Applicable CONNECTIONS Ports 2		
CONNECTIONS Ports 2		
Ports 2		
Leaderdad IO M. Oakla (Farrigues et		
Included KVM Cable (Equipment		
Side) - Connector 1 HD15 (Male)		
Included KVM Cable (Equipment Side) - Connector 2 (x2) MiniDIN6 (Male)		
Local Console Ports - Port 1 HD15 (Female)		
Local Console Ports - Port 2 (x2) MiniDIN6 (Female)		
WARRANTY		
Product Warranty Period (Worldwide) 1-year limited warranty		

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.