



Safety Data Sheet

Copyright, 2015, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	29-9033-1	Version number:	4.00
Revision date:	25/09/2015	Supersedes date:	10/05/2013
Transportation version number: 3.00 (13/05/2015)			

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-100 KIT

Product Identification Numbers

FS-9100-5234-9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Structural adhesive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

29-8932-5, 29-8950-7

TRANSPORTATION INFORMATION

FS-9100-5234-9

Not hazardous for transportation

KIT LABEL

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

WARNING.

Symbols:

GHS07 (Exclamation mark) | GHS09 (Environment) |

Pictograms



HAZARD STATEMENTS:

H319 Causes serious eye irritation.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P280 Wear protective gloves.
P273 Avoid release to the environment.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SUPPLEMENTAL INFORMATION

Supplemental Hazard Statements:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Revision information:

Label: CLP Percent Unknown - Kit information was added.
Company Telephone information was added.
Section 2: H phrase reference information was added.
Label: CLP Classification information was added.
Label: Graphic Text information was deleted.
Label: Graphic information was deleted.
Label: Signal Word information was modified.
Section 2: Label remarks information was deleted.
Section 2: Risk phrase information information was deleted.
Safety phrase information was deleted.



Safety Data Sheet

Copyright, 2015, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	29-8932-5	Version number:	5.00
Revision date:	24/09/2015	Supersedes date:	16/10/2014
Transportation version number:	1.00 (01/09/2011)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-100: Part A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Structural adhesive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

WARNING.

Symbols:

GHS07 (Exclamation mark) |

Pictograms**HAZARD STATEMENTS:**

H319 Causes serious eye irritation.
H315 Causes skin irritation.

PRECAUTIONARY STATEMENTS**Response:**

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Contains 92% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EU Inventory	% by Wt	Classification
Polymercaptan	Trade Secret		80 - 100	
2,4,6-Tris(dimethylaminomethyl)phenol (REACH Reg. No.:01-2119560597-27)	90-72-2	EINECS 202-013-9	5 - 10	Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319 (CLP)
Bis[(dimethylamino)methyl]phenol	71074-89-0	EINECS 275-162-0	0 - 1.5	Acute Tox. 4, H302; Skin Corr. 1B, H314 (Self Classified)

Please see section 16 for the full text of any H statements referred to in this section

Please refer to section 15 for any applicable Notas that have been applied to the above components

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide.

Carbon dioxide.

Oxides of sulphur.

Condition

During combustion.

During combustion.

During combustion.

5.3. Advice for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limits**

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Derived no effect level (DNEL)

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
2,4,6-Tris(dimethylaminomethyl)phenol		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	0.31 mg/m ³

Predicted no effect concentrations (PNEC)

Ingredient	Degradation Product	Compartment	PNEC
2,4,6-Tris(dimethylaminomethyl)phenol		Freshwater	0.84 mg/l

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls

Provide ventilated enclosure for heat curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions.

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-100: Part A

Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Butyl rubber.	No data available	No data available
Nitrile rubber.	No data available	No data available
Polymer laminate	No data available	No data available

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours

For questions about suitability for a specific application, consult with your respirator manufacturer.

8.2.3. Environmental exposure controls

Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Amber liquid
Appearance/Odour	Mercaptan odour; Amber liquid
Odour threshold	<i>No data available.</i>
pH	<i>No data available.</i>
Boiling point/boiling range	<i>No data available.</i>
Melting point	<i>Not applicable.</i>
Flammability (solid, gas)	Not applicable.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	149 °C [<i>Test Method</i> :Closed Cup]
Autoignition temperature	<i>No data available.</i>
Flammable Limits(LEL)	<i>Not applicable.</i>
Flammable Limits(UEL)	<i>Not applicable.</i>
Vapour pressure	<i>Not applicable.</i>
Relative density	1.13 - 1.17 [<i>Ref Std</i> :WATER=1]
Water solubility	<i>No data available.</i>
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Vapour density	<i>Not applicable.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	10 - 17 MPa-s
Density	1.13 - 1.17 kg/m ³

9.2. Other information

Volatile organic compounds (VOC)	<i>Not applicable.</i>
Percent volatile	<= 1 %

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5 Incompatible materials

Strong acids.

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion

May be harmful if swallowed.

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen.

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-100: Part A**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
Polymercaptan	Dermal	Rabbit	LD50 > 10,200 mg/kg
Polymercaptan	Ingestion	Rat	LD50 2,600 mg/kg
2,4,6-Tris(dimethylaminomethyl)phenol	Dermal	Rat	LD50 1,280 mg/kg
2,4,6-Tris(dimethylaminomethyl)phenol	Ingestion	Rat	LD50 1,000 mg/kg
Bis[(dimethylamino)methyl]phenol	Ingestion		LD50 estimated to be 300 - 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
2,4,6-Tris(dimethylaminomethyl)phenol	Rabbit	Corrosive
Bis[(dimethylamino)methyl]phenol	similar compounds	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
2,4,6-Tris(dimethylaminomethyl)phenol	Rabbit	Corrosive
Bis[(dimethylamino)methyl]phenol	similar compounds	Corrosive

Skin Sensitisation

Name	Species	Value
2,4,6-Tris(dimethylaminomethyl)phenol	Guinea pig	Some positive data exist, but the data are not sufficient for classification

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
2,4,6-Tris(dimethylaminomethyl)phenol	In Vitro	Not mutagenic

Carcinogenicity

For the component/components, either no data is currently available or the data is not sufficient for classification.

Reproductive Toxicity**Reproductive and/or Developmental Effects**

For the component/components, either no data is currently available or the data is not sufficient for classification.

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2,4,6-	Inhalation	respiratory irritation	Some positive data exist, but the		NOAEL Not	

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-100: Part A

Tris(dimethylaminomethyl)phenol			data are not sufficient for classification		available	
---------------------------------	--	--	--	--	-----------	--

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2,4,6-Tris(dimethylaminomethyl)phenol	Dermal	skin liver nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 125 mg/kg/day	28 days
2,4,6-Tris(dimethylaminomethyl)phenol	Dermal	auditory system hematopoietic system eyes	All data are negative	Rat	NOAEL 125 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
2,4,6-Tris(dimethylaminomethyl)phenol	90-72-2	Grass Shrimp	Experimental	96 hours	LC50	718 mg/l
2,4,6-Tris(dimethylaminomethyl)phenol	90-72-2	Common Carp	Experimental	96 hours	LC50	175 mg/l
Bis[(dimethylamino)methyl]phenol	71074-89-0		Data not available or insufficient for classification			
Polymercaptan	Trade Secret		Data not available or insufficient for classification			

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Bis[(dimethylamino)methyl]phenol	71074-89-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polymercaptan	Trade Secret	Data not available or	N/A	N/A	N/A	N/A

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-100: Part A

		insufficient for classification				
2,4,6-Tris(dimethylaminomethyl)phenol	90-72-2	Experimental Biodegradation	28 days	BOD	4 % weight	OECD 301D - Closed bottle test

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Polymercaptan	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Bis[(dimethylamino)methyl]phenol	71074-89-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2,4,6-Tris(dimethylaminomethyl)phenol	90-72-2	Experimental Bioconcentration		Log Kow	-0.66	Other methods

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

See Section 11.1 Information on toxicological effects

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

- 08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances
- 20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

ADR/IMDG/IATA: Not hazardous for transport

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information.

15.2. Chemical Safety Assessment

A chemical safety assessment has been carried out for the relevant substances in this material by the registrant in accordance with regulation REGULATION (EC) No 1907/2006

SECTION 16: Other information

List of relevant H statements

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

Revision information:

Industrial Application of Adhesives: Section 16: Annex information was deleted.
Section 2.1: Classification information information was deleted.
Section 2: Additional label requirements phrase information was deleted.
Label: Signal Word information was modified.
Section 3: Composition/ Information of ingredients table information was modified.
Section 3: Reference to H statement explanation in Section 016 information was added.
Section 3: Reference to R and H statement explanation in Section 16 information was deleted.
Section 3: Reference to section 15 for Nota info information was modified.
Section 6: Accidental release personal information information was modified.
Section 8: glove data value information was added.
Section 8: Personal Protection - Skin/hand information information was modified.
Section 8: Skin protection - recommended gloves information information was deleted.
Section 11: Aspiration Hazard text information was added.
Section 11: Carcinogenicity text information was added.
Section 11: Health Effects - Ingestion information information was modified.
Section 11: Respiratory Sensitization text information was added.
Section 11: Specific Target Organ Toxicity - single exposure text information was added.
Section 12: Persistence and Degradability information information was modified.
Section 12:Biocumulative potential information information was modified.
Annex: Prediction of exposure statement information was deleted.
Section 16: List of relevant R phrase information information was deleted.
Section 16: List of relevant R-phrases information was deleted.

Annex

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the

product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M United Kingdom MSDSs are available at www.3M.com/uk



Safety Data Sheet

Copyright, 2015, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	29-8950-7	Version number:	5.00
Revision date:	24/09/2015	Supersedes date:	16/10/2014
Transportation version number:	1.00 (01/09/2011)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-100: part B

REACH registration number: 01-2119456619-26-0025

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Structural adhesive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-100: part B

SIGNAL WORD

WARNING.

Symbols:

GHS07 (Exclamation mark) | GHS09 (Environment) |

Pictograms



Ingredient

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane

CAS Nbr

25068-38-6

% by Wt

100

HAZARD STATEMENTS:

H319 Causes serious eye irritation.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P280E Wear protective gloves.
P273 Avoid release to the environment.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EU Inventory	% by Wt	Classification
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	25068-38-6	NLP 500-033-5	100	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 2, H411 (CLP)

Please see section 16 for the full text of any H statements referred to in this section

Please refer to section 15 for any applicable Notas that have been applied to the above components

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Aldehydes.	During combustion.
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.

5.3. Advice for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing of vapours created during the cure cycle. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from strong bases. Store away from oxidising agents. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Derived no effect level (DNEL)

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	8.3 mg/kg bw/d
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane		Worker	Dermal, Short-term exposure, Systemic effects	8.3 mg/kg
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	12.3 mg/m ³
4,4'-		Worker	Inhalation, Short-term	12.3 mg/m ³

Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane			exposure, Systemic effects	
---	--	--	----------------------------	--

Predicted no effect concentrations (PNEC)

Ingredient	Degradation Product	Compartment	PNEC
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane		Freshwater	0.003 mg/l
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane		Freshwater sediments	0.5 mg/kg w.w.
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane		Intermittent releases to water	0.013 mg/l
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane		Marine water	0.0003 mg/l
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane		Marine water sediments	0.5 mg/kg w.w.
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane		Sewage Treatment Plant	10 mg/l

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls

Provide ventilated enclosure for heat curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)
Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

In case of inadequate ventilation wear respiratory protection. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours

For questions about suitability for a specific application, consult with your respirator manufacturer.

8.2.3. Environmental exposure controls

Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Yellow liquid
Appearance/Odour	Slight odour; Yellow liquid
Odour threshold	<i>No data available.</i>
pH	7
Boiling point/boiling range	≥ 200 °C
Melting point	<i>Not applicable.</i>
Flammability (solid, gas)	Not applicable.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	≥ 150 °C [<i>Test Method</i> : Closed Cup]
Autoignition temperature	<i>No data available.</i>
Flammable Limits(LEL)	<i>Not applicable.</i>
Flammable Limits(UEL)	<i>Not applicable.</i>
Vapour pressure	<i>Not applicable.</i>
Relative density	1.16 [<i>Ref Std</i> : WATER=1]
Water solubility	<i>No data available.</i>
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Vapour density	<i>Not applicable.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	12 - 14 Pa-s [<i>@ 25 °C</i>]

Density 1.16 g/cm³

9.2. Other information

Volatile organic compounds (VOC) *No data available.*
Percent volatile *No data available.*

SECTION 10: Stability and reactivity**10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5 Incompatible materials

Amines.
Strong bases.
Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

No health effects are expected.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-100: part B

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Dermal	Rat	LD50 > 1,600 mg/kg
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Ingestion	Rat	LD50 > 1,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Rabbit	Moderate irritant

Skin Sensitisation

Name	Species	Value
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Human and animal	Sensitising

Respiratory Sensitisation

Name	Species	Value
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Human	Some positive data exist, but the data are not sufficient for classification

Germ Cell Mutagenicity

Name	Route	Value
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	In vivo	Not mutagenic
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
------	-------	-------	---------	-------------	-------------------

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-100: part B

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Ingestion	Not toxic to female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Ingestion	Not toxic to male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Dermal	Not toxic to development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Ingestion	Not toxic to development	Rat	NOAEL 750 mg/kg/day	2 generation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

For the component/components, either no data is currently available or the data is not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Dermal	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	2 years
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Dermal	nervous system	All data are negative	Rat	NOAEL 1,000 mg/kg/day	13 weeks
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	All data are negative	Rat	NOAEL 1,000 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
4,4'-Isopropylidene diphenol, oligomeric	25068-38-6	Ricefish	Experimental	96 hours	LC50	1.41 mg/l

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-100: part B

reaction products with 1-chloro-2,3-epoxypropane						
4,4'-Isopropylidene diphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	25068-38-6	Water flea	Experimental	21 days	NOEC	0.3 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
4,4'-Isopropylidene diphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	25068-38-6	Laboratory Hydrolysis		Hydrolytic half-life	<2 days (t 1/2)	Other methods
4,4'-Isopropylidene diphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	25068-38-6	Laboratory Biodegradation	28 days	BOD	0 % weight	OECD 301C - MITI test (I)

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
4,4'-Isopropylidene diphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	25068-38-6	Laboratory BCF - Other	28 days	Bioaccumulation factor	<42	Other methods

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

See Section 11.1 Information on toxicological effects

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

- 08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances
- 20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

ADR/IMDG/IATA: Not hazardous for transport.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA.

15.2. Chemical Safety Assessment

A chemical safety assessment has been carried out for the relevant substances in this material by the registrant in accordance with regulation REGULATION (EC) No 1907/2006

SECTION 16: Other information

List of relevant H statements

- | | |
|------|--|
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H411 | Toxic to aquatic life with long lasting effects. |

Revision information:

Industrial Mixing and Application: Section 16: Annex information was modified.
Industrial Transfer: Section 16: Annex information was modified.
Section 1: REACH registration number information was added.
Section 2: Additional label requirements phrase information was deleted.
Section 2: Indication of danger information information was deleted.
Label: Graphic Text information was deleted.
Label: Graphic information was deleted.
Label: Signal Word information was modified.
Section 2: Label ingredient information information was deleted.
Section 2: R phrase reference information was deleted.
Risk phrase information was deleted.
Safety phrase information was deleted.
Section 3: Composition/ Information of ingredients table information was modified.
Section 3: Reference to H statement explanation in Section 016 information was added.
Section 3: Reference to R and H statement explanation in Section 16 information was deleted.
Section 3: Reference to section 15 for Nota info information was modified.
Section 6: Accidental release personal information information was modified.
Section 8: DNEL table row information was added.
Section 8: glove data value information was added.
Section 8: Personal Protection - Skin/hand information information was modified.
Section 8: PNEC table row information was added.
Section 8: Skin protection - recommended gloves information information was deleted.
Section 11: Aspiration Hazard text information was added.
Section 11: Health Effects - Skin information information was modified.
Section 11: Reproductive and/or Developmental Effects text information was added.
Section 11: Specific Target Organ Toxicity - single exposure text information was added.
Section 14: Transportation classification information was modified.
Section 16: List of relevant R phrase information information was deleted.
Section 16: List of relevant R-phrases information was deleted.

Annex

1. Title	
Substance identification	CAS Nbr 25068-38-6; EC No. 500-033-5
Free short title	Industrial Mixing and Application
Identified uses	PROC 05, ERC 05, SU 03 ; PROC 13, ERC 05, SU 03 ;
Processes, tasks and activities covered	Mixing and filling processes, by machines and application tools. Hand-mixing of preparations, e.g. plasters, resins, two-component adhesives.
2. Operational conditions and risk management measures	
Operating Conditions	General operating conditions: Duration of exposure per day at workplace [for one worker]: 8 hours/day; Emission days per year: 220 days per year; Local freshwater dilution factor: 10 ; Local marine water dilution factor: 100 ; Used amount or applied quantity per task/application by worker: 3,550 kg per day;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health:

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-100: part B

	Provide extract ventilation to points where emissions occur; Wear chemically resistant gloves (tested to EN374) in combination with ‘basic’ employee training.; Environmental: None needed;
Waste management measures	Discharge to aquatic environment is restricted; Do not apply industrial sludge to natural soils; Prevent discharge of undissolved substance to or recover from wastewater; Sludge should be incinerated, contained or reclaimed;
3. Prediction of exposure	
Prediction of exposure	

1. Title	
Substance identification	CAS Nbr 25068-38-6; EC No. 500-033-5
Free short title	Industrial Transfer
Identified uses	PROC 09, ERC 02, SU 03 ;
Processes, tasks and activities covered	Storage. Transfer of substances/mixtures into large containers e.g. vessels, drums or reservoirs. Transfer of substances/mixtures into small containers e.g. tubes , bottles or small reservoirs.
2. Operational conditions and risk management measures	
Operating Conditions	General operating conditions: Continuous release; Duration of exposure per day at workplace [for one worker]: 8 hours/day; Emission days per year: 225 days per year; Local freshwater dilution factor: 10 ; Local marine water dilution factor: 100 ;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Wear chemically resistant gloves (tested to EN374) in combination with ‘basic’ employee training.; Environmental: None needed;
Waste management measures	Discharge to aquatic environment is restricted; Do not apply industrial sludge to natural soils; Sludge should be incinerated, contained or reclaimed;
3. Prediction of exposure	
Prediction of exposure	

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M United Kingdom MSDSs are available at www.3M.com/uk