

118-04700



Article Number: 118-04700

Outside Serrated Cable Tie, 4" Long, 18lb Tensile Strength, PA66HS, Black, 100/pkg



Download drawing

Download spec sheet

Base Data

Local Order Number	118-04700
Type	T18ROS
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"><li>• Outside serrations minimize damage to cables, while still providing high tensile strength and low insertion force.</li><li>• Contour style head design provides additional space in constrained areas.</li><li>• Heat stabilized material provides excellent resistance to high heat exposures.</li></ul>
Product Description	HellermannTyton outside serrated cable ties are designed with a smooth inside surface to help minimize indentation or damage to wire and cable insulation, while offering high tensile strength and low insertion force. The contour style head takes up less space than traditional style cable ties making it ideal for space constrained areas. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Outside Serrated Cable Tie, 4" Long, 18lb Tensile Strength, PA66HS, Black, 100/pkg

Product Dimensions

Minimum Tensile Strength (Imperial)	18.0 lbs
Minimum Tensile Strength (Metric)	80.0 N
Length L (Imperial)	4.0 "
Length L (Metric)	100.0 mm
Fixation Method	None
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Outside Serrated
Width W (Imperial)	0.1 "
Width W (Metric)	2.5 mm
Height H (Imperial)	0.039 "
Height H (Metric)	1 mm
Bundle Diameter Min. (Imperial)	0.06 "
Bundle Diameter Min. (Metric)	1.6 mm
Bundle Diameter Max. (Imperial)	0.79 "
Bundle Diameter Max. (Metric)	20.0 mm
Thickness T (Imperial)	0.039 "
Cable Tie Head Length (Imperial)	0.2 "
Cable Tie Head Width (Imperial)	0.2 "
Thickness T (Metric)	1 mm

Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	100 Pieces
Carton Quantity	25000 Pieces
Weight (Metric)	0.28 kg

Material and Specifications

Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL94 V2
Halogenfree	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Compliant	Yes
Certification/Specification	PAN6481